

Bearing Insert w/ Set Screw, Narrow Inner Ring - Spherical O.D.

Set Screw Type Bearings - Spherical O.D.

122 items



Select an NTN item number to open its detail page on www.catson.vn.

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
A-AR201-008D1	12,700 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
A-AR202-010D1	15,875 mm	40 mm	22,500 mm	Double Sealed	8.600 N	3.600 N	7.500 RPM	—
A-AR204-012D1	19,050 mm	47 mm	25,500 mm	Double Sealed	14.200 N	6.650 N	5.000 RPM	—
A-AR204-012D1M	19,050 mm	47 mm	25,500 mm	Double Sealed	14.200 N	6.650 N	5.000 RPM	—
A-AR205-014D1	22,225 mm	52 mm	27 mm	Double Sealed	15.500 N	7.850 N	4.450 RPM	—
A-AR205-015D1	23,813 mm	52 mm	27 mm	Double Sealed	15.500 N	7.850 N	4.450 RPM	—
A-AR205D1	25 mm	52 mm	27 mm	Double Sealed	15.500 N	7.850 N	4.450 RPM	—
A-AR206-102D1M	28,575 mm	61,999 mm	30 mm	Double Sealed	21.600 N	11.300 N	3.650 RPM	—
A-AR210-114D1	47,625 mm	90 mm	43 mm	Double Sealed	39.000 N	23.200 N	2.350 RPM	—
A-AR211-203D1M	53,975 mm	100 mm	43 mm	Double Sealed	48.000 N	29.200 N	2.150 RPM	—
A-AS201-008D1	12,700 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
A-AS202-010D1	15,875 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
A-AS205-100D1	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR201	12 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
AR201-008	12,700 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
AR202	15 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AR202-009	14,288 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
AR202-010	15,875 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AR203	17 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	8.000 RPM	—
AR203-011	17,463 mm	40 mm	22,500 mm	Double Sealed	9.600 N	4.600 N	8.000 RPM	—
AR204	20 mm	47 mm	25,500 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
AR204-012	19,050 mm	47 mm	25,500 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
AR205	25 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR205-013	20,638 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR205-014	22,225 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR205-015	23,813 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR205-100	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR205-100D1W2V4	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AR206	30 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AR206-101	26,988 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AR206-102	28,575 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AR206-103	30,163 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AR206-104	31,750 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AR207	35 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AR207-104	31,750 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AR207-105	33,338 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AR207-106	34,925 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AR207-107	36,513 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AR208	40 mm	80 mm	40 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AR208-108	38,100 mm	80 mm	40 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AR208-109	39,688 mm	80 mm	40 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AS201	12 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
AS201-008	12,700 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
AS201-008D1	12,700 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
AS201-008HT2-A3	12,700 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	—	—
AS201D1	12 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	11.000 RPM	—
AS202	15 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AS202-009	14,288 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AS202-009D1	14,288 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AS202-010	15,875 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AS202-010D1	15,875 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AS202D1	15 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	10.000 RPM	—
AS203	17 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	8.000 RPM	—
AS203-011	17,463 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	8.000 RPM	—
AS203-011D1	17,463 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	8.000 RPM	—
AS203D1	17 mm	40 mm	22 mm	Double Sealed	9.600 N	4.600 N	8.000 RPM	—
AS204	20 mm	47 mm	25 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
AS204-012	19,050 mm	47 mm	25 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
AS204-012D1	19,050 mm	47 mm	25 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
AS204D1	20 mm	47 mm	25 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
AS205	25 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-013	20,638 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-013D1	20,638 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-014	22,225 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-014D1	22,225 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-015	23,813 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-015D1	23,813 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-100	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-100D1	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205-100D1V14	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
AS205D1	25 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
AS206	30 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-101	26,988 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-101D1	26,988 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-102	28,575 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-102D1	28,575 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-103	30,163 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-103D1	30,163 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-104	31,750 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-104D1	31,750 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS206-104FG1	31,750 mm	62 mm	29 mm	Double Sealed	21.600 N	11.300 N	3.650 RPM	—
AS206D1	30 mm	62 mm	29 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
AS207	35 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-104	31,750 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-104D1	31,750 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-105	33,338 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-105D1	33,338 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-106	34,925 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-106D1	34,925 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-107	36,513 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207-107D1	36,513 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS207D1	35 mm	72 mm	34 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
AS208	40 mm	80 mm	38 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AS208-108	38,100 mm	80 mm	38 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AS208-108D1	38,100 mm	80 mm	38 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AS208-109	39,688 mm	80 mm	38 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AS208D1	40 mm	80 mm	38 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
AS209D1	45 mm	85 mm	40 mm	Double Sealed	32.700 N	20.500 N	—	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
AS210D1	50 mm	90 mm	42 mm	Double Sealed	35.000 N	23.200 N	—	—
SNPS008RR	12,700 mm	40 mm	22,500 mm	Double Sealed	6.090 N	2.730 N	11.000 RPM	—
SNPS010RR	15,875 mm	40 mm	22,500 mm	Double Sealed	7.730 N	3.580 N	10.000 RPM	—
SNPS012RR	19,050 mm	47 mm	27 mm	Double Sealed	12.800 N	6.650 N	6.700 RPM	—
SNPS013RR	20,638 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
SNPS014RR	22,225 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
SNPS015RR	23,813 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
SNPS100RR	25,400 mm	52 mm	27 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
SNPS102RR	28,575 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
SNPS103RR	30,163 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
SNPS103RR2	31,750 mm	62 mm	30 mm	Double Sealed	19.500 N	11.300 N	4.900 RPM	—
SNPS104RR	31,750 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
SNPS105RR	33,338 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
SNPS106RR	34,925 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
SNPS107RR	36,513 mm	72 mm	35 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
SNPS108RR	38,100 mm	80 mm	40 mm	Double Sealed	29.100 N	17.800 N	3.700 RPM	—
SNPS110RR	41,275 mm	85 mm	41,500 mm	Double Sealed	32.500 N	20.400 N	3.500 RPM	—
SNPS112RR	44,450 mm	85 mm	41,500 mm	Double Sealed	32.500 N	20.400 N	3.500 RPM	—
SNPS114RR	47,625 mm	90 mm	43 mm	Double Sealed	35.000 N	23.200 N	3.100 RPM	—
SNPS115RR	49,213 mm	90 mm	43 mm	Double Sealed	35.000 N	23.200 N	3.100 RPM	—
SNPS115RR2	50,800 mm	90 mm	43 mm	Double Sealed	35.000 N	23.200 N	3.100 RPM	—
SNPS200RR	50,800 mm	100 mm	43 mm	Double Sealed	7.550 N	3.350 N	2.850 RPM	—
SNPS202RR	53,975 mm	100 mm	43 mm	Double Sealed	—	—	—	—
SNPS203RR	55,562 mm	100 mm	43 mm	Double Sealed	7.550 N	3.350 N	2.850 RPM	—

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn
Phone: +84 28 3820 8888
Fax: +84 28 3826 8888

