

## Clearance-Adjustable Needle Roller Bearing w/o Inner Ring

Clearance-Adjustable Needle Roller Bearings w/o Inner Ring

17 items



Select an NTN item number to open its detail page on [www.catson.vn](http://www.catson.vn).

| Item                      | d | D      | B     | Type | Dynamic  | Static    | Grease    | Oil        |
|---------------------------|---|--------|-------|------|----------|-----------|-----------|------------|
| <a href="#">RNA4906S</a>  | — | 47 mm  | 17 mm | Open | 14.900 N | 21.600 N  | 7.300 RPM | 11.000 RPM |
| <a href="#">RNA4907S</a>  | — | 55 mm  | 20 mm | Open | 32.000 N | 50.000 N  | 6.500 RPM | 9.500 RPM  |
| <a href="#">RNA4908S</a>  | — | 62 mm  | 22 mm | Open | 22.500 N | 40.500 N  | 5.700 RPM | 8.500 RPM  |
| <a href="#">RNA4909S</a>  | — | 68 mm  | 22 mm | Open | 23.100 N | 43.500 N  | 5.000 RPM | 7.500 RPM  |
| <a href="#">RNA4910S</a>  | — | 72 mm  | 22 mm | Open | 24.700 N | 49.000 N  | 4.700 RPM | 7.000 RPM  |
| <a href="#">RNA4911S</a>  | — | 80 mm  | 25 mm | Open | 33.000 N | 65.500 N  | 4.300 RPM | 6.500 RPM  |
| <a href="#">RNA4912S</a>  | — | 85 mm  | 25 mm | Open | 34.000 N | 69.000 N  | 4.000 RPM | 6.000 RPM  |
| <a href="#">RNA4913S</a>  | — | 90 mm  | 25 mm | Open | 34.000 N | 70.500 N  | 3.700 RPM | 5.500 RPM  |
| <a href="#">RNA4914S</a>  | — | 100 mm | 30 mm | Open | 44.500 N | 94.000 N  | 3.300 RPM | 5.000 RPM  |
| <a href="#">RNA4915S</a>  | — | 105 mm | 30 mm | Open | 45.500 N | 99.000 N  | 3.100 RPM | 4.700 RPM  |
| <a href="#">RNA4916S</a>  | — | 110 mm | 30 mm | Open | 46.500 N | 104.000 N | 2.900 RPM | 4.400 RPM  |
| <a href="#">RNA4917S</a>  | — | 120 mm | 35 mm | Open | 57.000 N | 140.000 N | 2.700 RPM | 4.000 RPM  |
| <a href="#">RNA4918S</a>  | — | 125 mm | 35 mm | Open | 58.500 N | 146.000 N | 2.500 RPM | 3.800 RPM  |
| <a href="#">RNA4919S</a>  | — | 130 mm | 35 mm | Open | 59.500 N | 152.000 N | 2.400 RPM | 3.600 RPM  |
| <a href="#">RNA4920S</a>  | — | 140 mm | 40 mm | Open | 72.000 N | 168.000 N | 2.300 RPM | 3.500 RPM  |
| <a href="#">RNA4922S</a>  | — | 150 mm | 40 mm | Open | 75.500 N | 184.000 N | 2.100 RPM | 3.200 RPM  |
| <a href="#">RNA49-32S</a> | — | 52 mm  | 20 mm | Open | 17.600 N | 27.800 N  | 6.700 RPM | 10.000 RPM |

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

