

Single Direction Thrust Ball Bearings

Single Direction Thrust Ball Bearings

278 mã sản phẩm



Nhập vào mã NTN để mở trang chi tiết trên www.catson.vn.

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
2900	10 mm	—	—	Open	12.700 N	17.100 N	—	—
2901	12 mm	—	—	Open	13.100 N	18.900 N	—	—
2902	15 mm	—	—	Open	14.200 N	22.900 N	—	—
2903	18 mm	—	—	Open	14.500 N	24.700 N	—	—
2904	22 mm	—	—	Open	11.390 N	21.130 N	—	—
2905	25 mm	—	—	Open	19.300 N	37.100 N	—	—
2906	30 mm	—	—	Open	20.200 N	42.300 N	—	—
2907	35 mm	—	—	Open	29.800 N	62.300 N	—	—
2908	40 mm	—	—	Open	31.400 N	69.800 N	—	—
2909	45 mm	—	—	Open	32.200 N	77.400 N	—	—
2910	50 mm	—	—	Open	42.900 N	93.900 N	—	—
2911	55 mm	—	—	Open	40.000 N	103.200 N	—	—
2912	60 mm	—	—	Open	40.500 N	108.100 N	—	—
2913	65 mm	—	—	Open	47.100 N	128.600 N	—	—
2914	70 mm	—	—	Open	48.900 N	140.100 N	—	—
2915	75 mm	—	—	Open	50.700 N	151.200 N	—	—
2916	80 mm	—	—	Open	57.400 N	171.200 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
2917	85 mm	—	—	Open	59.200 N	184.600 N	—	—
2918	90 mm	—	—	Open	59.600 N	189.000 N	—	—
2919	95 mm	—	—	Open	55.600 N	177.900 N	—	—
2920	100 mm	—	—	Open	85.000 N	269.100 N	—	—
2922	110 mm	—	—	Open	87.000 N	287.000 N	—	—
2924-1	120 mm	—	—	Open	98.300 N	335.800 N	—	—
51100	10 mm	24 mm	—	Open	10.000 N	14.000 N	6.700 RPM	9.500 RPM
51100C3	10 mm	24 mm	—	Open	10.000 N	14.000 N	6.700 RPM	9.500 RPM
51101	12 mm	26 mm	—	Open	10.300 N	15.400 N	6.400 RPM	9.200 RPM
51101C3	12 mm	26 mm	—	Open	10.300 N	15.400 N	6.400 RPM	9.200 RPM
51102	15 mm	28 mm	—	Open	10.500 N	16.800 N	6.200 RPM	8.800 RPM
51102C3	15 mm	28 mm	—	Open	10.500 N	16.800 N	6.200 RPM	8.800 RPM
51103	17 mm	30 mm	—	Open	10.800 N	18.200 N	6.000 RPM	8.500 RPM
51103C3	17 mm	30 mm	—	Open	10.800 N	18.200 N	6.000 RPM	8.500 RPM
51104	20 mm	35 mm	—	Open	14.200 N	24.700 N	5.200 RPM	7.500 RPM
51104C3	20 mm	35 mm	—	Open	14.200 N	24.700 N	5.200 RPM	7.500 RPM
51105	25 mm	42 mm	—	Open	19.600 N	37.000 N	4.600 RPM	6.500 RPM
51105C3	25 mm	42 mm	—	Open	19.600 N	37.000 N	4.600 RPM	6.500 RPM
51105YP5	25 mm	42 mm	—	Open	19.600 N	37.000 N	4.600 RPM	6.500 RPM
51106	30 mm	47 mm	—	Open	20.400 N	42.000 N	4.300 RPM	6.200 RPM
51106C3	30 mm	47 mm	—	Open	20.400 N	42.000 N	4.300 RPM	6.200 RPM
51107	35 mm	52 mm	—	Open	20.400 N	44.500 N	3.900 RPM	5.600 RPM
51107C3	35 mm	52 mm	—	Open	20.400 N	44.500 N	3.900 RPM	5.600 RPM
51107YP5	35 mm	52 mm	—	Open	20.400 N	44.500 N	3.900 RPM	5.600 RPM
51108	40 mm	60 mm	—	Open	26.900 N	63.000 N	3.500 RPM	5.000 RPM
51108C3	40 mm	60 mm	—	Open	26.900 N	63.000 N	3.500 RPM	5.000 RPM
51109	45 mm	65 mm	—	Open	27.900 N	69.000 N	3.200 RPM	4.600 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51109C3	45 mm	65 mm	—	Open	27.900 N	69.000 N	3.200 RPM	4.600 RPM
51110	50 mm	70 mm	—	Open	28.800 N	75.500 N	3.100 RPM	4.500 RPM
51110C3	50 mm	70 mm	—	Open	28.800 N	75.500 N	3.100 RPM	4.500 RPM
51111	55 mm	78 mm	—	Open	35.000 N	93.000 N	2.800 RPM	4.000 RPM
51111C3	55 mm	78 mm	—	Open	35.000 N	93.000 N	2.800 RPM	4.000 RPM
51112	60 mm	85 mm	—	Open	41.500 N	113.000 N	2.600 RPM	3.700 RPM
51112C3	60 mm	85 mm	—	Open	41.500 N	113.000 N	2.600 RPM	3.700 RPM
51112PX2	60 mm	85 mm	—	Open	41.500 N	113.000 N	2.600 RPM	3.700 RPM
51113	65 mm	90 mm	—	Open	41.500 N	117.000 N	2.400 RPM	3.500 RPM
51113C3	65 mm	90 mm	—	Open	41.500 N	117.000 N	2.400 RPM	3.500 RPM
51114	70 mm	95 mm	—	Open	43.000 N	127.000 N	2.400 RPM	3.400 RPM
51114C3	70 mm	95 mm	—	Open	43.000 N	127.000 N	2.400 RPM	3.400 RPM
51114YP5	70 mm	95 mm	—	Open	43.000 N	127.000 N	2.400 RPM	3.400 RPM
51115	75 mm	100 mm	—	Open	44.500 N	136.000 N	2.200 RPM	3.200 RPM
51115C3	75 mm	100 mm	—	Open	44.500 N	136.000 N	2.200 RPM	3.200 RPM
51116	80 mm	105 mm	—	Open	44.500 N	141.000 N	2.200 RPM	3.100 RPM
51116C3	80 mm	105 mm	—	Open	44.500 N	141.000 N	2.200 RPM	3.100 RPM
51117	85 mm	110 mm	—	Open	46.000 N	150.000 N	2.100 RPM	3.000 RPM
51117C3	85 mm	110 mm	—	Open	46.000 N	150.000 N	2.100 RPM	3.000 RPM
51118	90 mm	120 mm	—	Open	59.500 N	190.000 N	1.900 RPM	2.700 RPM
51118C3	90 mm	120 mm	—	Open	59.500 N	190.000 N	1.900 RPM	2.700 RPM
51120	100 mm	135 mm	—	Open	85.000 N	268.000 N	1.700 RPM	2.400 RPM
51120C3	100 mm	135 mm	—	Open	85.000 N	268.000 N	1.700 RPM	2.400 RPM
51122	110 mm	145 mm	—	Open	87.000 N	288.000 N	1.600 RPM	2.300 RPM
51122C3	110 mm	145 mm	—	Open	87.000 N	288.000 N	1.600 RPM	2.300 RPM
51124	120 mm	155 mm	—	Open	89.000 N	310.000 N	1.500 RPM	2.200 RPM
51124C3	120 mm	155 mm	—	Open	89.000 N	310.000 N	1.500 RPM	2.200 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51126	130 mm	170 mm	—	Open	104.000 N	350.000 N	1.300 RPM	1.900 RPM
51126C3	130 mm	170 mm	—	Open	104.000 N	350.000 N	1.300 RPM	1.900 RPM
51128	140 mm	180 mm	—	Open	107.000 N	375.000 N	1.300 RPM	1.800 RPM
51128C3	140 mm	180 mm	—	Open	107.000 N	375.000 N	1.300 RPM	1.800 RPM
51128L1P5	140 mm	180 mm	—	Open	107.000 N	375.000 N	1.300 RPM	1.800 RPM
51130	150 mm	190 mm	—	Open	109.000 N	400.000 N	1.200 RPM	1.800 RPM
51130C3	150 mm	190 mm	—	Open	109.000 N	400.000 N	1.200 RPM	1.800 RPM
51132	160 mm	200 mm	—	Open	112.000 N	425.000 N	1.200 RPM	1.700 RPM
51132C3	160 mm	200 mm	—	Open	112.000 N	425.000 N	1.200 RPM	1.700 RPM
51134	170 mm	215 mm	—	Open	134.000 N	510.000 N	1.100 RPM	1.600 RPM
51134C3	170 mm	215 mm	—	Open	134.000 N	510.000 N	1.100 RPM	1.600 RPM
51136	180 mm	225 mm	—	Open	135.000 N	525.000 N	1.100 RPM	1.500 RPM
51136C3	180 mm	225 mm	—	Open	135.000 N	525.000 N	1.100 RPM	1.500 RPM
51138	190 mm	240 mm	—	Open	170.000 N	655.000 N	980 RPM	1.400 RPM
51138C3	190 mm	240 mm	—	Open	170.000 N	655.000 N	980 RPM	1.400 RPM
51140	200 mm	250 mm	—	Open	172.000 N	675.000 N	960 RPM	1.400 RPM
51140C3	200 mm	250 mm	—	Open	172.000 N	675.000 N	960 RPM	1.400 RPM
51144	220 mm	270 mm	—	Open	177.000 N	740.000 N	920 RPM	1.300 RPM
51144C3	220 mm	270 mm	—	Open	177.000 N	740.000 N	920 RPM	1.300 RPM
51148	240 mm	300 mm	—	Open	228.000 N	935.000 N	780 RPM	1.100 RPM
51148C3	240 mm	300 mm	—	Open	228.000 N	935.000 N	780 RPM	1.100 RPM
511-500	500 mm	600 mm	—	Open	58.500 N	345.000 N	370 RPM	540 RPM
511-500C3	500 mm	600 mm	—	Open	58.500 N	345.000 N	370 RPM	540 RPM
51152	260 mm	320 mm	—	Open	232.000 N	990.000 N	750 RPM	1.100 RPM
51152C3	260 mm	320 mm	—	Open	232.000 N	990.000 N	750 RPM	1.100 RPM
511-530	530 mm	640 mm	—	Open	645.000 N	4.000.000 N	350 RPM	500 RPM
511-530C3	530 mm	640 mm	—	Open	645.000 N	4.000.000 N	350 RPM	500 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
51156	280 mm	350 mm	—	Open	305.000 N	1.270.000 N	650 RPM	940 RPM
51156C3	280 mm	350 mm	—	Open	305.000 N	1.270.000 N	650 RPM	940 RPM
51160	300 mm	380 mm	—	Open	355.000 N	1.560.000 N	580 RPM	820 RPM
51160C3	300 mm	380 mm	—	Open	355.000 N	1.560.000 N	580 RPM	820 RPM
51164	320 mm	400 mm	—	Open	365.000 N	1.660.000 N	550 RPM	790 RPM
51164C3	320 mm	400 mm	—	Open	365.000 N	1.660.000 N	550 RPM	790 RPM
51168	340 mm	420 mm	—	Open	375.000 N	1.760.000 N	530 RPM	760 RPM
51168C3	340 mm	420 mm	—	Open	375.000 N	1.760.000 N	530 RPM	760 RPM
51172	360 mm	440 mm	—	Open	380.000 N	1.860.000 N	510 RPM	730 RPM
51172C3	360 mm	440 mm	—	Open	380.000 N	1.860.000 N	510 RPM	730 RPM
51176	380 mm	460 mm	—	Open	380.000 N	1.910.000 N	500 RPM	710 RPM
51176C3	380 mm	460 mm	—	Open	380.000 N	1.910.000 N	500 RPM	710 RPM
51180	400 mm	480 mm	—	Open	390.000 N	2.010.000 N	480 RPM	690 RPM
51180C3	400 mm	480 mm	—	Open	390.000 N	2.010.000 N	480 RPM	690 RPM
51184	420 mm	500 mm	—	Open	395.000 N	2.110.000 N	470 RPM	670 RPM
51184C3	420 mm	500 mm	—	Open	395.000 N	2.110.000 N	470 RPM	670 RPM
51188	440 mm	540 mm	—	Open	515.000 N	2.850.000 N	400 RPM	580 RPM
51188C3	440 mm	540 mm	—	Open	515.000 N	2.850.000 N	400 RPM	580 RPM
51192	460 mm	560 mm	—	Open	525.000 N	3.000.000 N	390 RPM	560 RPM
51192C3	460 mm	560 mm	—	Open	525.000 N	3.000.000 N	390 RPM	560 RPM
51196	480 mm	580 mm	—	Open	525.000 N	3.100.000 N	380 RPM	550 RPM
51196C3	480 mm	580 mm	—	Open	525.000 N	3.100.000 N	380 RPM	550 RPM
51200	10 mm	26 mm	—	Open	12.700 N	17.100 N	5.800 RPM	8.300 RPM
51200C3	10 mm	26 mm	—	Open	12.700 N	17.100 N	5.800 RPM	8.300 RPM
51201	12 mm	28 mm	—	Open	13.200 N	19.000 N	5.600 RPM	8.000 RPM
51201C3	12 mm	28 mm	—	Open	13.200 N	19.000 N	5.600 RPM	8.000 RPM
51202	15 mm	32 mm	—	Open	16.600 N	24.800 N	5.000 RPM	7.100 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51202C3	15 mm	32 mm	—	Open	16.600 N	24.800 N	5.000 RPM	7.100 RPM
51203	17 mm	35 mm	—	Open	17.200 N	27.300 N	4.800 RPM	6.800 RPM
51203C3	17 mm	35 mm	—	Open	17.200 N	27.300 N	4.800 RPM	6.800 RPM
51204	20 mm	40 mm	—	Open	22.300 N	37.500 N	4.100 RPM	5.900 RPM
51204C3	20 mm	40 mm	—	Open	22.300 N	37.500 N	4.100 RPM	5.900 RPM
51205	25 mm	47 mm	—	Open	27.800 N	50.500 N	3.700 RPM	5.300 RPM
51205C3	25 mm	47 mm	—	Open	27.800 N	50.500 N	3.700 RPM	5.300 RPM
51205YP5	25 mm	47 mm	—	Open	27.800 N	50.500 N	3.700 RPM	5.300 RPM
51206	30 mm	52 mm	—	Open	29.300 N	58.000 N	3.400 RPM	4.900 RPM
51206C3	30 mm	52 mm	—	Open	29.300 N	58.000 N	3.400 RPM	4.900 RPM
51206YP5	30 mm	52 mm	—	Open	29.300 N	58.000 N	3.400 RPM	4.900 RPM
51207	35 mm	62 mm	—	Open	39.000 N	78.000 N	2.900 RPM	4.200 RPM
51207C3	35 mm	62 mm	—	Open	39.000 N	78.000 N	2.900 RPM	4.200 RPM
51208	40 mm	68 mm	—	Open	47.000 N	98.500 N	2.700 RPM	3.900 RPM
51208C3	40 mm	68 mm	—	Open	47.000 N	98.500 N	2.700 RPM	3.900 RPM
51208YP5	40 mm	68 mm	—	Open	47.000 N	98.500 N	2.700 RPM	3.900 RPM
51209	45 mm	73 mm	—	Open	48.000 N	105.000 N	2.600 RPM	3.700 RPM
51209C3	45 mm	73 mm	—	Open	48.000 N	105.000 N	2.600 RPM	3.700 RPM
51209YP4	45 mm	73 mm	—	Open	48.000 N	105.000 N	2.600 RPM	3.700 RPM
51209YP5	45 mm	73 mm	—	Open	48.000 N	105.000 N	2.600 RPM	3.700 RPM
51210	50 mm	78 mm	—	Open	48.500 N	111.000 N	2.400 RPM	3.400 RPM
51210C3	50 mm	78 mm	—	Open	48.500 N	111.000 N	2.400 RPM	3.400 RPM
51211	55 mm	90 mm	—	Open	69.500 N	159.000 N	2.100 RPM	3.000 RPM
51211C3	55 mm	90 mm	—	Open	69.500 N	159.000 N	2.100 RPM	3.000 RPM
51212	60 mm	95 mm	—	Open	73.500 N	179.000 N	2.000 RPM	2.800 RPM
51212C3	60 mm	95 mm	—	Open	73.500 N	179.000 N	2.000 RPM	2.800 RPM
51213	65 mm	100 mm	—	Open	75.000 N	189.000 N	1.900 RPM	2.700 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51213C3	65 mm	100 mm	—	Open	75.000 N	189.000 N	1.900 RPM	2.700 RPM
51214	70 mm	105 mm	—	Open	76.000 N	199.000 N	1.800 RPM	2.600 RPM
51214C3	70 mm	105 mm	—	Open	76.000 N	199.000 N	1.800 RPM	2.600 RPM
51215	75 mm	110 mm	—	Open	77.500 N	209.000 N	1.800 RPM	2.600 RPM
51215C3	75 mm	110 mm	—	Open	77.500 N	209.000 N	1.800 RPM	2.600 RPM
51216	80 mm	115 mm	—	Open	78.500 N	218.000 N	1.700 RPM	2.400 RPM
51216C3	80 mm	115 mm	—	Open	78.500 N	218.000 N	1.700 RPM	2.400 RPM
51217	85 mm	125 mm	—	Open	95.500 N	264.000 N	1.600 RPM	2.200 RPM
51217C3	85 mm	125 mm	—	Open	95.500 N	264.000 N	1.600 RPM	2.200 RPM
51218	90 mm	135 mm	—	Open	117.000 N	325.000 N	1.400 RPM	2.000 RPM
51218C3	90 mm	135 mm	—	Open	117.000 N	325.000 N	1.400 RPM	2.000 RPM
51220	100 mm	150 mm	—	Open	147.000 N	410.000 N	1.300 RPM	1.800 RPM
51220C3	100 mm	150 mm	—	Open	147.000 N	410.000 N	1.300 RPM	1.800 RPM
51222	110 mm	160 mm	—	Open	153.000 N	450.000 N	1.200 RPM	1.800 RPM
51222C3	110 mm	160 mm	—	Open	153.000 N	450.000 N	1.200 RPM	1.800 RPM
51224	120 mm	170 mm	—	Open	154.000 N	470.000 N	1.200 RPM	1.700 RPM
51224C3	120 mm	170 mm	—	Open	154.000 N	470.000 N	1.200 RPM	1.700 RPM
51226	130 mm	190 mm	—	Open	191.000 N	565.000 N	1.000 RPM	1.500 RPM
51226C3	130 mm	190 mm	—	Open	191.000 N	565.000 N	1.000 RPM	1.500 RPM
51228	140 mm	200 mm	—	Open	193.000 N	595.000 N	980 RPM	1.400 RPM
51228C3	140 mm	200 mm	—	Open	193.000 N	595.000 N	980 RPM	1.400 RPM
51230	150 mm	215 mm	—	Open	220.000 N	685.000 N	900 RPM	1.300 RPM
51230C3	150 mm	215 mm	—	Open	220.000 N	685.000 N	900 RPM	1.300 RPM
51232	160 mm	225 mm	—	Open	223.000 N	720.000 N	870 RPM	1.200 RPM
51232C3	160 mm	225 mm	—	Open	223.000 N	720.000 N	870 RPM	1.200 RPM
51234	170 mm	240 mm	—	Open	261.000 N	835.000 N	810 RPM	1.200 RPM
51234C3	170 mm	240 mm	—	Open	261.000 N	835.000 N	810 RPM	1.200 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51236	180 mm	250 mm	—	Open	266.000 N	875.000 N	780 RPM	1.100 RPM
51236C3	180 mm	250 mm	—	Open	266.000 N	875.000 N	780 RPM	1.100 RPM
51238	190 mm	270 mm	—	Open	310.000 N	1.060.000 N	710 RPM	1.000 RPM
51238C3	190 mm	270 mm	—	Open	310.000 N	1.060.000 N	710 RPM	1.000 RPM
51240	200 mm	280 mm	—	Open	315.000 N	1.110.000 N	700 RPM	990 RPM
51240C3	200 mm	280 mm	—	Open	315.000 N	1.110.000 N	700 RPM	990 RPM
51244	220 mm	300 mm	—	Open	325.000 N	1.210.000 N	660 RPM	950 RPM
51244C3	220 mm	300 mm	—	Open	325.000 N	1.210.000 N	660 RPM	950 RPM
51248	240 mm	340 mm	—	Open	415.000 N	1.650.000 N	550 RPM	790 RPM
51248C3	240 mm	340 mm	—	Open	415.000 N	1.650.000 N	550 RPM	790 RPM
51252	260 mm	360 mm	—	Open	440.000 N	1.810.000 N	530 RPM	760 RPM
51252C3	260 mm	360 mm	—	Open	440.000 N	1.810.000 N	530 RPM	760 RPM
51256	280 mm	380 mm	—	Open	460.000 N	1.970.000 N	510 RPM	730 RPM
51256C3	280 mm	380 mm	—	Open	460.000 N	1.970.000 N	510 RPM	730 RPM
51260	300 mm	420 mm	—	Open	590.000 N	2.680.000 N	440 RPM	630 RPM
51260C3	300 mm	420 mm	—	Open	590.000 N	2.680.000 N	440 RPM	630 RPM
51268	340 mm	460 mm	—	Open	605.000 N	2.920.000 N	—	—
51305	25 mm	52 mm	—	Open	35.500 N	61.500 N	3.200 RPM	4.600 RPM
51305C3	25 mm	52 mm	—	Open	35.500 N	61.500 N	3.200 RPM	4.600 RPM
51306	30 mm	60 mm	—	Open	43.000 N	78.500 N	2.800 RPM	3.900 RPM
51306C3	30 mm	60 mm	—	Open	43.000 N	78.500 N	2.800 RPM	3.900 RPM
51307	35 mm	68 mm	—	Open	55.500 N	105.000 N	2.400 RPM	3.500 RPM
51307C3	35 mm	68 mm	—	Open	55.500 N	105.000 N	2.400 RPM	3.500 RPM
51308	40 mm	78 mm	—	Open	69.000 N	135.000 N	2.200 RPM	3.100 RPM
51308C3	40 mm	78 mm	—	Open	69.000 N	135.000 N	2.200 RPM	3.100 RPM
51308P5	40 mm	78 mm	—	Open	69.000 N	135.000 N	2.200 RPM	3.100 RPM
51309	45 mm	85 mm	—	Open	80.000 N	163.000 N	2.000 RPM	2.900 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51309C3	45 mm	85 mm	—	Open	80.000 N	163.000 N	2.000 RPM	2.900 RPM
51309P5	45 mm	85 mm	—	Open	80.000 N	163.000 N	2.000 RPM	2.900 RPM
51310	50 mm	95 mm	—	Open	96.500 N	202.000 N	1.800 RPM	2.600 RPM
51310C3	50 mm	95 mm	—	Open	96.500 N	202.000 N	1.800 RPM	2.600 RPM
51311	55 mm	105 mm	—	Open	119.000 N	246.000 N	1.600 RPM	2.300 RPM
51311C3	55 mm	105 mm	—	Open	119.000 N	246.000 N	1.600 RPM	2.300 RPM
51312	60 mm	110 mm	—	Open	123.000 N	267.000 N	1.600 RPM	2.300 RPM
51312C3	60 mm	110 mm	—	Open	123.000 N	267.000 N	1.600 RPM	2.300 RPM
51313	65 mm	115 mm	—	Open	128.000 N	287.000 N	1.500 RPM	2.200 RPM
51313C3	65 mm	115 mm	—	Open	128.000 N	287.000 N	1.500 RPM	2.200 RPM
51314	70 mm	125 mm	—	Open	148.000 N	340.000 N	1.400 RPM	2.000 RPM
51314C3	70 mm	125 mm	—	Open	148.000 N	340.000 N	1.400 RPM	2.000 RPM
51315	75 mm	135 mm	—	Open	171.000 N	395.000 N	1.300 RPM	1.800 RPM
51315C3	75 mm	135 mm	—	Open	171.000 N	395.000 N	1.300 RPM	1.800 RPM
51316	80 mm	140 mm	—	Open	176.000 N	425.000 N	1.200 RPM	1.800 RPM
51316C3	80 mm	140 mm	—	Open	176.000 N	425.000 N	1.200 RPM	1.800 RPM
51317	85 mm	150 mm	—	Open	201.000 N	490.000 N	1.100 RPM	1.600 RPM
51317C3	85 mm	150 mm	—	Open	201.000 N	490.000 N	1.100 RPM	1.600 RPM
51318	90 mm	155 mm	—	Open	198.000 N	490.000 N	1.100 RPM	1.600 RPM
51318C3	90 mm	155 mm	—	Open	198.000 N	490.000 N	1.100 RPM	1.600 RPM
51320	100 mm	170 mm	—	Open	237.000 N	595.000 N	900 RPM	1.400 RPM
51320C3	100 mm	170 mm	—	Open	237.000 N	595.000 N	900 RPM	1.400 RPM
51322	110 mm	190 mm	—	Open	267.000 N	705.000 N	870 RPM	1.200 RPM
51322C3	110 mm	190 mm	—	Open	267.000 N	705.000 N	870 RPM	1.200 RPM
51324	120 mm	210 mm	—	Open	296.000 N	805.000 N	780 RPM	1.100 RPM
51324C3	120 mm	210 mm	—	Open	296.000 N	805.000 N	780 RPM	1.100 RPM
51326	130 mm	225 mm	—	Open	330.000 N	960.000 N	720 RPM	1.000 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51326C3	130 mm	225 mm	—	Open	330.000 N	960.000 N	720 RPM	1.000 RPM
51328	140 mm	240 mm	—	Open	350.000 N	1.050.000 N	670 RPM	960 RPM
51328C3	140 mm	240 mm	—	Open	350.000 N	1.050.000 N	670 RPM	960 RPM
51330	150 mm	250 mm	—	Open	360.000 N	1.130.000 N	660 RPM	940 RPM
51330C3	150 mm	250 mm	—	Open	360.000 N	1.130.000 N	660 RPM	940 RPM
51332	160 mm	270 mm	—	Open	450.000 N	1.470.000 N	600 RPM	860 RPM
51332C3	160 mm	270 mm	—	Open	450.000 N	1.470.000 N	600 RPM	860 RPM
51334	170 mm	280 mm	—	Open	465.000 N	1.570.000 N	590 RPM	840 RPM
51334C3	170 mm	280 mm	—	Open	465.000 N	1.570.000 N	590 RPM	840 RPM
51336	180 mm	300 mm	—	Open	490.000 N	1.700.000 N	540 RPM	780 RPM
51336C3	180 mm	300 mm	—	Open	490.000 N	1.700.000 N	540 RPM	780 RPM
51338	190 mm	320 mm	—	Open	545.000 N	1.950.000 N	500 RPM	710 RPM
51338C3	190 mm	320 mm	—	Open	545.000 N	1.950.000 N	500 RPM	710 RPM
51340	200 mm	340 mm	—	Open	595.000 N	2.220.000 N	470 RPM	670 RPM
51340C3	200 mm	340 mm	—	Open	595.000 N	2.220.000 N	470 RPM	670 RPM
51405	25 mm	60 mm	—	Open	55.500 N	89.500 N	2.600 RPM	3.700 RPM
51405C3	25 mm	60 mm	—	Open	55.500 N	89.500 N	2.600 RPM	3.700 RPM
51406	30 mm	70 mm	—	Open	72.500 N	126.000 N	2.200 RPM	3.200 RPM
51406C3	30 mm	70 mm	—	Open	72.500 N	126.000 N	2.200 RPM	3.200 RPM
51407	35 mm	80 mm	—	Open	87.000 N	155.000 N	1.900 RPM	2.800 RPM
51407C3	35 mm	80 mm	—	Open	87.000 N	155.000 N	1.900 RPM	2.800 RPM
51408	40 mm	90 mm	—	Open	112.000 N	205.000 N	1.700 RPM	2.500 RPM
51408C3	40 mm	90 mm	—	Open	112.000 N	205.000 N	1.700 RPM	2.500 RPM
51409	45 mm	100 mm	—	Open	130.000 N	242.000 N	1.600 RPM	2.200 RPM
51409C3	45 mm	100 mm	—	Open	130.000 N	242.000 N	1.600 RPM	2.200 RPM
51410A	50 mm	110 mm	—	Open	14.800 N	283.000 N	1.400 RPM	2.000 RPM
51410AC3	50 mm	110 mm	—	Open	14.800 N	283.000 N	1.400 RPM	2.000 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
51411	55 mm	120 mm	—	Open	178.000 N	360.000 N	1.300 RPM	1.800 RPM
51411C3	55 mm	120 mm	—	Open	178.000 N	360.000 N	1.300 RPM	1.800 RPM
51412	60 mm	130 mm	—	Open	214.000 N	435.000 N	1.200 RPM	1.700 RPM
51412C3	60 mm	130 mm	—	Open	214.000 N	435.000 N	1.200 RPM	1.700 RPM
51413	65 mm	140 mm	—	Open	232.000 N	495.000 N	1.100 RPM	1.600 RPM
51413C3	65 mm	140 mm	—	Open	232.000 N	495.000 N	1.100 RPM	1.600 RPM
51414	70 mm	150 mm	—	Open	250.000 N	555.000 N	1.000 RPM	1.500 RPM
51414C3	70 mm	150 mm	—	Open	250.000 N	555.000 N	1.000 RPM	1.500 RPM
51415	75 mm	160 mm	—	Open	269.000 N	615.000 N	940 RPM	1.400 RPM
51415C3	75 mm	160 mm	—	Open	269.000 N	615.000 N	940 RPM	1.400 RPM
51416	80 mm	170 mm	—	Open	270.000 N	620.000 N	890 RPM	1.300 RPM
51416C3	80 mm	170 mm	—	Open	270.000 N	620.000 N	890 RPM	1.300 RPM
51417	85 mm	180 mm	—	Open	288.000 N	685.000 N	840 RPM	1.200 RPM
51417C3	85 mm	180 mm	—	Open	288.000 N	685.000 N	840 RPM	1.200 RPM
51418	90 mm	190 mm	—	Open	305.000 N	750.000 N	790 RPM	1.100 RPM
51418C3	90 mm	190 mm	—	Open	305.000 N	750.000 N	790 RPM	1.100 RPM
51420	100 mm	210 mm	—	Open	370.000 N	970.000 N	710 RPM	1.000 RPM
51420C3	100 mm	210 mm	—	Open	370.000 N	970.000 N	710 RPM	1.000 RPM

LIÊN HỆ

Email: infos@catson.com.vn

Website: www.catson.vn

Điện thoại: +84 28 3820 8888

Fax: +84 28 3826 8888

