

Single Row Radial Ball Bearing - Double Sealed (Contact Rubber Seal), WC88000 Series

Single Row Radial Ball Bearings - 8000, 87000, 88000, WC8000, WC8800 Series

58 items



Select an NTN item number to open its detail page on www.catson.vn.

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
WC88006	6 mm	24 mm	—	Double Sealed	3.350 N	1.400 N	24.000 RPM	—
WC88006C3	6 mm	24 mm	—	Double Sealed	3.350 N	1.400 N	24.000 RPM	—
WC88007	7 mm	24 mm	—	Double Sealed	4.000 N	1.580 N	24.000 RPM	—
WC88007C3	7 mm	24 mm	—	Double Sealed	4.000 N	1.580 N	24.000 RPM	—
WC88008	8 mm	24 mm	—	Double Sealed	4.000 N	1.580 N	24.000 RPM	—
WC88008C3	8 mm	24 mm	—	Double Sealed	4.000 N	1.580 N	24.000 RPM	—
WC88009	9 mm	30 mm	—	Double Sealed	5.100 N	2.400 N	18.000 RPM	—
WC88009C3	9 mm	30 mm	—	Double Sealed	5.100 N	2.400 N	18.000 RPM	—
WC88011	11 mm	32 mm	—	Double Sealed	6.100 N	2.740 N	16.000 RPM	—
WC88011C3	11 mm	32 mm	—	Double Sealed	6.100 N	2.740 N	16.000 RPM	—
WC88013	13 mm	32 mm	—	Double Sealed	6.100 N	2.740 N	16.000 RPM	—
WC88013C3	13 mm	32 mm	—	Double Sealed	6.100 N	2.740 N	16.000 RPM	—
WC88014	14 mm	35 mm	—	Double Sealed	7.750 N	3.600 N	15.000 RPM	—
WC88014C3	14 mm	35 mm	—	Double Sealed	7.750 N	3.600 N	15.000 RPM	—
WC88016	16 mm	35 mm	—	Double Sealed	7.750 N	3.600 N	15.000 RPM	—
WC88016C3	16 mm	35 mm	—	Double Sealed	7.750 N	3.600 N	15.000 RPM	—
WC88026	26 mm	52 mm	—	Double Sealed	14.000 N	7.850 N	8.900 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
WC88026C3	26 mm	52 mm	—	Double Sealed	14.000 N	7.850 N	8.900 RPM	—
WC88035	5 mm	19 mm	—	Double Sealed	2.340 N	890 N	30.000 RPM	—
WC88035C3	5 mm	19 mm	—	Double Sealed	2.340 N	890 N	30.000 RPM	—
WC88036	6 mm	19 mm	—	Double Sealed	2.340 N	890 N	30.000 RPM	—
WC88036C3	6 mm	19 mm	—	Double Sealed	2.340 N	890 N	30.000 RPM	—
WC88037	7 mm	22 mm	—	Double Sealed	3.350 N	1.400 N	23.000 RPM	—
WC88037C3	7 mm	22 mm	—	Double Sealed	3.350 N	1.400 N	23.000 RPM	—
WC88038	8 mm	22 mm	—	Double Sealed	3.350 N	1.400 N	23.000 RPM	—
WC88038C3	8 mm	22 mm	—	Double Sealed	3.350 N	1.400 N	23.000 RPM	—
WC88039	9 mm	26 mm	—	Double Sealed	4.600 N	1.960 N	21.000 RPM	—
WC88039C3	9 mm	26 mm	—	Double Sealed	4.600 N	1.960 N	21.000 RPM	—
WC88500	10 mm	30 mm	—	Double Sealed	5.100 N	2.400 N	18.000 RPM	—
WC88500C3	10 mm	30 mm	—	Double Sealed	5.100 N	2.400 N	18.000 RPM	—
WC88501	12 mm	32 mm	—	Double Sealed	6.100 N	2.740 N	16.000 RPM	—
WC88501C3	12 mm	32 mm	—	Double Sealed	6.100 N	2.740 N	16.000 RPM	—
WC88502	15 mm	35 mm	—	Double Sealed	7.750 N	3.600 N	15.000 RPM	—
WC88502C3	15 mm	35 mm	—	Double Sealed	7.750 N	3.600 N	15.000 RPM	—
WC88503	17 mm	40 mm	—	Double Sealed	9.600 N	4.600 N	12.000 RPM	—
WC88503C3	17 mm	40 mm	—	Double Sealed	9.600 N	4.600 N	12.000 RPM	—
WC88504	20 mm	47 mm	—	Double Sealed	12.900 N	6.650 N	10.000 RPM	—
WC88504C3	20 mm	47 mm	—	Double Sealed	12.900 N	6.650 N	10.000 RPM	—
WC88505	25 mm	52 mm	—	Double Sealed	14.000 N	7.850 N	8.900 RPM	—
WC88505C3	25 mm	52 mm	—	Double Sealed	14.000 N	7.850 N	8.900 RPM	—
WC88506	30 mm	62 mm	—	Double Sealed	19.600 N	11.300 N	7.300 RPM	—
WC88506C3	30 mm	62 mm	—	Double Sealed	19.600 N	11.300 N	7.300 RPM	—
WC88507	35 mm	72 mm	—	Double Sealed	25.600 N	15.300 N	6.300 RPM	—
WC88507C3	35 mm	72 mm	—	Double Sealed	25.600 N	15.300 N	6.300 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
WC88508	40 mm	80 mm	—	Double Sealed	29.100 N	17.800 N	5.600 RPM	—
WC88508C3	40 mm	80 mm	—	Double Sealed	29.100 N	17.800 N	5.600 RPM	—
WC88509	45 mm	85 mm	—	Double Sealed	32.500 N	20.500 N	5.200 RPM	—
WC88509C3	45 mm	85 mm	—	Double Sealed	32.500 N	20.500 N	5.200 RPM	—
WC88510	50 mm	90 mm	—	Double Sealed	35.000 N	23.100 N	4.700 RPM	—
WC88510C3	50 mm	90 mm	—	Double Sealed	35.000 N	23.100 N	4.700 RPM	—
WC88511	55 mm	100 mm	—	Double Sealed	43.500 N	29.100 N	4.300 RPM	—
WC88511C3	55 mm	100 mm	—	Double Sealed	43.500 N	29.100 N	4.300 RPM	—
WC88603	17 mm	47 mm	—	Double Sealed	13.600 N	6.550 N	11.000 RPM	—
WC88603C3	17 mm	47 mm	—	Double Sealed	13.600 N	6.550 N	11.000 RPM	—
WC88604	20 mm	52 mm	—	Double Sealed	16.000 N	7.850 N	10.000 RPM	—
WC88604C3	20 mm	52 mm	—	Double Sealed	16.000 N	7.850 N	10.000 RPM	—
WC88605	25 mm	62 mm	—	Double Sealed	21.100 N	10.900 N	8.100 RPM	—
WC88605C3	25 mm	62 mm	—	Double Sealed	21.100 N	10.900 N	8.100 RPM	—

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

