

Single Row Radial Ball Bearing - Single Sealed (Contact Rubber Seal), 8000 Series

Single Row Radial Ball Bearings - 8000, 87000, 88000, WC8000, WC8800 Series

76 items



Select an NTN item number to open its detail page on www.catson.vn.

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
8006	6 mm	24 mm	—	Single Sealed	3.350 N	107.000 N	24.000 RPM	—
8006C3	6 mm	24 mm	—	Single Sealed	3.350 N	107.000 N	24.000 RPM	—
8007	7 mm	24 mm	—	Single Sealed	4.000 N	107.000 N	24.000 RPM	—
8007C3	7 mm	24 mm	—	Single Sealed	4.000 N	107.000 N	24.000 RPM	—
8008	8 mm	24 mm	—	Single Sealed	4.000 N	107.000 N	24.000 RPM	—
8008C3	8 mm	24 mm	—	Single Sealed	4.000 N	107.000 N	24.000 RPM	—
8009	9 mm	30 mm	—	Single Sealed	5.100 N	80.000 N	18.000 RPM	—
8009C3	9 mm	30 mm	—	Single Sealed	5.100 N	80.000 N	18.000 RPM	—
8011	11 mm	32 mm	—	Single Sealed	6.100 N	71.000 N	16.000 RPM	—
8011C3	11 mm	32 mm	—	Single Sealed	6.100 N	71.000 N	16.000 RPM	—
8013	13 mm	32 mm	—	Single Sealed	6.100 N	71.000 N	16.000 RPM	—
8013C3	13 mm	32 mm	—	Single Sealed	6.100 N	71.000 N	16.000 RPM	—
8014	14 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8014C3	14 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8016	16 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8016-2AS	16 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8016C3	16 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
8026	26 mm	52 mm	—	Single Sealed	14.000 N	39.500 N	8.900 RPM	—
8026C3	26 mm	52 mm	—	Single Sealed	14.000 N	39.500 N	8.900 RPM	—
8035	5 mm	19 mm	—	Single Sealed	2.340 N	133.000 N	30.000 RPM	—
8035C3	5 mm	19 mm	—	Single Sealed	2.340 N	133.000 N	30.000 RPM	—
8036	6 mm	19 mm	—	Single Sealed	2.340 N	133.000 N	30.000 RPM	—
8036C3	6 mm	19 mm	—	Single Sealed	2.340 N	133.000 N	30.000 RPM	—
8037	7 mm	22 mm	—	Single Sealed	3.350 N	102.000 N	23.000 RPM	—
8037C3	7 mm	22 mm	—	Single Sealed	3.350 N	102.000 N	23.000 RPM	—
8038	8 mm	22 mm	—	Single Sealed	3.350 N	102.000 N	23.000 RPM	—
8038C3	8 mm	22 mm	—	Single Sealed	3.350 N	102.000 N	23.000 RPM	—
8039	9 mm	26 mm	—	Single Sealed	4.600 N	93.500 N	21.000 RPM	—
8039C3	9 mm	26 mm	—	Single Sealed	4.600 N	93.500 N	21.000 RPM	—
8500	10 mm	30 mm	—	Single Sealed	5.100 N	80.000 N	18.000 RPM	—
8500C3	10 mm	30 mm	—	Single Sealed	5.100 N	80.000 N	18.000 RPM	—
8501	12 mm	32 mm	—	Single Sealed	6.100 N	71.000 N	16.000 RPM	—
8501C3	12 mm	32 mm	—	Single Sealed	6.100 N	71.000 N	16.000 RPM	—
8502	15 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8502-2AS	15 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8502C3	15 mm	35 mm	—	Single Sealed	7.750 N	66.500 N	15.000 RPM	—
8503	17 mm	40 mm	—	Single Sealed	9.600 N	53.500 N	12.000 RPM	—
8503C3	17 mm	40 mm	—	Single Sealed	9.600 N	53.500 N	12.000 RPM	—
8504	20 mm	47 mm	—	Single Sealed	12.900 N	44.500 N	10.000 RPM	—
8504C3	20 mm	47 mm	—	Single Sealed	12.900 N	44.500 N	10.000 RPM	—
8505	25 mm	52 mm	—	Single Sealed	14.000 N	39.500 N	8.900 RPM	—
8505C3	25 mm	52 mm	—	Single Sealed	14.000 N	39.500 N	8.900 RPM	—
8506	30 mm	62 mm	—	Single Sealed	19.600 N	32.500 N	7.300 RPM	—
8506C3	30 mm	62 mm	—	Single Sealed	19.600 N	32.500 N	7.300 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
8507	35 mm	72 mm	—	Single Sealed	25.700 N	28.000 N	6.300 RPM	—
8507C3	35 mm	72 mm	—	Single Sealed	25.700 N	28.000 N	6.300 RPM	—
8508	40 mm	80 mm	—	Single Sealed	29.100 N	24.900 N	5.600 RPM	—
8508C3	40 mm	80 mm	—	Single Sealed	29.100 N	24.900 N	5.600 RPM	—
8509	45 mm	85 mm	—	Single Sealed	32.500 N	23.100 N	5.200 RPM	—
8509C3	45 mm	85 mm	—	Single Sealed	32.500 N	23.100 N	5.200 RPM	—
8510	50 mm	90 mm	—	Single Sealed	35.000 N	20.900 N	4.700 RPM	—
8510C3	50 mm	90 mm	—	Single Sealed	35.000 N	20.900 N	4.700 RPM	—
8511	55 mm	100 mm	—	Single Sealed	43.500 N	19.100 N	4.300 RPM	—
8511C3	55 mm	100 mm	—	Single Sealed	43.500 N	19.100 N	4.300 RPM	—
8512	60 mm	110 mm	—	Single Sealed	52.500 N	16.900 N	3.800 RPM	—
8512C3	60 mm	110 mm	—	Single Sealed	52.500 N	16.900 N	3.800 RPM	—
8513	65 mm	120 mm	—	Single Sealed	57.500 N	16.000 N	3.600 RPM	—
8513C3	65 mm	120 mm	—	Single Sealed	57.500 N	16.000 N	3.600 RPM	—
8514	70 mm	125 mm	—	Single Sealed	62.500 N	15.100 N	3.400 RPM	—
8514C3	70 mm	125 mm	—	Single Sealed	62.500 N	15.100 N	3.400 RPM	—
8602	15 mm	42 mm	—	Single Sealed	11.400 N	53.500 N	12.000 RPM	—
8602C3	15 mm	42 mm	—	Single Sealed	11.400 N	53.500 N	12.000 RPM	—
8603	17 mm	47 mm	—	Single Sealed	13.600 N	49.000 N	11.000 RPM	—
8603C3	17 mm	47 mm	—	Single Sealed	13.600 N	49.000 N	11.000 RPM	—
8604	20 mm	52 mm	—	Single Sealed	16.000 N	44.500 N	10.000 RPM	—
8604C3	20 mm	52 mm	—	Single Sealed	16.000 N	44.500 N	10.000 RPM	—
8605	25 mm	62 mm	—	Single Sealed	21.100 N	36.000 N	8.100 RPM	—
8605C3	25 mm	62 mm	—	Single Sealed	21.100 N	36.000 N	8.100 RPM	—
8606	30 mm	72 mm	—	Single Sealed	26.700 N	29.400 N	6.600 RPM	—
8606C3	30 mm	72 mm	—	Single Sealed	26.700 N	29.400 N	6.600 RPM	—
8607	35 mm	80 mm	—	Single Sealed	33.500 N	26.700 N	6.000 RPM	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
8607C3	35 mm	80 mm	—	Single Sealed	33.500 N	26.700 N	6.000 RPM	—
8608	40 mm	90 mm	—	Single Sealed	40.500 N	23.600 N	5.300 RPM	—
8608C3	40 mm	90 mm	—	Single Sealed	40.500 N	23.600 N	5.300 RPM	—
8609	45 mm	100 mm	—	Single Sealed	53.000 N	20.900 N	4.700 RPM	—
8609C3	45 mm	100 mm	—	Single Sealed	53.000 N	20.900 N	4.700 RPM	—

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

