

Tapered Roller Set - Inch Series and J Series

Tapered Roller Set - Inch Series and J Series

1000 mã sản phẩm



Nhập vào mã NTN để mở trang chi tiết trên www.catson.vn.

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
02474-02420	—	68,263 mm	28,575 mm	Open	57.000 N	67.000 N	5.800 RPM	—
02475-02420	—	68,263 mm	31,750 mm	Open	57.000 N	67.000 N	—	—
02476-02420	—	68,263 mm	31,750 mm	Open	57.000 N	67.000 N	5.800 RPM	—
02872-02820	—	73,025 mm	28,575 mm	Open	56.500 N	68.000 N	5.300 RPM	—
02875-02820	—	68,263 mm	31,750 mm	Open	56.500 N	68.000 N	—	—
02877-02820	—	73,025 mm	34,925 mm	Open	56.500 N	68.000 N	—	—
02878-02820	—	73,025 mm	34,925 mm	Open	56.500 N	68.000 N	5.300 RPM	—
03062-03162	—	41,275 mm	15,875 mm	Open	20.300 N	18.700 N	10.000 RPM	—
05062-05185	—	47 mm	15,875 mm	Open	24.000 N	24.200 N	—	—
05066-05185	—	47 mm	16,993 mm	Open	24.000 N	24.200 N	—	—
05075-05185	—	47 mm	19,050 mm	Open	24.000 N	24.200 N	—	—
05079-07196	—	50,005 mm	19,987 mm	Open	24.000 N	24.200 N	—	—
07079-07196	—	50,005 mm	20 mm	Open	26.000 N	27.900 N	7.500 RPM	—
07087-07196	—	50,005 mm	22,225 mm	Open	26.000 N	27.900 N	—	—
07087-07204	—	51,994 mm	22,225 mm	Open	26.000 N	27.900 N	7.500 RPM	—
07093-07196	—	50,005 mm	23,812 mm	Open	26.000 N	27.900 N	—	—
07096-07196	—	50,005 mm	25,159 mm	Open	26.000 N	27.900 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
07097-07196	—	50,005 mm	25 mm	Open	26.000 N	27.900 N	—	—
07098-07196	—	50,005 mm	24,981 mm	Open	26.000 N	27.900 N	—	—
07100-07196	—	50,005 mm	25,400 mm	Open	26.000 N	27.900 N	7.500 RPM	—
07100-07196-3	—	50,005 mm	25,400 mm	Open	26.000 N	27.900 N	10.000 RPM	—
07100-07204	—	51,994 mm	25,400 mm	Open	26.000 N	27.900 N	7.500 RPM	—
07100L-07196	—	50,005 mm	25,400 mm	Open	26.000 N	27.900 N	—	—
07100S-07196	—	50,005 mm	25,400 mm	Open	26.000 N	27.900 N	—	—
08125-08231	—	58,738 mm	31,750 mm	Open	28.200 N	32.500 N	—	—
09062-09195	—	49,225 mm	15,875 mm	Open	38.500 N	39.000 N	8.500 RPM	—
09067-09195	—	49,225 mm	19,050 mm	Open	38.500 N	39.000 N	8.500 RPM	—
09067-09196	—	49,225 mm	19,050 mm	Open	38.500 N	39.000 N	—	—
09078-09195	—	49,225 mm	19,050 mm	Open	38.500 N	39.000 N	—	—
09081-09195	—	49,225 mm	20,625 mm	Open	38.500 N	39.000 N	—	—
09081-09196	—	49,225 mm	20,625 mm	Open	38.500 N	39.000 N	8.500 RPM	—
11162-11300	—	76,200 mm	41,275 mm	Open	42.500 N	51.500 N	4.900 RPM	—
11162-11315	—	80 mm	41,275 mm	Open	42.500 N	51.500 N	—	—
11590-11520	—	42,863 mm	15,875 mm	Open	17.600 N	17.500 N	8.700 RPM	—
12175-12303	—	76,992 mm	44,450 mm	Open	44.000 N	54.000 N	—	—
12580-12520	—	49,225 mm	20,638 mm	Open	37.500 N	39.000 N	8.200 RPM	—
13685-13621	—	69,012 mm	38,100 mm	Open	47.500 N	59.500 N	—	—
13687-13620	—	69,012 mm	38,100 mm	Open	47.500 N	59.500 N	—	—
13687-13621	—	69,012 mm	38,100 mm	Open	47.500 N	59.500 N	—	—
1380-1328	—	52,388 mm	22,225 mm	Open	40.500 N	43.000 N	7.600 RPM	—
1380-1329	—	53,975 mm	22,225 mm	Open	40.500 N	43.000 N	—	—
13889-13830	—	63,500 mm	38,100 mm	Open	25.900 N	33.500 N	—	—
14116-14274	—	69,012 mm	30,226 mm	Open	48.500 N	58.000 N	—	—
14116-14276	—	69,012 mm	30,226 mm	Open	48.500 N	58.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
14117A-14276	—	69,012 mm	30 mm	Open	48.500 N	58.000 N	—	—
14124-14276	—	69,012 mm	31,750 mm	Open	48.500 N	58.000 N	5.600 RPM	—
14125A-14276	—	69,012 mm	31,750 mm	Open	48.500 N	58.000 N	5.600 RPM	—
14130-14276	—	69,012 mm	33,338 mm	Open	48.500 N	58.000 N	5.600 RPM	—
14137A-14276	—	69,012 mm	34,925 mm	Open	48.500 N	58.000 N	5.600 RPM	—
14138A-14276	—	69,012 mm	34,925 mm	Open	48.500 N	58.000 N	—	—
14139-14276	—	69,012 mm	34,976 mm	Open	48.500 N	58.000 N	—	—
15100-15245	—	61,999 mm	25,400 mm	Open	46.500 N	54.000 N	—	—
15101-15243	—	61,913 mm	25,400 mm	Open	46.500 N	54.000 N	—	—
15102-15245	—	61,999 mm	25,400 mm	Open	46.500 N	54.000 N	—	—
15103-15245	—	61,999 mm	26,157 mm	Open	46.500 N	54.000 N	—	—
15103S-15243	—	61,913 mm	26,162 mm	Open	46.500 N	54.000 N	—	—
15106-15245	—	61,999 mm	26,988 mm	Open	46.500 N	54.000 N	—	—
15106-15250X	—	63,500 mm	26,988 mm	Open	46.500 N	54.000 N	—	—
15112-15245	—	61,999 mm	28,575 mm	Open	46.500 N	54.000 N	—	—
15116-15245	—	61,999 mm	30,112 mm	Open	46.500 N	54.000 N	—	—
15117-15245	—	61,999 mm	29,987 mm	Open	46.500 N	54.000 N	—	—
15118-15245	—	61,999 mm	30,213 mm	Open	46.500 N	54.000 N	—	—
15119-15245	—	61,999 mm	30,213 mm	Open	46.500 N	54.000 N	—	—
15120-15245	—	61,999 mm	30,213 mm	Open	46.500 N	54.000 N	—	—
15123-15245	—	61,999 mm	31,750 mm	Open	46.500 N	54.000 N	—	—
15125-15245	—	61,999 mm	31,750 mm	Open	46.500 N	54.000 N	6.100 RPM	—
15126-15245	—	61,999 mm	31,750 mm	Open	46.500 N	54.000 N	6.100 RPM	—
15579X-15520	—	57,150 mm	25,987 mm	Open	39.500 N	45.500 N	—	—
15580-15520	—	57,150 mm	26,988 mm	Open	39.500 N	45.500 N	6.700 RPM	—
15580-15523	—	60,325 mm	26,988 mm	Open	39.500 N	45.500 N	—	—
15590-15520	—	57,150 mm	28,575 mm	Open	39.500 N	45.500 N	6.700 RPM	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
15590-15523	—	60,325 mm	28,575 mm	Open	39.500 N	45.500 N	6.700 RPM	—
16137-16284	—	72,238 mm	34,925 mm	Open	48.000 N	58.500 N	—	—
16150-16282	—	71,999 mm	38,100 mm	Open	48.000 N	58.500 N	5.300 RPM	—
17098-17244	—	61,999 mm	24,981 mm	Open	39.000 N	42.000 N	6.300 RPM	—
17118-17244	—	61,999 mm	29,987 mm	Open	39.000 N	42.000 N	6.300 RPM	—
17119-17244	—	61,999 mm	30,162 mm	Open	39.000 N	42.000 N	6.300 RPM	—
1755-1729	—	56,896 mm	22,225 mm	Open	42.500 N	46.500 N	—	—
17580-17520	—	42,863 mm	15,875 mm	Open	26.700 N	26.000 N	9.800 RPM	—
17580-17520-3	—	42,862 mm	15,875 mm	Open	26.700 N	26.000 N	—	—
1775-1729	—	56,896 mm	19,050 mm	Open	42.500 N	46.500 N	—	—
1779-1729	—	56,896 mm	23,812 mm	Open	42.500 N	46.500 N	—	—
1780-1729	—	56,896 mm	25,400 mm	Open	42.500 N	46.500 N	7.200 RPM	—
17887-17831	—	79,985 mm	45,230 mm	Open	53.400 N	46.300 N	—	—
18590-18520	—	73,025 mm	41,275 mm	Open	46.000 N	55.500 N	5.000 RPM	—
18685-18620	—	79,375 mm	44,450 mm	Open	45.500 N	55.600 N	—	—
18690-18620	—	79,375 mm	46,038 mm	Open	45.500 N	56.000 N	4.600 RPM	—
18790-18720	—	85,001 mm	50,800 mm	Open	49.500 N	65.000 N	4.200 RPM	—
18790-18724	—	88,900 mm	50,800 mm	Open	49.500 N	65.000 N	—	—
19150-19268	—	68,263 mm	38,100 mm	Open	43.500 N	51.000 N	—	—
19150-19281	—	71,438 mm	38,100 mm	Open	43.500 N	51.000 N	—	—
1985-1930	—	56,896 mm	28,575 mm	Open	40.500 N	44.500 N	—	—
1985-1931	—	60,325 mm	28,575 mm	Open	40.500 N	44.500 N	—	—
1985-1932	—	58,738 mm	28,575 mm	Open	40.500 N	44.500 N	—	—
1986-1922	—	57,150 mm	25,400 mm	Open	40.500 N	44.500 N	—	—
1988-1922	—	57,150 mm	28,575 mm	Open	40.500 N	44.500 N	—	—
21075-21212	—	53,975 mm	19,050 mm	Open	40.000 N	39.000 N	8.000 RPM	—
22780-22720	—	82,550 mm	42,862 mm	Open	75.500 N	97.000 N	4.600 RPM	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
23100-23256	—	65,088 mm	25,400 mm	Open	47.000 N	50.500 N	5.700 RPM	—
24780-24720	—	76,200 mm	41,275 mm	Open	65.000 N	80.500 N	4.900 RPM	—
24780-24720D	—	76,200 mm	41,275 mm	Open	65.000 N	80.500 N	—	—
25572-25520	—	82,931 mm	38,100 mm	Open	76.000 N	98.000 N	—	—
25577-25520	—	82,931 mm	42,875 mm	Open	76.000 N	98.000 N	—	—
25577-25521	—	83,058 mm	42,875 mm	Open	76.000 N	98.000 N	—	—
25577-25523	—	82,931 mm	42,875 mm	Open	76.000 N	98.000 N	—	—
25578-25520	—	82,931 mm	42,862 mm	Open	76.000 N	98.000 N	—	—
25580-25520	—	82,931 mm	44,450 mm	Open	76.000 N	98.000 N	4.500 RPM	—
25580-25522	—	83,058 mm	44,450 mm	Open	76.000 N	98.000 N	4.500 RPM	—
25580-25523	—	82,931 mm	44,450 mm	Open	76.000 N	98.000 N	—	—
25582-25520	—	82,931 mm	44,450 mm	Open	76.000 N	98.000 N	—	—
2558-2523	—	69,850 mm	30,162 mm	Open	69.000 N	81.500 N	—	—
25584-25520	—	82,931 mm	44,983 mm	Open	76.000 N	98.000 N	4.500 RPM	—
25590-25519	—	82,550 mm	45,618 mm	Open	76.000 N	98.000 N	—	—
25590-25520	—	82,931 mm	45,618 mm	Open	76.000 N	98.000 N	4.500 RPM	—
25590-25522	—	83,058 mm	45,618 mm	Open	76.000 N	98.000 N	—	—
25590-25523	—	82,931 mm	45,618 mm	Open	76.000 N	98.000 N	—	—
25590-25526	—	85,001 mm	45,618 mm	Open	76.000 N	98.000 N	—	—
25592-25520	—	82,931 mm	46,038 mm	Open	76.000 N	98.000 N	—	—
2578-2523	—	69,850 mm	28,575 mm	Open	69.000 N	81.500 N	—	—
2580-2520	—	66,421 mm	31,750 mm	Open	69.000 N	81.500 N	5.700 RPM	—
2580-2523	—	69,850 mm	31,750 mm	Open	69.000 N	81.500 N	5.700 RPM	—
2582-2523	—	69,850 mm	31,750 mm	Open	69.000 N	81.500 N	5.700 RPM	—
2585-2523	—	69,850 mm	33,338 mm	Open	69.000 N	81.500 N	5.700 RPM	—
25877-25820	—	73,025 mm	34,925 mm	Open	71.000 N	85.000 N	5.300 RPM	—
25877-25821	—	73,025 mm	34,925 mm	Open	71.000 N	85.000 N	5.300 RPM	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
25878-25820	—	73,025 mm	34,925 mm	Open	71.000 N	85.000 N	—	—
25880-25821	—	73,025 mm	36,487 mm	Open	71.000 N	85.000 N	5.300 RPM	—
2682-2631	—	66,421 mm	26,162 mm	Open	64.500 N	72.500 N	—	—
2687-2631	—	66,421 mm	25,400 mm	Open	64.500 N	72.500 N	6.200 RPM	—
26878-26822	—	79,375 mm	38,100 mm	Open	76.500 N	97.500 N	—	—
26881-26822	—	79,375 mm	39,688 mm	Open	76.500 N	97.500 N	—	—
26882-26823	—	76,200 mm	41,275 mm	Open	76.500 N	97.500 N	—	—
26882-26824	—	80 mm	41,275 mm	Open	76.500 N	97.500 N	—	—
2688-2631	—	66,421 mm	26,988 mm	Open	64.500 N	72.500 N	—	—
26883-26822	—	79,375 mm	35 mm	Open	76.500 N	97.500 N	4.800 RPM	—
26884-26822	—	79,375 mm	42,875 mm	Open	76.500 N	97.500 N	—	—
26885-26822	—	79,375 mm	41,275 mm	Open	76.500 N	97.500 N	—	—
26886-26824	—	80 mm	42,875 mm	Open	76.500 N	97.500 N	—	—
2689-2631	—	66,421 mm	28,575 mm	Open	64.500 N	72.500 N	—	—
2690-2631	—	66,421 mm	29,367 mm	Open	64.500 N	72.500 N	—	—
27680-27620	—	125,413 mm	73,025 mm	Open	109.000 N	179.000 N	—	—
27684-27620	—	125,413 mm	76,200 mm	Open	109.000 N	179.000 N	—	—
27687-27620	—	125,413 mm	82,550 mm	Open	109.000 N	179.000 N	2.700 RPM	—
27689-27620	—	125,413 mm	83,345 mm	Open	109.000 N	179.000 N	—	—
27690-27620	—	125,413 mm	83,345 mm	Open	109.000 N	179.000 N	—	—
27691-27620	—	125,413 mm	83,345 mm	Open	102.000 N	163.000 N	—	—
27695-27620	—	125,413 mm	84,976 mm	Open	109.000 N	179.000 N	—	—
2776-2720	—	76,200 mm	38,100 mm	Open	73.000 N	90.500 N	—	—
2780-2720	—	76,200 mm	36,487 mm	Open	73.000 N	90.500 N	—	—
2785-2720	—	76,200 mm	33,338 mm	Open	73.000 N	90.500 N	—	—
27880-27820	—	80,035 mm	38,100 mm	Open	67.000 N	82.500 N	—	—
27881-27820	—	80,035 mm	38,100 mm	Open	67.000 N	82.500 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
2788-2720	—	76,200 mm	38,100 mm	Open	73.000 N	90.500 N	—	—
2788-2729	—	76,200 mm	38,100 mm	Open	73.000 N	90.500 N	—	—
2789-2720	—	76,200 mm	39,688 mm	Open	73.000 N	90.500 N	—	—
2793-2720	—	76,200 mm	34,925 mm	Open	73.000 N	90.500 N	5.100 RPM	—
2793-2729	—	76,200 mm	34,925 mm	Open	73.000 N	90.500 N	—	—
2793-2735X	—	73,025 mm	34,925 mm	Open	73.000 N	90.500 N	—	—
2796-2720	—	76,200 mm	34,925 mm	Open	73.000 N	90.500 N	—	—
28150-28300	—	76,200 mm	38,100 mm	Open	55.500 N	63.000 N	—	—
28150-28315	—	80 mm	38,100 mm	Open	55.500 N	63.000 N	—	—
28158-28300	—	76,200 mm	40 mm	Open	55.500 N	63.000 N	5.000 RPM	—
28579-28521	—	92,075 mm	49,987 mm	Open	83.500 N	116.000 N	—	—
28580-28521	—	92,075 mm	50,800 mm	Open	83.500 N	116.000 N	4.000 RPM	—
28584-28521	—	92,075 mm	52,388 mm	Open	83.500 N	116.000 N	4.000 RPM	—
28678-28622	—	97,630 mm	50,800 mm	Open	88.500 N	128.000 N	—	—
28680-28622	—	97,630 mm	55,562 mm	Open	88.500 N	128.000 N	3.700 RPM	—
28682-28622	—	97,630 mm	57,150 mm	Open	88.500 N	128.000 N	—	—
2878-2820	—	73,025 mm	34,925 mm	Open	62.500 N	75.500 N	5.200 RPM	—
2879-2820	—	73,025 mm	31,750 mm	Open	62.500 N	75.500 N	—	—
28880-28820E1	—	304,800 mm	247,650 mm	Open	147.000 N	358.000 N	—	—
28985-28921	—	100 mm	60,325 mm	Open	90.500 N	134.000 N	3.500 RPM	—
28990-28919	—	99,979 mm	61,976 mm	Open	90.500 N	134.000 N	—	—
28990-28920	—	101,600 mm	61,976 mm	Open	90.500 N	134.000 N	—	—
28995-28920	—	101,600 mm	62,738 mm	Open	90.500 N	134.000 N	—	—
29580-29520	—	107,950 mm	60 mm	Open	101.000 N	159.000 N	—	—
29580-29521	—	110 mm	60 mm	Open	101.000 N	159.000 N	—	—
29580-29522	—	107,950 mm	60 mm	Open	101.000 N	159.000 N	—	—
29582-29520	—	107,950 mm	60 mm	Open	101.000 N	159.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
29582-29521	—	110 mm	60 mm	Open	101.000 N	159.000 N	—	—
29582-29522	—	107,950 mm	60 mm	Open	101.000 N	159.000 N	—	—
29585-29520	—	107,950 mm	63,500 mm	Open	101.000 N	159.000 N	—	—
29585-29521	—	110 mm	63,500 mm	Open	101.000 N	159.000 N	—	—
29585-29522	—	107,950 mm	63,500 mm	Open	101.000 N	159.000 N	—	—
29586-29520	—	107,950 mm	63,500 mm	Open	101.000 N	159.000 N	—	—
29586-29521	—	110 mm	63,500 mm	Open	101.000 N	159.000 N	—	—
29586-29522	—	107,950 mm	63,500 mm	Open	101.000 N	159.000 N	—	—
29590-29520	—	107,950 mm	66,675 mm	Open	101.000 N	159.000 N	—	—
29590-29521	—	110 mm	66,675 mm	Open	101.000 N	159.000 N	—	—
29590-29522	—	107,950 mm	66,675 mm	Open	101.000 N	159.000 N	3.200 RPM	—
29675-29620	—	112,713 mm	69,850 mm	Open	105.000 N	171.000 N	—	—
29675-29630	—	120,650 mm	69,850 mm	Open	105.000 N	171.000 N	—	—
29680-29620	—	112,713 mm	70,637 mm	Open	105.000 N	171.000 N	—	—
29680-29630	—	120,650 mm	70,637 mm	Open	105.000 N	171.000 N	—	—
29685-29620	—	112,713 mm	73,025 mm	Open	105.000 N	171.000 N	—	—
29685-29630	—	120,650 mm	73,025 mm	Open	105.000 N	171.000 N	—	—
29688-29620	—	112,713 mm	73,817 mm	Open	105.000 N	171.000 N	—	—
29688-29630	—	120,650 mm	73,817 mm	Open	105.000 N	171.000 N	—	—
2984-2924	—	85 mm	46,038 mm	Open	79.000 N	104.000 N	4.400 RPM	—
31593-31520	—	76,200 mm	34,925 mm	Open	80.500 N	97.000 N	—	—
31594-31520	—	76,200 mm	34,925 mm	Open	80.500 N	97.000 N	5.100 RPM	—
31597-31520	—	76,200 mm	36,512 mm	Open	80.500 N	97.000 N	—	—
3187-3120	—	72,626 mm	30,162 mm	Open	84.500 N	98.000 N	—	—
3188-3120	—	72,626 mm	31,750 mm	Open	84.500 N	98.000 N	—	—
3193-3120	—	72,626 mm	31,750 mm	Open	84.500 N	98.000 N	—	—
3196-3120	—	72,626 mm	33,338 mm	Open	84.500 N	98.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
33225-33462	—	117,475 mm	57,150 mm	Open	125.000 N	194.000 N	—	—
33225-33472	—	120 mm	57,150 mm	Open	125.000 N	194.000 N	—	—
33225-33475	—	120,650 mm	57,150 mm	Open	125.000 N	194.000 N	—	—
33262-33462	—	117,475 mm	66,675 mm	Open	125.000 N	194.000 N	—	—
33262-33472	—	120 mm	66,675 mm	Open	125.000 N	194.000 N	—	—
33262-33475	—	120,650 mm	66,675 mm	Open	125.000 N	194.000 N	—	—
33269-33462	—	117,475 mm	68,263 mm	Open	125.000 N	194.000 N	—	—
33269-33472	—	120 mm	68,263 mm	Open	125.000 N	194.000 N	—	—
33269-33475	—	120,650 mm	68,263 mm	Open	125.000 N	194.000 N	—	—
33275-33462	—	117,475 mm	69,850 mm	Open	125.000 N	194.000 N	—	—
33275-33472	—	120 mm	69,850 mm	Open	125.000 N	194.000 N	—	—
33275-33475	—	120,650 mm	69,850 mm	Open	125.000 N	194.000 N	—	—
33281-33462	—	117,475 mm	71,438 mm	Open	125.000 N	194.000 N	—	—
33281-33472	—	120 mm	71,438 mm	Open	125.000 N	194.000 N	—	—
33281-33475	—	120,650 mm	71,438 mm	Open	125.000 N	194.000 N	—	—
33287-33462	—	117,475 mm	73,025 mm	Open	125.000 N	194.000 N	—	—
33287-33472	—	120 mm	73,025 mm	Open	125.000 N	194.000 N	—	—
33287-33475	—	120,650 mm	73,025 mm	Open	125.000 N	194.000 N	—	—
336-332	—	80 mm	41,275 mm	Open	68.000 N	75.000 N	4.700 RPM	—
3379-3320	—	80,167 mm	34,925 mm	Open	95.000 N	112.000 N	4.800 RPM	—
3382-3321	—	77,534 mm	39,688 mm	Open	95.000 N	112.000 N	—	—
3382-3339	—	80,035 mm	39,688 mm	Open	95.000 N	112.000 N	—	—
3386-3320	—	80,167 mm	39,688 mm	Open	95.000 N	112.000 N	4.800 RPM	—
33885-33821	—	95,250 mm	44,450 mm	Open	107.000 N	139.000 N	—	—
33889-33821	—	95,250 mm	50,800 mm	Open	107.000 N	139.000 N	—	—
33890-33821	—	95,250 mm	52,388 mm	Open	107.000 N	139.000 N	—	—
339-332	—	80 mm	35 mm	Open	68.000 N	75.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
34274-34478	—	121,442 mm	69,952 mm	Open	88.500 N	194.000 N	—	—
34274-34492A	—	125,052 mm	69,952 mm	Open	88.500 N	194.000 N	—	—
34274-34500	—	127 mm	69,952 mm	Open	88.500 N	194.000 N	—	—
34275-34478	—	121,442 mm	70 mm	Open	89.500 N	136.000 N	—	—
34275-34492A	—	125,052 mm	70 mm	Open	89.500 N	136.000 N	—	—
34275-34500	—	127 mm	70 mm	Open	89.500 N	136.000 N	—	—
34300-34478	—	121,442 mm	76,200 mm	Open	90.500 N	194.000 N	—	—
34300-34492A	—	125,052 mm	76,200 mm	Open	90.500 N	194.000 N	—	—
34300-34500	—	127 mm	76,200 mm	Open	90.500 N	194.000 N	—	—
34301-34478	—	121,442 mm	76,200 mm	Open	91.500 N	194.000 N	—	—
34301-34478DB-1-01	—	121,442 mm	76,200 mm	Open	91.500 N	194.000 N	—	—
34301-34492A	—	125,052 mm	76,200 mm	Open	91.500 N	194.000 N	—	—
34301-34500	—	127 mm	76,200 mm	Open	91.500 N	194.000 N	—	—
34306-34478	—	121,442 mm	77,788 mm	Open	92.500 N	194.000 N	2.900 RPM	—
34306-34492A	—	125,052 mm	77,788 mm	Open	92.500 N	194.000 N	—	—
34306-34500	—	127 mm	77,788 mm	Open	92.500 N	194.000 N	—	—
34307-34478	—	121,442 mm	77,788 mm	Open	93.500 N	136.000 N	—	—
34307-34492A	—	125,052 mm	77,788 mm	Open	93.500 N	136.000 N	—	—
34307-34500	—	127 mm	77,788 mm	Open	93.500 N	136.000 N	—	—
344-332	—	80 mm	40 mm	Open	68.000 N	75.000 N	—	—
3476-3420	—	79,375 mm	31,750 mm	Open	93.000 N	114.000 N	—	—
3478-3420	—	79,375 mm	34,925 mm	Open	93.000 N	114.000 N	—	—
3479-3420	—	79,375 mm	36,512 mm	Open	93.000 N	114.000 N	—	—
3490-3420	—	79,375 mm	38,100 mm	Open	93.000 N	114.000 N	—	—
350A-354A	—	85,001 mm	40 mm	Open	69.500 N	79.500 N	—	—
355-354A	—	85,001 mm	44,450 mm	Open	69.500 N	79.500 N	—	—
3576-3525	—	87,313 mm	41,275 mm	Open	94.000 N	117.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
3578-3520	—	84,138 mm	44,450 mm	Open	94.000 N	117.000 N	—	—
3578-3525	—	87,313 mm	44,450 mm	Open	94.000 N	117.000 N	—	—
3578A-3525	—	87,313 mm	44,450 mm	Open	94.000 N	117.000 N	—	—
3579-3525	—	87,313 mm	42,862 mm	Open	94.000 N	117.000 N	—	—
3580-3525	—	87,313 mm	38,100 mm	Open	94.000 N	117.000 N	—	—
358-354A	—	85,001 mm	45 mm	Open	69.500 N	79.500 N	—	—
3585-3525	—	87,313 mm	41,275 mm	Open	94.000 N	117.000 N	—	—
3586-3525	—	87,313 mm	45,237 mm	Open	94.000 N	117.000 N	—	—
358X-354A	—	85,001 mm	45 mm	Open	69.500 N	79.500 N	—	—
359A-354A	—	85,001 mm	46,038 mm	Open	69.500 N	79.500 N	—	—
359S-352	—	90,119 mm	46,038 mm	Open	69.500 N	79.500 N	—	—
365-362	—	90 mm	50 mm	Open	84.000 N	103.000 N	—	—
365-362A	—	88,900 mm	50 mm	Open	84.000 N	103.000 N	—	—
365-363	—	90 mm	50 mm	Open	84.000 N	103.000 N	—	—
365A-362	—	90 mm	50 mm	Open	84.000 N	103.000 N	—	—
365A-362A	—	88,900 mm	50 mm	Open	84.000 N	103.000 N	—	—
365A-363	—	90 mm	50 mm	Open	84.000 N	103.000 N	—	—
365S-362	—	90 mm	49,213 mm	Open	84.000 N	103.000 N	—	—
365S-362A	—	88,900 mm	49,213 mm	Open	84.000 N	103.000 N	—	—
365S-363	—	90 mm	49,213 mm	Open	84.000 N	103.000 N	—	—
366-362A	—	88,900 mm	50 mm	Open	84.000 N	103.000 N	—	—
366-363	—	90 mm	50 mm	Open	84.000 N	103.000 N	—	—
366-363D-A	—	90 mm	50 mm	Open	84.000 N	103.000 N	—	—
36690-36620	—	193,675 mm	146,050 mm	Open	185.000 N	400.000 N	1.600 RPM	—
36690-36626	—	203,200 mm	146,050 mm	Open	185.000 N	400.000 N	—	—
36691-36620	—	193,675 mm	146,050 mm	Open	185.000 N	400.000 N	—	—
36691-36626	—	203,200 mm	146,050 mm	Open	185.000 N	400.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
367-362	—	90 mm	45 mm	Open	84.000 N	103.000 N	—	—
367-362A	—	88,900 mm	45 mm	Open	84.000 N	103.000 N	—	—
367-363	—	90 mm	45 mm	Open	84.000 N	103.000 N	—	—
368-362	—	90 mm	50,800 mm	Open	84.000 N	103.000 N	—	—
368-362A	—	88,900 mm	50,800 mm	Open	84.000 N	103.000 N	—	—
368-363	—	90 mm	50,800 mm	Open	84.000 N	103.000 N	—	—
368A-362	—	90 mm	50,800 mm	Open	84.000 N	103.000 N	4.100 RPM	—
368A-362A	—	88,900 mm	50,800 mm	Open	84.000 N	103.000 N	—	—
368A-363	—	90 mm	50,800 mm	Open	84.000 N	103.000 N	—	—
368S-362	—	90 mm	51,592 mm	Open	84.000 N	103.000 N	—	—
368S-362A	—	88,900 mm	51,592 mm	Open	84.000 N	103.000 N	—	—
368S-363	—	90 mm	51,592 mm	Open	84.000 N	103.000 N	—	—
36990-36920	—	227,013 mm	177,800 mm	Open	197.000 N	465.000 N	—	—
369A-362	—	90 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
369A-362A	—	88,900 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
369A-363	—	90 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
369S-362	—	90 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
369S-362A	—	88,900 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
369S-363	—	90 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
370A-362	—	90 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
370A-362A	—	88,900 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
370A-363	—	90 mm	47,625 mm	Open	84.000 N	103.000 N	—	—
37425-37624	—	158,750 mm	107,950 mm	Open	107.000 N	180.000 N	—	—
37425-37625	—	158,750 mm	107,950 mm	Open	107.000 N	180.000 N	2.100 RPM	—
37431-37624	—	158,750 mm	109,538 mm	Open	107.000 N	180.000 N	—	—
37431-37625	—	158,750 mm	109,538 mm	Open	107.000 N	180.000 N	2.100 RPM	—
37431A-37624	—	158,750 mm	109,538 mm	Open	107.000 N	180.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
37431A-37625	—	158,750 mm	109,538 mm	Open	107.000 N	180.000 N	—	—
3767-3720	—	93,264 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767-3726	—	95,250 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767-3730	—	93,264 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767-3732	—	98,425 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767-3733	—	100,038 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767-3735	—	100,040 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767A-3720	—	93,264 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767A-3726	—	95,250 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767A-3730	—	93,264 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767A-3732	—	98,425 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767A-3733	—	100,038 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3767A-3735	—	100,040 mm	52,388 mm	Open	109.000 N	148.000 N	—	—
3774-3720	—	93,264 mm	39,688 mm	Open	109.000 N	148.000 N	—	—
3774-3726	—	95,250 mm	39,688 mm	Open	109.000 N	148.000 N	—	—
3774-3730	—	93,264 mm	39,688 mm	Open	109.000 N	148.000 N	—	—
3774-3732	—	98,425 mm	39,688 mm	Open	109.000 N	148.000 N	—	—
3774-3733	—	100,038 mm	39,688 mm	Open	109.000 N	148.000 N	—	—
3774-3735	—	100,040 mm	39,688 mm	Open	109.000 N	148.000 N	—	—
3775-3720	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3775-3726	—	95,250 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3775-3730	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3775-3732	—	98,425 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3775-3733	—	100,038 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3775-3735	—	100,040 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3776-3720	—	93,264 mm	44,983 mm	Open	109.000 N	148.000 N	—	—
3776-3726	—	95,250 mm	44,983 mm	Open	109.000 N	148.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
3776-3730	—	93,264 mm	44,983 mm	Open	109.000 N	148.000 N	—	—
3776-3732	—	98,425 mm	44,983 mm	Open	109.000 N	148.000 N	—	—
3776-3733	—	100,038 mm	44,983 mm	Open	109.000 N	148.000 N	—	—
3776-3735	—	100,040 mm	44,983 mm	Open	109.000 N	148.000 N	—	—
3777-3720	—	93,264 mm	46,038 mm	Open	109.000 N	148.000 N	—	—
3777-3726	—	95,250 mm	46,038 mm	Open	109.000 N	148.000 N	—	—
3777-3730	—	93,264 mm	46,038 mm	Open	109.000 N	148.000 N	—	—
3777-3732	—	98,425 mm	46,038 mm	Open	109.000 N	148.000 N	—	—
3777-3733	—	100,038 mm	46,038 mm	Open	109.000 N	148.000 N	—	—
3777-3735	—	100,040 mm	46,038 mm	Open	109.000 N	148.000 N	—	—
3778-3720	—	93,264 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3778-3726	—	95,250 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3778-3730	—	93,264 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3778-3732	—	98,425 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3778-3733	—	100,038 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3778-3735	—	100,040 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3779-3720	—	93,264 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3779-3726	—	95,250 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3779-3730	—	93,264 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3779-3733	—	100,038 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3779-3735	—	100,040 mm	47,625 mm	Open	109.000 N	148.000 N	—	—
3780-3720	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3780-3726	—	95,250 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3780-3730	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3780-3732	—	98,425 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3780-3733	—	100,038 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3780-3735	—	100,040 mm	50,800 mm	Open	109.000 N	148.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
3781-3720	—	93,264 mm	49,212 mm	Open	109.000 N	148.000 N	—	—
3781-3726	—	95,250 mm	49,212 mm	Open	109.000 N	148.000 N	—	—
3781-3730	—	93,264 mm	49,212 mm	Open	109.000 N	148.000 N	—	—
3781-3732	—	98,425 mm	49,212 mm	Open	109.000 N	148.000 N	—	—
3781-3733	—	100,038 mm	49,212 mm	Open	109.000 N	148.000 N	—	—
3781-3735	—	100,040 mm	49,212 mm	Open	109.000 N	148.000 N	—	—
3781A-3720	—	93,264 mm	48,412 mm	Open	109.000 N	148.000 N	—	—
3781A-3726	—	95,250 mm	48,412 mm	Open	109.000 N	148.000 N	—	—
3781A-3730	—	93,264 mm	48,412 mm	Open	109.000 N	148.000 N	—	—
3781A-3732	—	98,425 mm	48,412 mm	Open	109.000 N	148.000 N	—	—
3781A-3733	—	100,038 mm	48,412 mm	Open	109.000 N	148.000 N	—	—
3781A-3735	—	100,040 mm	48,412 mm	Open	109.000 N	148.000 N	—	—
3782-3720	—	93,264 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3782-3726	—	95,250 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3782-3730	—	93,264 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3782-3732	—	98,425 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3782-3733	—	100,038 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3782-3735	—	100,040 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3783-3720	—	93,264 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3783-3726	—	95,250 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3783-3730	—	93,264 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3783-3732	—	98,425 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3783-3733	—	100,038 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3783-3735	—	100,040 mm	44,450 mm	Open	109.000 N	148.000 N	—	—
3784-3720	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3784-3726	—	95,250 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3784-3730	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
3784-3732	—	98,425 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3784-3733	—	100,038 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3784-3735	—	100,040 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3795-3720	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3795-3726	—	95,250 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3795-3730	—	93,264 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3795-3732	—	98,425 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3795-3733	—	100,038 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
3795-3735	—	100,040 mm	50,800 mm	Open	109.000 N	148.000 N	—	—
385-362A	—	88,900 mm	55 mm	Open	82.500 N	105.000 N	—	—
385-382	—	98,425 mm	55 mm	Open	82.500 N	105.000 N	—	—
385-382A	—	96,838 mm	55 mm	Open	82.500 N	105.000 N	—	—
385-382S	—	96,838 mm	55 mm	Open	82.500 N	105.000 N	—	—
385A-382	—	98,425 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385A-382A	—	96,838 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385A-382S	—	96,838 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385A-383A	—	100 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385AX-382	—	98,425 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385AX-382A	—	96,838 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385AX-382S	—	96,838 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385AX-383A	—	100 mm	50,800 mm	Open	82.500 N	105.000 N	—	—
385X-382	—	98,425 mm	55,001 mm	Open	82.500 N	105.000 N	—	—
385X-382A	—	96,838 mm	55,001 mm	Open	82.500 N	105.000 N	—	—
385X-382S	—	96,838 mm	55,001 mm	Open	82.500 N	105.000 N	—	—
385X-383A	—	100 mm	55,001 mm	Open	82.500 N	105.000 N	—	—
386A-382	—	98,425 mm	47,625 mm	Open	82.500 N	105.000 N	—	—
386A-382A	—	96,838 mm	47,625 mm	Open	82.500 N	105.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
386A-382S	—	96,838 mm	47,625 mm	Open	82.500 N	105.000 N	—	—
386A-383A	—	100 mm	47,625 mm	Open	82.500 N	105.000 N	—	—
387-382	—	98,425 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387-382A	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387-382S	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387-383A	—	100 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
3875-3820	—	85,725 mm	38,100 mm	Open	105.000 N	132.000 N	—	—
3876-3820	—	85,725 mm	38,100 mm	Open	105.000 N	132.000 N	—	—
3877-3820	—	85,725 mm	41,275 mm	Open	105.000 N	132.000 N	—	—
387A-382	—	98,425 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387A-382A	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387A-382S	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387A-383A	—	100 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387AS-382	—	98,425 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387AS-382A	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387AS-382S	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387AS-383A	—	100 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387S-382	—	98,425 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387S-382A	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387S-382S	—	96,838 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
387S-383A	—	100 mm	57,150 mm	Open	82.500 N	105.000 N	—	—
38800-38820	—	325,438 mm	263,525 mm	Open	226.000 N	570.000 N	—	—
3880-3820	—	85,725 mm	41,275 mm	Open	105.000 N	132.000 N	—	—
38885-38820	—	325,438 mm	266,700 mm	Open	226.000 N	570.000 N	—	—
388A-382	—	98,425 mm	57,531 mm	Open	82.500 N	105.000 N	—	—
388A-382A	—	96,838 mm	57,531 mm	Open	82.500 N	105.000 N	—	—
388A-382S	—	96,838 mm	57,531 mm	Open	82.500 N	105.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
388A-383A	—	100 mm	57,531 mm	Open	82.500 N	105.000 N	—	—
389-382	—	98,425 mm	55,575 mm	Open	82.500 N	10.500 N	—	—
389-382A	—	96,838 mm	55,575 mm	Open	82.500 N	10.500 N	—	—
389-382S	—	96,838 mm	55,575 mm	Open	82.500 N	10.500 N	—	—
389-383A	—	100 mm	55,575 mm	Open	82.500 N	10.500 N	—	—
389A-382	—	98,425 mm	53,975 mm	Open	82.500 N	105.000 N	—	—
389A-382A	—	96,838 mm	53,975 mm	Open	82.500 N	105.000 N	—	—
389A-382S	—	96,838 mm	53,975 mm	Open	82.500 N	105.000 N	—	—
389A-383A	—	100 mm	53,975 mm	Open	82.500 N	105.000 N	—	—
390-394A	—	110 mm	57,150 mm	Open	90.000 N	123.000 N	3.200 RPM	—
390-394AS	—	110 mm	57,150 mm	Open	90.000 N	123.000 N	—	—
390-394CS	—	113,487 mm	57,150 mm	Open	90.000 N	123.000 N	—	—
390A-394A	—	110 mm	63,500 mm	Open	90.000 N	123.000 N	3.200 RPM	—
390A-394AS	—	110 mm	63,500 mm	Open	90.000 N	123.000 N	—	—
390A-394CS	—	113,487 mm	63,500 mm	Open	90.000 N	123.000 N	—	—
392-394A	—	110 mm	61,912 mm	Open	90.000 N	123.000 N	—	—
392-394AS	—	110 mm	61,912 mm	Open	90.000 N	123.000 N	—	—
392-394CS	—	113,487 mm	61,912 mm	Open	90.000 N	123.000 N	—	—
39250-39412	—	104,775 mm	63,500 mm	Open	91.500 N	123.000 N	—	—
39250-39412DFD0CB35	—	104,775 mm	63,500 mm	Open	91.500 N	123.000 N	—	—
39250-39422	—	107,158 mm	63,500 mm	Open	91.500 N	123.000 N	—	—
395-394A	—	110 mm	63,500 mm	Open	90.000 N	123.000 N	—	—
395-394AS	—	110 mm	63,500 mm	Open	90.000 N	123.000 N	—	—
395-394CS	—	113,487 mm	63,500 mm	Open	90.000 N	123.000 N	—	—
39573-39520	—	112,713 mm	50,800 mm	Open	153.000 N	223.000 N	—	—
39573-39521	—	112,713 mm	50,800 mm	Open	153.000 N	223.000 N	—	—
39575-39520	—	112,713 mm	50,800 mm	Open	153.000 N	223.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
39575-39521	—	112,713 mm	50,800 mm	Open	153.000 N	223.000 N	—	—
39578-39520	—	112,712 mm	53,975 mm	Open	153.000 N	223.000 N	—	—
39578-39521	—	112,713 mm	53,975 mm	Open	153.000 N	223.000 N	—	—
39580-39520	—	112,713 mm	57,150 mm	Open	153.000 N	223.000 N	3.200 RPM	—
39580-39521	—	112,713 mm	57,150 mm	Open	153.000 N	223.000 N	—	—
39581-39520	—	112,713 mm	57,150 mm	Open	153.000 N	223.000 N	—	—
39581-39521	—	112,713 mm	57,150 mm	Open	153.000 N	223.000 N	—	—
39585-39520	—	112,713 mm	63,500 mm	Open	153.000 N	223.000 N	3.200 RPM	—
39585-39521	—	112,713 mm	63,500 mm	Open	153.000 N	223.000 N	—	—
39585A-39520	—	112,713 mm	63,500 mm	Open	153.000 N	223.000 N	—	—
39585A-39521	—	112,713 mm	63,500 mm	Open	153.000 N	223.000 N	—	—
39586-39520	—	112,713 mm	64,988 mm	Open	153.000 N	223.000 N	—	—
39586-39521	—	112,713 mm	64,988 mm	Open	153.000 N	223.000 N	—	—
39589-39520	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
39589-39521	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
39590-39520DB-3-03	—	112,712 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
39590-39521	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
39590A-39520	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
39590A-39521	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
39591-39520	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	3.200 RPM	—
39591-39521	—	112,713 mm	66,675 mm	Open	153.000 N	223.000 N	—	—
395A-394A	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395A-394AS	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395A-394CS	—	113,487 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395CS-394A	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395CS-394AS	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395CS-394CS	—	113,487 mm	66,675 mm	Open	90.000 N	123.000 N	3.200 RPM	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
395ES-394A	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395ES-394AS	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395ES-394CS	—	113,487 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395S-394A	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395S-394AS	—	110 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
395S-394CS	—	113,487 mm	66,675 mm	Open	90.000 N	123.000 N	—	—
396-3920	—	112,712 mm	50 mm	Open	90.000 N	123.000 N	3.200 RPM	—
396-394A	—	110 mm	50 mm	Open	90.000 N	123.000 N	—	—
396-394AS	—	110 mm	50 mm	Open	90.000 N	123.000 N	—	—
396-394CS	—	113,487 mm	50 mm	Open	90.000 N	123.000 N	—	—
397-394A	—	110 mm	60 mm	Open	90.000 N	123.000 N	3.200 RPM	—
397-394AS	—	110 mm	60 mm	Open	90.000 N	123.000 N	—	—
397-394CS	—	113,487 mm	60 mm	Open	90.000 N	123.000 N	—	—
3975-3920	—	112,712 mm	50,800 mm	Open	125.000 N	187.000 N	—	—
3977-3920	—	112,712 mm	60 mm	Open	125.000 N	187.000 N	3.200 RPM	—
3979-3920	—	112,712 mm	57,150 mm	Open	125.000 N	187.000 N	3.200 RPM	—
3980-3920	—	112,712 mm	60,325 mm	Open	125.000 N	187.000 N	—	—
3982-3920	—	112,712 mm	63,500 mm	Open	125.000 N	187.000 N	3.200 RPM	—
3982-3926	—	112,712 mm	63,500 mm	Open	125.000 N	187.000 N	3.200 RPM	—
398-394A	—	110 mm	50,800 mm	Open	90.000 N	123.000 N	—	—
398-394AS	—	110 mm	50,800 mm	Open	90.000 N	123.000 N	—	—
398-394CS	—	113,487 mm	50,800 mm	Open	90.000 N	123.000 N	—	—
3984-3920	—	112,712 mm	66,675 mm	Open	125.000 N	187.000 N	3.200 RPM	—
3984-3925	—	112,712 mm	66,675 mm	Open	125.000 N	187.000 N	—	—
3994-3920	—	112,712 mm	66,675 mm	Open	125.000 N	187.000 N	3.200 RPM	—
399A-394A	—	110 mm	68,263 mm	Open	90.000 N	123.000 N	—	—
399A-394AS	—	110 mm	68,263 mm	Open	90.000 N	123.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
399A-394CS	—	113,487 mm	68,263 mm	Open	90.000 N	123.000 N	—	—
399AS-394A	—	110 mm	68,263 mm	Open	90.000 N	123.000 N	—	—
399AS-394AS	—	110 mm	68,263 mm	Open	90.000 N	123.000 N	—	—
399AS-394CS	—	113,487 mm	68,263 mm	Open	90.000 N	123.000 N	—	—
41125-41286	—	72,626 mm	28,575 mm	Open	58.000 N	55.500 N	—	—
418-414	—	88,501 mm	38,100 mm	Open	95.500 N	107.000 N	—	—
420-414	—	88,501 mm	40 mm	Open	95.500 N	107.000 N	—	—
42346-42584	—	148,430 mm	87,960 mm	Open	150.000 N	242.000 N	—	—
42346-42585	—	148,430 mm	87,960 mm	Open	150.000 N	242.000 N	—	—
42346-42586	—	148,430 mm	87,960 mm	Open	150.000 N	242.000 N	—	—
42346-42587	—	149,225 mm	87,960 mm	Open	150.000 N	242.000 N	—	—
42350-42584	—	148,430 mm	88,900 mm	Open	150.000 N	242.000 N	—	—
42350-42585	—	148,430 mm	88,900 mm	Open	150.000 N	242.000 N	—	—
42350-42586	—	148,430 mm	88,900 mm	Open	150.000 N	242.000 N	—	—
42350-42587	—	149,225 mm	88,900 mm	Open	150.000 N	242.000 N	—	—
42362-42584	—	148,430 mm	92,075 mm	Open	150.000 N	242.000 N	—	—
42362-42585	—	148,430 mm	92,075 mm	Open	150.000 N	242.000 N	—	—
42362-42586	—	148,430 mm	92,075 mm	Open	150.000 N	242.000 N	—	—
42362-42587	—	149,225 mm	92,075 mm	Open	150.000 N	242.000 N	—	—
42368-42584	—	148,430 mm	93,662 mm	Open	150.000 N	242.000 N	—	—
42368-42585	—	148,430 mm	93,662 mm	Open	150.000 N	242.000 N	—	—
42368-42586	—	148,430 mm	93,662 mm	Open	150.000 N	242.000 N	—	—
42368-42587	—	149,225 mm	93,662 mm	Open	150.000 N	242.000 N	—	—
42375-42584	—	148,430 mm	95,250 mm	Open	150.000 N	242.000 N	2.300 RPM	—
42375-42585	—	148,430 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
42375-42586	—	148,430 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
42375-42587	—	149,225 mm	95,250 mm	Open	150.000 N	242.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
42376-42584	—	148,430 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
42376-42585	—	148,430 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
42376-42586	—	148,430 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
42376-42587	—	149,225 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
42381-42584	—	148,430 mm	96,838 mm	Open	150.000 N	242.000 N	2.300 RPM	—
42381-42585	—	148,430 mm	96,838 mm	Open	150.000 N	242.000 N	—	—
42381-42586	—	148,430 mm	96,838 mm	Open	150.000 N	242.000 N	—	—
42381-42587	—	149,225 mm	96,838 mm	Open	150.000 N	242.000 N	2.300 RPM	—
42381-42587D-AD-01	—	149,225 mm	96,838 mm	Open	150.000 N	242.000 N	—	—
42687-42620	—	127 mm	76,200 mm	Open	142.000 N	213.000 N	—	—
42688-42620	—	127 mm	76,200 mm	Open	142.000 N	213.000 N	—	—
42690-42620	—	127 mm	77,788 mm	Open	142.000 N	213.000 N	2.800 RPM	—
43131-43312	—	79,375 mm	33,338 mm	Open	65.500 N	67.000 N	—	—
436-432	—	95,250 mm	46,038 mm	Open	108.000 N	129.000 N	—	—
438-432	—	95,250 mm	44,450 mm	Open	108.000 N	129.000 N	—	—
4388-4335	—	90,488 mm	41,275 mm	Open	136.000 N	175.000 N	4.300 RPM	—
4395-4335	—	90,488 mm	42,070 mm	Open	136.000 N	175.000 N	—	—
44143-44348	—	88,501 mm	36,512 mm	Open	70.500 N	78.000 N	—	—
44143-44348PX2	—	88,500 mm	36,512 mm	Open	70.500 N	78.000 N	—	—
44150-44348	—	88,501 mm	38,100 mm	Open	70.500 N	78.000 N	—	—
44158-44348	—	88,501 mm	39,688 mm	Open	70.500 N	78.000 N	—	—
44162-44348	—	88,501 mm	41,275 mm	Open	70.500 N	78.000 N	—	—
45282-45220	—	104,775 mm	47,625 mm	Open	139.000 N	188.000 N	—	—
45285-45220	—	104,775 mm	50,800 mm	Open	139.000 N	188.000 N	—	—
45285A-45220	—	104,775 mm	50,800 mm	Open	139.000 N	188.000 N	—	—
45287-45220	—	104,775 mm	53,975 mm	Open	139.000 N	188.000 N	3.500 RPM	—
45289-45220	—	104,775 mm	57,150 mm	Open	139.000 N	188.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
45290-45220	—	104,775 mm	57,150 mm	Open	139.000 N	188.000 N	3.500 RPM	—
45291-45220	—	104,775 mm	57,150 mm	Open	139.000 N	188.000 N	3.500 RPM	—
4553-4520	—	101,200 mm	53,975 mm	Open	163.000 N	235.000 N	—	—
4553-4535	—	104,775 mm	53,975 mm	Open	163.000 N	235.000 N	—	—
4553-4536	—	111,125 mm	53,975 mm	Open	163.000 N	235.000 N	—	—
455-452	—	107,950 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
455-453A	—	107,950 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
455-453X	—	104,775 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
455-454	—	110 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
4559-4520	—	101,200 mm	45,001 mm	Open	163.000 N	235.000 N	—	—
4559-4535	—	104,775 mm	45 mm	Open	163.000 N	235.000 N	—	—
4559-4536	—	111,125 mm	45,001 mm	Open	163.000 N	235.000 N	—	—
455S-452	—	107,950 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
455S-453A	—	107,950 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
455S-453X	—	104,775 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
455S-454	—	110 mm	50,800 mm	Open	123.000 N	163.000 N	—	—
456-452	—	107,950 mm	53,975 mm	Open	123.000 N	163.000 N	—	—
456-453A	—	107,950 mm	53,975 mm	Open	123.000 N	163.000 N	—	—
456-453X	—	104,775 mm	53,975 mm	Open	123.000 N	163.000 N	—	—
456-454	—	110 mm	53,975 mm	Open	123.000 N	163.000 N	—	—
4580-4520	—	101,200 mm	50,800 mm	Open	163.000 N	235.000 N	—	—
4580-4535	—	104,775 mm	50,800 mm	Open	163.000 N	235.000 N	—	—
4580-4536	—	111,125 mm	50,800 mm	Open	163.000 N	235.000 N	—	—
458S-452	—	107,950 mm	45,001 mm	Open	123.000 N	163.000 N	—	—
458S-453A	—	107,950 mm	45,001 mm	Open	123.000 N	163.000 N	—	—
458S-453X	—	104,775 mm	45,001 mm	Open	123.000 N	163.000 N	—	—
458S-454	—	110 mm	45,001 mm	Open	123.000 N	163.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
4595-4520	—	101,200 mm	53,975 mm	Open	163.000 N	235.000 N	—	—
4595-4535	—	104,775 mm	53,975 mm	Open	163.000 N	235.000 N	—	—
4595-4536	—	111,125 mm	53,975 mm	Open	163.000 N	235.000 N	—	—
460-452	—	107,950 mm	44,450 mm	Open	123.000 N	163.000 N	—	—
460-453A	—	107,950 mm	44,450 mm	Open	123.000 N	163.000 N	—	—
460-453X	—	104,775 mm	44,450 mm	Open	123.000 N	163.000 N	—	—
460-454	—	110 mm	44,450 mm	Open	123.000 N	163.000 N	—	—
46162-46368	—	93,670 mm	41,275 mm	Open	103.000 N	131.000 N	—	—
46175-46368	—	93,670 mm	44,450 mm	Open	103.000 N	131.000 N	—	—
462-452	—	107,950 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462-453A	—	107,950 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462-453X	—	104,775 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462-454	—	110 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462A-452	—	107,950 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462A-453A	—	107,950 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462A-453X	—	104,775 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
462A-454	—	110 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
463-452	—	107,950 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
463-453A	—	107,950 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
463-453X	—	104,775 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
463-454	—	110 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
466-452	—	107,950 mm	54,988 mm	Open	123.000 N	163.000 N	—	—
466-453A	—	107,950 mm	54,988 mm	Open	123.000 N	163.000 N	—	—
466-453X	—	104,775 mm	54,988 mm	Open	123.000 N	163.000 N	—	—
466-454	—	110 mm	54,988 mm	Open	123.000 N	163.000 N	—	—
467-452	—	107,950 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
467-453A	—	107,950 mm	47,625 mm	Open	123.000 N	163.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
467-453X	—	104,775 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
467-454	—	110 mm	47,625 mm	Open	123.000 N	163.000 N	—	—
46780-46720	—	225,425 mm	158,750 mm	Open	280.000 N	635.000 N	—	—
46780-46720D-AC120	—	225,425 mm	158,750 mm	Open	280.000 N	635.000 N	—	—
46790-46720	—	225,425 mm	165,100 mm	Open	280.000 N	635.000 N	—	—
46792-46720	—	225,425 mm	166,688 mm	Open	280.000 N	635.000 N	—	—
468-452	—	107,950 mm	52,388 mm	Open	123.000 N	163.000 N	—	—
468-453A	—	107,950 mm	52,388 mm	Open	123.000 N	163.000 N	—	—
468-453X	—	104,775 mm	52,388 mm	Open	123.000 N	163.000 N	—	—
468-454	—	110 mm	52,388 mm	Open	123.000 N	163.000 N	—	—
469-453A	—	107,950 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
469-453X	—	104,775 mm	57,150 mm	Open	123.000 N	163.000 N	3.500 RPM	—
469-454	—	110 mm	57,150 mm	Open	123.000 N	163.000 N	—	—
47487-47420	—	120 mm	69,850 mm	Open	164.000 N	249.000 N	—	—
47490-47420	—	120 mm	71,438 mm	Open	164.000 N	249.000 N	3.000 RPM	—
475-472	—	120 mm	55,001 mm	Open	130.000 N	184.000 N	—	—
475-472A	—	120 mm	55,001 mm	Open	130.000 N	184.000 N	—	—
475-472X	—	123,825 mm	55,001 mm	Open	130.000 N	184.000 N	—	—
475-473	—	120 mm	55,001 mm	Open	130.000 N	184.000 N	—	—
476-472	—	120 mm	60 mm	Open	130.000 N	184.000 N	—	—
476-472A	—	120 mm	60 mm	Open	130.000 N	184.000 N	—	—
476-472X	—	123,825 mm	60 mm	Open	130.000 N	184.000 N	—	—
476-473	—	120 mm	60 mm	Open	130.000 N	184.000 N	—	—
47675-47620	—	133,350 mm	71,438 mm	Open	171.000 N	274.000 N	—	—
47675-47620A	—	133,350 mm	71,438 mm	Open	171.000 N	274.000 N	—	—
47675-47622W	—	136,525 mm	71,438 mm	Open	171.000 N	274.000 N	—	—
47675-47623A	—	136,525 mm	71,438 mm	Open	171.000 N	274.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
47678-47620	—	133,350 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47678-47620A	—	133,350 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47678-47622W	—	136,525 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47678-47623A	—	136,525 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47679-47620	—	133,350 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47679-47620A	—	133,350 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47679-47622W	—	136,525 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47679-47623A	—	136,525 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47680-47620	—	133,350 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47680-47620A	—	133,350 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47680-47622W	—	136,525 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47680-47623A	—	136,525 mm	76,200 mm	Open	171.000 N	274.000 N	—	—
47681-47620	—	133,350 mm	80,962 mm	Open	171.000 N	274.000 N	—	—
47681-47620A	—	133,350 mm	80,962 mm	Open	171.000 N	274.000 N	—	—
47681-47622W	—	136,525 mm	80,962 mm	Open	171.000 N	274.000 N	—	—
47681-47623A	—	136,525 mm	80,962 mm	Open	171.000 N	274.000 N	—	—
47685-47620	—	133,350 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47685-47620A	—	133,350 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47685-47622W	—	136,525 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47685-47623A	—	136,525 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47686-47620	—	133,350 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47686-47620A	—	133,350 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47686-47622W	—	136,525 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47686-47623A	—	136,525 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47687-47620	—	133,350 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47687-47620A	—	133,350 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
47687-47622W	—	136,525 mm	82,550 mm	Open	171.000 N	274.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
47687-47623A	—	136,525 mm	82,550 mm	Open	171.000 N	274.000 N	—	—
477-472	—	120 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
477-472A	—	120 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
477-472X	—	123,825 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
477-473	—	120 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
478-472	—	120 mm	65,001 mm	Open	130.000 N	184.000 N	—	—
478-472A	—	120 mm	65,001 mm	Open	130.000 N	184.000 N	—	—
478-472X	—	123,825 mm	65,001 mm	Open	130.000 N	184.000 N	—	—
478-473	—	120 mm	65,001 mm	Open	130.000 N	184.000 N	—	—
47896-47820	—	146,050 mm	95,250 mm	Open	182.000 N	310.000 N	2.400 RPM	—
47896-47820DB-56-01	—	146,050 mm	95,250 mm	Open	182.000 N	310.000 N	—	—
479-472	—	120 mm	66,675 mm	Open	130.000 N	184.000 N	—	—
479-472A	—	120 mm	66,675 mm	Open	130.000 N	184.000 N	—	—
479-472X	—	123,825 mm	66,675 mm	Open	130.000 N	184.000 N	—	—
479-473	—	120 mm	66,675 mm	Open	130.000 N	184.000 N	—	—
480-472	—	120 mm	68,262 mm	Open	130.000 N	184.000 N	—	—
480-472A	—	120 mm	68,262 mm	Open	130.000 N	184.000 N	—	—
480-472X	—	123,825 mm	68,262 mm	Open	130.000 N	184.000 N	—	—
480-473	—	120 mm	68,262 mm	Open	130.000 N	184.000 N	—	—
48190-48120	—	161,925 mm	107,950 mm	Open	177.000 N	310.000 N	—	—
482-472	—	120 mm	69,850 mm	Open	130.000 N	184.000 N	—	—
482-472A	—	120 mm	69,850 mm	Open	130.000 N	184.000 N	—	—
482-472D-ACS204	—	120 mm	69,850 mm	Open	130.000 N	184.000 N	—	—
482-472X	—	123,825 mm	69,850 mm	Open	130.000 N	184.000 N	—	—
482-473	—	120 mm	69,850 mm	Open	130.000 N	184.000 N	—	—
48286-48220	—	182,563 mm	123,825 mm	Open	247.000 N	495.000 N	1.800 RPM	—
48290-48220	—	182,563 mm	127 mm	Open	247.000 N	495.000 N	1.800 RPM	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
48290-48220D-AC4	—	182,563 mm	127 mm	Open	247.000 N	495.000 N	—	—
483-472	—	120 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
483-472A	—	120 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
483-472X	—	123,825 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
483-473	—	120 mm	63,500 mm	Open	130.000 N	184.000 N	—	—
48384A-48320	—	190,500 mm	133,248 mm	Open	261.000 N	545.000 N	—	—
48385-48320	—	190,500 mm	133,350 mm	Open	261.000 N	545.000 N	1.700 RPM	—
48385A-48320	—	190,500 mm	133,350 mm	Open	261.000 N	545.000 N	—	—
48393-48320	—	190,500 mm	136,525 mm	Open	261.000 N	545.000 N	1.700 RPM	—
48393-48320D-A	—	190,500 mm	136,525 mm	Open	261.000 N	545.000 N	—	—
48393A-48320	—	190,500 mm	136,525 mm	Open	261.000 N	545.000 N	—	—
484-472	—	120 mm	70 mm	Open	130.000 N	184.000 N	—	—
484-472A	—	120 mm	70 mm	Open	130.000 N	184.000 N	—	—
484-473	—	120 mm	70 mm	Open	130.000 N	184.000 N	—	—
48506-48750	—	190,500 mm	128,588 mm	Open	216.000 N	405.000 N	—	—
48684-48620	—	200,025 mm	142,875 mm	Open	263.000 N	560.000 N	—	—
48685-48620	—	200,025 mm	142,875 mm	Open	263.000 N	560.000 N	1.600 RPM	—
495-492A	—	133,350 mm	82,550 mm	Open	140.000 N	213.000 N	—	—
495-493	—	136,525 mm	82,550 mm	Open	140.000 N	213.000 N	2.600 RPM	—
495-493D-ACB90	—	136,525 mm	82,550 mm	Open	140.000 N	213.000 N	—	—
49576-49520	—	101,600 mm	44,450 mm	Open	122.000 N	156.000 N	—	—
49576-49521	—	101,600 mm	44,450 mm	Open	122.000 N	156.000 N	—	—
49576-49522	—	101,600 mm	44,450 mm	Open	122.000 N	156.000 N	—	—
49577-49520	—	101,600 mm	44,450 mm	Open	122.000 N	156.000 N	—	—
49577-49521	—	101,600 mm	44,450 mm	Open	122.000 N	156.000 N	—	—
49577-49522	—	101,600 mm	44,450 mm	Open	122.000 N	156.000 N	—	—
49580-49520	—	101,600 mm	47,625 mm	Open	122.000 N	156.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
49580-49521	—	101,600 mm	47,625 mm	Open	122.000 N	156.000 N	—	—
49580-49522	—	101,600 mm	47,625 mm	Open	122.000 N	156.000 N	—	—
49585-49520	—	101,600 mm	50,800 mm	Open	122.000 N	156.000 N	—	—
49585-49521	—	101,600 mm	50,800 mm	Open	122.000 N	156.000 N	—	—
49585-49522	—	101,600 mm	50,800 mm	Open	122.000 N	156.000 N	—	—
495A-492A	—	133,350 mm	76,200 mm	Open	140.000 N	213.000 N	2.600 RPM	—
495A-493	—	136,525 mm	76,200 mm	Open	140.000 N	213.000 N	2.600 RPM	—
495AS-492A	—	133,350 mm	77,788 mm	Open	140.000 N	213.000 N	—	—
495AS-493	—	136,525 mm	77,788 mm	Open	140.000 N	213.000 N	—	—
495AX-492A	—	133,350 mm	76,200 mm	Open	140.000 N	213.000 N	—	—
495AX-493	—	136,525 mm	76,200 mm	Open	140.000 N	213.000 N	—	—
495S-492A	—	133,350 mm	71,438 mm	Open	140.000 N	213.000 N	—	—
495S-493	—	136,525 mm	71,438 mm	Open	140.000 N	213.000 N	—	—
496-492A	—	133,350 mm	80,962 mm	Open	140.000 N	213.000 N	—	—
496-493	—	136,525 mm	80,962 mm	Open	140.000 N	213.000 N	—	—
496AS-492A	—	133,350 mm	81,699 mm	Open	140.000 N	213.000 N	—	—
496AS-493	—	136,525 mm	81,699 mm	Open	140.000 N	213.000 N	—	—
497-492A	—	133,350 mm	85,725 mm	Open	140.000 N	213.000 N	2.600 RPM	—
497-493	—	136,525 mm	85,725 mm	Open	140.000 N	213.000 N	2.600 RPM	—
497A-492A	—	133,350 mm	85,725 mm	Open	140.000 N	213.000 N	—	—
497A-493	—	136,525 mm	85,725 mm	Open	140.000 N	213.000 N	—	—
498-492A	—	133,350 mm	84,138 mm	Open	140.000 N	213.000 N	—	—
498-493	—	136,525 mm	84,138 mm	Open	140.000 N	213.000 N	—	—
4T-42375-42587DW-02	—	149,225 mm	95,250 mm	Open	150.000 N	242.000 N	—	—
4T-67790-67720CD-04	—	247,650 mm	177,800 mm	Open	370.000 N	780.000 N	—	—
4T-HH926749-HH92-02	—	273,050 mm	120,650 mm	Open	1.120.000 N	630.000 N	—	—
4T-JLM506849A-J-01	—	90 mm	55,001 mm	Open	77.500 N	109.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
4T-LL639249-LL63-01	—	241,300 mm	196,850 mm	Open	160.000 N	330.000 N	—	—
4T-LM104949E-LM-03	—	82,550 mm	50,800 mm	Open	—	—	—	—
4T-LM501349-4T-02	—	73,431 mm	41,275 mm	Open	56.000 N	69.500 N	—	—
52375-52618	—	157,163 mm	95,250 mm	Open	205.000 N	345.000 N	—	—
52375-52637	—	161,925 mm	95,250 mm	Open	205.000 N	345.000 N	—	—
52375-52638	—	161,925 mm	95,250 mm	Open	205.000 N	345.000 N	—	—
52375-52639	—	161,925 mm	95,250 mm	Open	205.000 N	345.000 N	—	—
52387-52618	—	157,163 mm	98,425 mm	Open	205.000 N	345.000 N	—	—
52387-52637	—	161,925 mm	98,425 mm	Open	205.000 N	345.000 N	—	—
52387-52638	—	161,925 mm	98,425 mm	Open	205.000 N	345.000 N	—	—
52387-52639	—	161,925 mm	98,425 mm	Open	205.000 N	345.000 N	—	—
52393-52618	—	157,163 mm	100,012 mm	Open	205.000 N	345.000 N	—	—
52393-52637	—	161,925 mm	100,012 mm	Open	205.000 N	345.000 N	—	—
52393-52638	—	161,925 mm	100,012 mm	Open	205.000 N	345.000 N	—	—
52393-52639	—	161,925 mm	100,012 mm	Open	205.000 N	345.000 N	—	—
52400-52618	—	157,163 mm	101,600 mm	Open	205.000 N	345.000 N	2.200 RPM	—
52400-52637	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52400-52638	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	2.200 RPM	—
52400-52639	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52400A-52618	—	157,163 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52400A-52637	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52400A-52638	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52400A-52639	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52401-52618	—	157,163 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52401-52637	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52401-52638	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—
52401-52639	—	161,925 mm	101,600 mm	Open	205.000 N	345.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
525-522	—	101,600 mm	38,100 mm	Open	148.000 N	187.000 N	—	—
525-532A	—	111,125 mm	38,100 mm	Open	148.000 N	187.000 N	—	—
525-532X	—	107,950 mm	38,100 mm	Open	148.000 N	187.000 N	—	—
526-522	—	101,600 mm	41,275 mm	Open	148.000 N	187.000 N	—	—
526-532A	—	111,125 mm	41,275 mm	Open	148.000 N	187.000 N	—	—
526-532X	—	107,950 mm	41,275 mm	Open	148.000 N	187.000 N	—	—
527-522	—	101,600 mm	44,450 mm	Open	148.000 N	187.000 N	—	—
527-532A	—	111,125 mm	44,450 mm	Open	148.000 N	187.000 N	—	—
527-532X	—	107,950 mm	44,450 mm	Open	148.000 N	187.000 N	—	—
527S-522	—	101,600 mm	44,983 mm	Open	148.000 N	187.000 N	—	—
527S-532A	—	111,125 mm	44,983 mm	Open	148.000 N	187.000 N	—	—
527S-532X	—	107,950 mm	44,983 mm	Open	148.000 N	187.000 N	—	—
528-522	—	101,600 mm	47,625 mm	Open	148.000 N	187.000 N	—	—
528-532A	—	111,125 mm	47,625 mm	Open	148.000 N	187.000 N	—	—
528-532X	—	107,950 mm	47,625 mm	Open	148.000 N	187.000 N	—	—
529-522	—	101,600 mm	50,800 mm	Open	148.000 N	187.000 N	—	—
529-532A	—	111,125 mm	50,800 mm	Open	148.000 N	187.000 N	—	—
529-532X	—	107,950 mm	50,800 mm	Open	148.000 N	187.000 N	—	—
529X-522	—	101,600 mm	50,800 mm	Open	148.000 N	187.000 N	—	—
529X-532A	—	111,125 mm	50,800 mm	Open	148.000 N	187.000 N	—	—
529X-532X	—	107,950 mm	50,800 mm	Open	148.000 N	187.000 N	—	—
53162-53375	—	95,250 mm	41,275 mm	Open	82.500 N	92.000 N	—	—
53177-53375	—	95,250 mm	44,450 mm	Open	82.500 N	92.000 N	—	—
535-522	—	101,600 mm	44,450 mm	Open	154.000 N	201.000 N	—	—
535-532A	—	111,125 mm	44,450 mm	Open	154.000 N	201.000 N	—	—
535-532X	—	107,950 mm	44,450 mm	Open	154.000 N	201.000 N	—	—
5356-5335	—	103,188 mm	44,450 mm	Open	189.000 N	263.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
5358-5335	—	103,188 mm	47,625 mm	Open	189.000 N	263.000 N	—	—
536-522	—	101,600 mm	47,625 mm	Open	154.000 N	201.000 N	—	—
536-532A	—	111,125 mm	47,625 mm	Open	154.000 N	201.000 N	—	—
536-532X	—	107,950 mm	47,625 mm	Open	154.000 N	201.000 N	—	—
537-522	—	101,600 mm	50,800 mm	Open	154.000 N	201.000 N	—	—
537-532A	—	111,125 mm	50,800 mm	Open	154.000 N	201.000 N	—	—
537-532X	—	107,950 mm	50,800 mm	Open	154.000 N	201.000 N	—	—
539-522	—	101,600 mm	53,975 mm	Open	154.000 N	201.000 N	—	—
539-532A	—	111,125 mm	53,975 mm	Open	154.000 N	201.000 N	3.600 RPM	—
539-532X	—	107,950 mm	53,975 mm	Open	154.000 N	201.000 N	—	—
5395-5335	—	103,188 mm	49,212 mm	Open	189.000 N	263.000 N	—	—
539A-522	—	101,600 mm	53,975 mm	Open	154.000 N	201.000 N	—	—
539A-532A	—	111,125 mm	53,975 mm	Open	154.000 N	201.000 N	—	—
539A-532X	—	107,950 mm	53,975 mm	Open	154.000 N	201.000 N	—	—
543085-543114	—	290,010 mm	215,900 mm	Open	223.000 N	455.000 N	—	—
543086-543114	—	290,010 mm	219,969 mm	Open	223.000 N	455.000 N	—	—
543-522	—	101,600 mm	40 mm	Open	154.000 N	201.000 N	—	—
543-532A	—	111,125 mm	40 mm	Open	154.000 N	201.000 N	—	—
543-532X	—	107,950 mm	40 mm	Open	154.000 N	201.000 N	3.600 RPM	—
544090-544116	—	295,275 mm	228,600 mm	Open	229.000 N	475.000 N	—	—
544090-544118	—	300,038 mm	228,600 mm	Open	229.000 N	475.000 N	—	—
544090-544118E1-3	—	300,038 mm	228,600 mm	Open	229.000 N	475.000 N	—	—
544091-544118	—	300,038 mm	231,775 mm	Open	229.000 N	475.000 N	—	—
55175C-55437	—	111,125 mm	44,450 mm	Open	115.000 N	157.000 N	3.200 RPM	—
55175C-55443	—	112,713 mm	44,450 mm	Open	115.000 N	157.000 N	—	—
55175CPW3-55437PW2	—	111,125 mm	44,450 mm	Open	115.000 N	157.000 N	—	—
55176C-55437	—	111,125 mm	44,450 mm	Open	115.000 N	157.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
55176C-55443	—	112,713 mm	44,450 mm	Open	115.000 N	157.000 N	—	—
55187C-55437	—	111,125 mm	47,625 mm	Open	115.000 N	157.000 N	3.200 RPM	—
55187C-55443	—	112,713 mm	47,625 mm	Open	115.000 N	157.000 N	—	—
55196C-55437	—	111,125 mm	49,975 mm	Open	115.000 N	157.000 N	—	—
55196C-55443	—	112,713 mm	49,975 mm	Open	115.000 N	157.000 N	—	—
55197C-55437	—	111,125 mm	43,099 mm	Open	115.000 N	157.000 N	—	—
55197C-55443	—	112,713 mm	43,099 mm	Open	115.000 N	157.000 N	—	—
55200C-55437	—	111,125 mm	50,800 mm	Open	115.000 N	157.000 N	3.200 RPM	—
55200C-55443	—	112,713 mm	50,800 mm	Open	115.000 N	157.000 N	—	—
55206-55444D-01	—	112,713 mm	52,388 mm	Open	157.000 N	216.000 N	—	—
55206C-55437	—	111,125 mm	52,388 mm	Open	115.000 N	157.000 N	—	—
55206C-55443	—	112,713 mm	52,388 mm	Open	115.000 N	157.000 N	—	—
55212C-55437	—	111,125 mm	53,975 mm	Open	115.000 N	157.000 N	—	—
55212C-55443	—	112,713 mm	53,975 mm	Open	115.000 N	157.000 N	—	—
554-552	—	123,825 mm	61,913 mm	Open	173.000 N	245.000 N	—	—
554-552A	—	123,825 mm	61,913 mm	Open	173.000 N	245.000 N	—	—
554-553X	—	122,238 mm	61,913 mm	Open	173.000 N	245.000 N	—	—
555-552	—	123,825 mm	50,800 mm	Open	173.000 N	245.000 N	—	—
555-552A	—	123,825 mm	50,800 mm	Open	173.000 N	245.000 N	—	—
555-553X	—	122,238 mm	50,800 mm	Open	173.000 N	245.000 N	—	—
5557-5520	—	120,251 mm	68,263 mm	Open	210.000 N	320.000 N	—	—
5557-5521	—	130 mm	68,263 mm	Open	210.000 N	320.000 N	—	—
5557-5535	—	122,238 mm	68,263 mm	Open	210.000 N	320.000 N	—	—
555S-552	—	123,825 mm	57,150 mm	Open	173.000 N	245.000 N	—	—
555S-552A	—	123,825 mm	57,150 mm	Open	173.000 N	245.000 N	—	—
555S-553X	—	122,238 mm	57,150 mm	Open	173.000 N	245.000 N	—	—
5565-5520	—	120,251 mm	50,800 mm	Open	210.000 N	320.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
5565-5521	—	130 mm	50,800 mm	Open	210.000 N	320.000 N	—	—
5565-5535	—	122,238 mm	50,800 mm	Open	210.000 N	320.000 N	—	—
5577-5520	—	120,251 mm	53,975 mm	Open	210.000 N	320.000 N	—	—
5577-5521	—	130 mm	53,975 mm	Open	210.000 N	320.000 N	—	—
5577-5535	—	122,238 mm	53,975 mm	Open	210.000 N	320.000 N	—	—
5578-5520	—	120,251 mm	53,975 mm	Open	210.000 N	320.000 N	—	—
5578-5521	—	130 mm	53,975 mm	Open	210.000 N	320.000 N	—	—
5578-5535	—	122,238 mm	53,975 mm	Open	210.000 N	320.000 N	3.100 RPM	—
557A-552	—	123,825 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
557A-552A	—	123,825 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
557A-553X	—	122,238 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
557S-552	—	123,825 mm	53,975 mm	Open	173.000 N	245.000 N	—	—
557S-552A	—	123,825 mm	53,975 mm	Open	173.000 N	245.000 N	3.000 RPM	—
557S-553X	—	122,238 mm	53,975 mm	Open	173.000 N	245.000 N	—	—
5582-5520	—	120,251 mm	60,325 mm	Open	210.000 N	320.000 N	—	—
5582-5521	—	130 mm	60,325 mm	Open	210.000 N	320.000 N	—	—
5582-5535	—	122,238 mm	60,325 mm	Open	210.000 N	320.000 N	—	—
5583-5520	—	120,251 mm	60,325 mm	Open	210.000 N	320.000 N	—	—
5583-5521	—	130 mm	60,325 mm	Open	210.000 N	320.000 N	—	—
5583-5535	—	122,238 mm	60,325 mm	Open	210.000 N	320.000 N	3.100 RPM	—
5584-5520	—	120,251 mm	63,500 mm	Open	210.000 N	320.000 N	—	—
5584-5521	—	130 mm	63,500 mm	Open	210.000 N	320.000 N	—	—
5584-5535	—	122,238 mm	63,500 mm	Open	210.000 N	320.000 N	3.100 RPM	—
558-552	—	123,825 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
558-552A	—	123,825 mm	60,325 mm	Open	173.000 N	245.000 N	3.000 RPM	—
558-553X	—	122,238 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
558A-552	—	123,825 mm	60,325 mm	Open	173.000 N	245.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
558A-552A	—	123,825 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
558A-553X	—	122,238 mm	60,325 mm	Open	173.000 N	245.000 N	—	—
558S-552	—	123,825 mm	59,987 mm	Open	173.000 N	245.000 N	—	—
558S-552A	—	123,825 mm	59,987 mm	Open	173.000 N	245.000 N	—	—
558S-553X	—	122,238 mm	59,987 mm	Open	173.000 N	245.000 N	—	—
559-552	—	123,825 mm	63,500 mm	Open	173.000 N	245.000 N	—	—
559-552A	—	123,825 mm	63,500 mm	Open	173.000 N	245.000 N	—	—
559-553X	—	122,238 mm	63,500 mm	Open	173.000 N	245.000 N	—	—
559S-5520	—	120,251 mm	65,883 mm	Open	210.000 N	320.000 N	—	—
559S-5521	—	130 mm	65,883 mm	Open	210.000 N	320.000 N	—	—
559S-5535	—	122,238 mm	65,883 mm	Open	210.000 N	320.000 N	—	—
560-552	—	123,825 mm	66,675 mm	Open	173.000 N	245.000 N	—	—
560-552A	—	123,825 mm	66,675 mm	Open	173.000 N	245.000 N	—	—
560-553X	—	122,238 mm	66,675 mm	Open	173.000 N	245.000 N	3.000 RPM	—
560S-552	—	123,825 mm	68,263 mm	Open	173.000 N	245.000 N	—	—
560S-552A	—	123,825 mm	68,263 mm	Open	173.000 N	245.000 N	—	—
560S-553X	—	122,238 mm	68,263 mm	Open	173.000 N	245.000 N	—	—
56418-56650	—	165,100 mm	106,363 mm	Open	209.000 N	355.000 N	—	—
56418-56662	—	168,275 mm	106,363 mm	Open	209.000 N	355.000 N	—	—
56425-56650	—	165,100 mm	107,950 mm	Open	209.000 N	355.000 N	2.100 RPM	—
56425-56662	—	168,275 mm	107,950 mm	Open	209.000 N	355.000 N	—	—
56426-56650	—	165,100 mm	107,950 mm	Open	209.000 N	355.000 N	2.100 RPM	—
565-563	—	127 mm	63,500 mm	Open	178.000 N	259.000 N	2.900 RPM	—
566-563	—	127 mm	69,850 mm	Open	178.000 N	259.000 N	2.900 RPM	—
567-563D-ACS205	—	127 mm	73,025 mm	Open	178.000 N	259.000 N	—	—
567A-563	—	127 mm	71,438 mm	Open	178.000 N	259.000 N	—	—
567S-563	—	127 mm	71,438 mm	Open	178.000 N	259.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
567XA-563	—	127 mm	73,025 mm	Open	178.000 N	259.000 N	—	—
568-563	—	127 mm	73,817 mm	Open	178.000 N	259.000 N	2.900 RPM	—
570-563	—	127 mm	68,263 mm	Open	178.000 N	259.000 N	2.900 RPM	—
575-572	—	139,992 mm	76,200 mm	Open	188.000 N	288.000 N	—	—
575-572DFD0CS00	—	140,018 mm	76,200 mm	Open	188.000 N	288.000 N	—	—
575S-572	—	139,992 mm	76,200 mm	Open	188.000 N	288.000 N	—	—
5760-5735	—	135,733 mm	76,200 mm	Open	229.000 N	375.000 N	2.700 RPM	—
576-572	—	139,992 mm	73,025 mm	Open	188.000 N	288.000 N	—	—
577-572	—	139,992 mm	74,612 mm	Open	188.000 N	288.000 N	—	—
578-572	—	139,992 mm	79,985 mm	Open	188.000 N	288.000 N	—	—
5795-5735	—	135,733 mm	77,788 mm	Open	229.000 N	375.000 N	—	—
580-572	—	139,992 mm	82,550 mm	Open	188.000 N	288.000 N	—	—
580-572D-ACB120	—	139,992 mm	82,550 mm	Open	188.000 N	288.000 N	—	—
581-572	—	139,992 mm	80,962 mm	Open	188.000 N	288.000 N	2.600 RPM	—
590A-592	—	152,400 mm	76,200 mm	Open	197.000 N	315.000 N	—	—
590A-592A	—	152,400 mm	76,200 mm	Open	197.000 N	315.000 N	—	—
590A-592XE	—	147,638 mm	76,200 mm	Open	197.000 N	315.000 N	—	—
590A-592XS	—	147,638 mm	76,200 mm	Open	197.000 N	315.000 N	—	—
59162-59412	—	104,775 mm	41,275 mm	Open	155.000 N	201.000 N	—	—
59162-59425	—	107,950 mm	41,275 mm	Open	155.000 N	201.000 N	—	—
59162-59429	—	108,966 mm	41,275 mm	Open	155.000 N	201.000 N	—	—
59175-59412	—	104,775 mm	44,450 mm	Open	155.000 N	201.000 N	—	—
59175-59425	—	107,950 mm	44,450 mm	Open	155.000 N	201.000 N	—	—
59175-59429	—	108,966 mm	44,450 mm	Open	155.000 N	201.000 N	—	—
59187-59412	—	104,775 mm	47,625 mm	Open	155.000 N	201.000 N	—	—
59187-59425	—	107,950 mm	47,625 mm	Open	155.000 N	201.000 N	—	—
59187-59429	—	108,966 mm	47,625 mm	Open	155.000 N	201.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
59200-59412	—	104,775 mm	50,800 mm	Open	155.000 N	201.000 N	—	—
59200-59425	—	107,950 mm	50,800 mm	Open	155.000 N	201.000 N	—	—
59200-59429	—	108,966 mm	50,800 mm	Open	155.000 N	201.000 N	—	—
59201-59412	—	104,775 mm	50,800 mm	Open	155.000 N	201.000 N	—	—
59201-59425	—	107,950 mm	50,800 mm	Open	155.000 N	201.000 N	—	—
59201-59429	—	108,966 mm	50,800 mm	Open	155.000 N	201.000 N	—	—
593-592	—	152,400 mm	88,900 mm	Open	197.000 N	315.000 N	—	—
593-592A	—	152,400 mm	88,900 mm	Open	197.000 N	315.000 N	2.300 RPM	—
593-592XE	—	147,638 mm	88,900 mm	Open	197.000 N	315.000 N	—	—
593-592XS	—	147,638 mm	88,900 mm	Open	197.000 N	315.000 N	—	—
593A-592	—	152,400 mm	88,900 mm	Open	197.000 N	315.000 N	—	—
593A-592A	—	152,400 mm	88,900 mm	Open	197.000 N	315.000 N	2.300 RPM	—
593A-592XE	—	147,638 mm	88,900 mm	Open	197.000 N	315.000 N	—	—
593A-592XS	—	147,638 mm	88,900 mm	Open	197.000 N	315.000 N	—	—
593S-592	—	152,400 mm	89,091 mm	Open	197.000 N	315.000 N	—	—
593S-592A	—	152,400 mm	89,091 mm	Open	197.000 N	315.000 N	—	—
593S-592XE	—	147,638 mm	89,091 mm	Open	197.000 N	315.000 N	—	—
593S-592XS	—	147,638 mm	89,091 mm	Open	197.000 N	315.000 N	—	—
594-592	—	152,400 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594-592A	—	152,400 mm	95,250 mm	Open	197.000 N	315.000 N	2.300 RPM	—
594-592XE	—	147,638 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594-592XS	—	147,638 mm	95,250 mm	Open	197.000 N	315.000 N	2.300 RPM	—
594A-592	—	152,400 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594A-592XE	—	147,638 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594A-592XS	—	147,638 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594R-592	—	152,400 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594R-592A	—	152,400 mm	95,250 mm	Open	197.000 N	315.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
594R-592XE	—	147,638 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
594R-592XS	—	147,638 mm	95,250 mm	Open	197.000 N	315.000 N	—	—
595-592	—	152,400 mm	82,550 mm	Open	197.000 N	315.000 N	—	—
595-592A	—	152,400 mm	82,550 mm	Open	197.000 N	315.000 N	—	—
595-592XE	—	147,638 mm	82,550 mm	Open	197.000 N	315.000 N	—	—
595-592XS	—	147,638 mm	82,550 mm	Open	197.000 N	315.000 N	—	—
595A-592	—	152,400 mm	79,375 mm	Open	197.000 N	315.000 N	—	—
595A-592A	—	152,400 mm	79,375 mm	Open	197.000 N	315.000 N	—	—
595A-592XE	—	147,638 mm	79,375 mm	Open	197.000 N	315.000 N	—	—
595A-592XS	—	147,638 mm	79,375 mm	Open	197.000 N	315.000 N	—	—
596-592	—	152,400 mm	85,725 mm	Open	197.000 N	315.000 N	—	—

LIÊN HỆ

Email: infos@catson.com.vn

Website: www.catson.vn

Điện thoại: +84 28 3820 8888

Fax: +84 28 3826 8888

