

Tapered Roller Set - Metric Series

Tapered Roller Set - Metric Series

415 mã sản phẩm



Nhập vào mã NTN để mở trang chi tiết trên www.catson.vn.

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
10R32005VC12UA	25 mm	47 mm	15 mm	Open	28.500 N	31.500 N	—	—
30202	15 mm	35 mm	11 mm	Open	13.400 N	12.300 N	9.900 RPM	13.000 RPM
30202P5	15 mm	35 mm	11 mm	Open	13.400 N	12.300 N	—	—
30203	17 mm	40 mm	12 mm	Open	20.500 N	20.300 N	9.900 RPM	13.000 RPM
30204	20 mm	47 mm	14 mm	Open	28.200 N	28.700 N	8.800 RPM	12.000 RPM
30204P5	20 mm	47 mm	14 mm	Open	28.700 N	28.200 N	8.800 RPM	12.000 RPM
30205	25 mm	52 mm	15 mm	Open	31.500 N	34.000 N	7.300 RPM	9.800 RPM
30205P5	25 mm	52 mm	15 mm	Open	31.500 N	34.000 N	7.300 RPM	9.800 RPM
30205X	25 mm	52 mm	15 mm	Open	31.500 N	34.000 N	7.300 RPM	9.800 RPM
30206	30 mm	62 mm	16 mm	Open	43.500 N	48.000 N	6.300 RPM	8.400 RPM
30206A	30 mm	62 mm	16 mm	Open	46.000 N	48.500 N	—	—
30206P5	30 mm	62 mm	16 mm	Open	43.500 N	48.000 N	6.300 RPM	8.400 RPM
30207	35 mm	72 mm	17 mm	Open	55.500 N	61.500 N	5.500 RPM	7.400 RPM
30207ST	35 mm	72 mm	17 mm	Open	55.500 N	61.500 N	5.500 RPM	7.400 RPM
30207UP4	35 mm	72 mm	17 mm	Open	55.500 N	61.500 N	5.500 RPM	7.400 RPM
30207X6-80EW	35 mm	72 mm	17 mm	Open	55.500 N	61.500 N	5.500 RPM	7.400 RPM
30208	40 mm	80 mm	18 mm	Open	61.000 N	67.000 N	4.900 RPM	6.600 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
30208P5	40 mm	80 mm	18 mm	Open	61.000 N	67.000 N	4.900 RPM	6.600 RPM
30208STPX2	40 mm	80 mm	18 mm	Open	61.000 N	67.000 N	4.900 RPM	6.600 RPM
30208UP4	40 mm	80 mm	18 mm	Open	61.000 N	67.000 N	4.900 RPM	6.600 RPM
30209	45 mm	85 mm	19 mm	Open	67.500 N	78.500 N	4.400 RPM	5.900 RPM
30209P5	45 mm	85 mm	19 mm	Open	67.500 N	78.500 N	4.400 RPM	5.900 RPM
30209UP4	45 mm	85 mm	19 mm	Open	67.500 N	78.500 N	4.400 RPM	5.900 RPM
30210	50 mm	90 mm	20 mm	Open	77.000 N	93.000 N	4.000 RPM	5.300 RPM
30211	55 mm	100 mm	21 mm	Open	93.000 N	111.000 N	3.600 RPM	4.900 RPM
30211U	55 mm	100 mm	21 mm	Open	93.000 N	111.000 N	3.600 RPM	4.900 RPM
30212	60 mm	110 mm	22 mm	Open	105.000 N	125.000 N	3.400 RPM	4.500 RPM
30213	65 mm	120 mm	23 mm	Open	123.000 N	148.000 N	3.100 RPM	4.200 RPM
30213E4	65 mm	120 mm	23 mm	Open	123.000 N	148.000 N	3.100 RPM	4.200 RPM
30214	70 mm	125 mm	24 mm	Open	131.000 N	162.000 N	2.900 RPM	3.900 RPM
30215	75 mm	130 mm	25 mm	Open	139.000 N	175.000 N	2.700 RPM	3.600 RPM
30215DFC3	75 mm	130 mm	25 mm	Open	—	—	—	—
30216	80 mm	140 mm	26 mm	Open	160.000 N	200.000 N	2.500 RPM	3.400 RPM
30216P5	80 mm	140 mm	26 mm	Open	177.000 N	200.000 N	2.500 RPM	3.400 RPM
30217	85 mm	150 mm	28 mm	Open	183.000 N	232.000 N	2.400 RPM	3.200 RPM
30218	90 mm	160 mm	30 mm	Open	208.000 N	267.000 N	2.200 RPM	3.000 RPM
30218P5	90 mm	160 mm	30 mm	Open	208.000 N	267.000 N	2.200 RPM	3.000 RPM
30219	95 mm	170 mm	32 mm	Open	226.000 N	290.000 N	2.100 RPM	2.800 RPM
30220	100 mm	180 mm	34 mm	Open	258.000 N	335.000 N	2.000 RPM	2.700 RPM
30220DFC3	100 mm	180 mm	—	Open	440.000 N	675.000 N	—	—
30221	105 mm	190 mm	36 mm	Open	287.000 N	380.000 N	1.900 RPM	2.500 RPM
30222	110 mm	200 mm	38 mm	Open	325.000 N	435.000 N	1.800 RPM	2.400 RPM
30224	120 mm	215 mm	40 mm	Open	345.000 N	470.000 N	1.700 RPM	2.200 RPM
30226	130 mm	230 mm	40 mm	Open	375.000 N	505.000 N	1.500 RPM	2.000 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
30226UDB-57-5	130 mm	230 mm	—	Open	640.000 N	1.010.000 N	—	—
30228	140 mm	250 mm	42 mm	Open	420.000 N	570.000 N	1.400 RPM	1.900 RPM
30228U	140 mm	250 mm	42 mm	Open	420.000 N	570.000 N	1.400 RPM	1.900 RPM
30230	150 mm	270 mm	45 mm	Open	450.000 N	605.000 N	1.300 RPM	1.700 RPM
30234	170 mm	310 mm	52 mm	Open	610.000 N	845.000 N	1.100 RPM	1.500 RPM
30236	180 mm	320 mm	52 mm	Open	630.000 N	890.000 N	1.100 RPM	1.400 RPM
30238	190 mm	340 mm	55 mm	Open	715.000 N	1.000.000 N	1.000 RPM	1.300 RPM
30240	200 mm	360 mm	58 mm	Open	785.000 N	1.110.000 N	950 RPM	1.300 RPM
30260	300 mm	540 mm	85 mm	Open	1.420.000 N	2.220.000 N	—	—
30302	15 mm	42 mm	13 mm	Open	23.200 N	20.800 N	9.900 RPM	13.000 RPM
30303	17 mm	47 mm	14 mm	Open	28.900 N	26.300 N	9.000 RPM	12.000 RPM
30304	20 mm	52 mm	16 mm	Open	35.500 N	34.000 N	—	—
30304A	20 mm	52 mm	16 mm	Open	35.500 N	34.000 N	8.000 RPM	11.000 RPM
30304CA	20 mm	52 mm	16 mm	Open	31.000 N	31.000 N	7.600 RPM	10.000 RPM
30305	25 mm	62 mm	17 mm	Open	48.500 N	47.500 N	6.700 RPM	8.900 RPM
30305A	25 mm	62 mm	17 mm	Open	47.500 N	44.500 N	—	—
30305C	25 mm	62 mm	17 mm	Open	41.500 N	41.500 N	6.400 RPM	8.500 RPM
30305D	25 mm	62 mm	17 mm	Open	40.500 N	43.500 N	5.900 RPM	7.800 RPM
30306	30 mm	72 mm	19 mm	Open	60.000 N	61.000 N	5.700 RPM	7.600 RPM
30306CA	30 mm	72 mm	19 mm	Open	58.500 N	58.500 N	5.500 RPM	7.300 RPM
30306D	30 mm	72 mm	19 mm	Open	48.500 N	51.500 N	5.000 RPM	6.700 RPM
30307	35 mm	80 mm	21 mm	Open	75.000 N	77.000 N	5.000 RPM	6.600 RPM
30307C	35 mm	80 mm	21 mm	Open	66.500 N	68.500 N	4.800 RPM	6.400 RPM
30307D	35 mm	80 mm	21 mm	Open	63.500 N	70.000 N	4.400 RPM	5.800 RPM
30308	40 mm	90 mm	23 mm	Open	91.500 N	102.000 N	4.400 RPM	5.900 RPM
30308A	40 mm	90 mm	23 mm	Open	90.000 N	96.000 N	—	—
30308C	40 mm	90 mm	23 mm	Open	83.000 N	87.000 N	4.200 RPM	5.600 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
30308D	40 mm	90 mm	23 mm	Open	77.000 N	85.500 N	—	—
30309	45 mm	100 mm	25 mm	Open	111.000 N	126.000 N	4.000 RPM	5.300 RPM
30309D	45 mm	100 mm	25 mm	Open	96.000 N	109.000 N	3.500 RPM	4.600 RPM
30309DDF	45 mm	100 mm	50 mm	Open	165.000 N	218.000 N	—	—
30309DDFC3	45 mm	100 mm	50 mm	Open	165.000 N	218.000 N	—	—
30309DDFDX1	45 mm	100 mm	50 mm	Open	165.000 N	218.000 N	—	—
30310	50 mm	110 mm	27 mm	Open	133.000 N	152.000 N	3.600 RPM	4.800 RPM
30310D	50 mm	110 mm	27 mm	Open	113.000 N	130.000 N	3.200 RPM	4.200 RPM
30311	55 mm	120 mm	29 mm	Open	155.000 N	179.000 N	3.300 RPM	4.400 RPM
30311D	55 mm	120 mm	29 mm	Open	132.000 N	154.000 N	2.900 RPM	3.800 RPM
30311DDF	55 mm	120 mm	42 mm	Open	155.000 N	179.000 N	—	—
30311DDT-6-5D-01	55 mm	120 mm	—	Open	139.000 N	154.000 N	—	—
30312	60 mm	130 mm	31 mm	Open	180.000 N	210.000 N	3.000 RPM	4.000 RPM
30312D	60 mm	130 mm	31 mm	Open	150.000 N	176.000 N	2.700 RPM	3.600 RPM
30312DSTPX1	60 mm	130 mm	31 mm	Open	150.000 N	176.000 N	—	—
30313	65 mm	140 mm	33 mm	Open	203.000 N	238.000 N	2.800 RPM	3.700 RPM
30313D	65 mm	140 mm	33 mm	Open	173.000 N	204.000 N	2.500 RPM	3.300 RPM
30313DST	65 mm	140 mm	33 mm	Open	173.000 N	204.000 N	—	—
30313DSTDT-7-01	65 mm	140 mm	73,500 mm	Open	325.000 N	410.000 N	—	—
30314	70 mm	150 mm	35 mm	Open	230.000 N	272.000 N	2.600 RPM	3.500 RPM
30314D	70 mm	150 mm	35 mm	Open	193.000 N	229.000 N	2.300 RPM	3.000 RPM
30314DST	70 mm	150 mm	35 mm	Open	193.000 N	229.000 N	—	—
30314DSTDT-7DX	70 mm	150 mm	—	Open	330.000 N	460.000 N	—	—
30315	75 mm	160 mm	37 mm	Open	255.000 N	305.000 N	2.400 RPM	3.200 RPM
30315D	75 mm	160 mm	37 mm	Open	215.000 N	256.000 N	2.100 RPM	2.800 RPM
30315DU	75 mm	160 mm	37 mm	Open	215.000 N	256.000 N	2.100 RPM	2.800 RPM
30315DUDFCS120	75 mm	160 mm	37 mm	Open	—	—	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
30316	80 mm	170 mm	39 mm	Open	291.000 N	350.000 N	2.300 RPM	3.000 RPM
30316D	80 mm	170 mm	39 mm	Open	236.000 N	283.000 N	2.000 RPM	2.700 RPM
30316DST	80 mm	170 mm	39 mm	Open	236.000 N	283.000 N	—	—
30317	85 mm	180 mm	41 mm	Open	305.000 N	365.000 N	2.100 RPM	2.900 RPM
30317D	85 mm	180 mm	41 mm	Open	247.000 N	293.000 N	—	—
30318	90 mm	190 mm	43 mm	Open	335.000 N	405.000 N	2.000 RPM	2.700 RPM
30318D	90 mm	190 mm	43 mm	Open	270.000 N	320.000 N	1.800 RPM	2.400 RPM
30319	95 mm	200 mm	45 mm	Open	365.000 N	445.000 N	1.900 RPM	2.500 RPM
30319D	95 mm	200 mm	45 mm	Open	296.000 N	355.000 N	1.700 RPM	2.200 RPM
30320	100 mm	215 mm	47 mm	Open	345.000 N	400.000 N	1.800 RPM	2.400 RPM
30320P5	100 mm	215 mm	47 mm	Open	345.000 N	400.000 N	1.800 RPM	2.400 RPM
30321	105 mm	225 mm	49 mm	Open	435.000 N	530.000 N	1.700 RPM	2.300 RPM
30322	110 mm	240 mm	50 mm	Open	325.000 N	435.000 N	1.600 RPM	2.200 RPM
30324	120 mm	260 mm	55 mm	Open	465.000 N	550.000 N	1.500 RPM	2.000 RPM
30324P5	120 mm	260 mm	55 mm	Open	560.000 N	695.000 N	1.500 RPM	2.000 RPM
30326	130 mm	280 mm	58 mm	Open	650.000 N	830.000 N	1.400 RPM	1.800 RPM
30328	140 mm	300 mm	62 mm	Open	735.000 N	950.000 N	1.300 RPM	1.700 RPM
30330	150 mm	320 mm	65 mm	Open	825.000 N	1.070.000 N	1.200 RPM	1.600 RPM
30332	160 mm	340 mm	68 mm	Open	755.000 N	975.000 N	1.100 RPM	1.500 RPM
30334	170 mm	360 mm	72 mm	Open	845.000 N	1.100.000 N	1.000 RPM	1.400 RPM
30338JXM1DFCS525P6	190 mm	400 mm	—	Open	—	—	—	—
31310A	50 mm	110 mm	27 mm	Open	116.000 N	130.000 N	—	—
31311A	55 mm	120 mm	29 mm	Open	128.000 N	142.000 N	—	—
31313A	65 mm	140 mm	33 mm	Open	173.000 N	199.000 N	—	—
31314A	70 mm	150 mm	35 mm	Open	195.000 N	225.000 N	—	—
31320X	100 mm	215 mm	51 mm	Open	355.000 N	435.000 N	1.800 RPM	2.400 RPM
31321X	105 mm	225 mm	53 mm	Open	380.000 N	470.000 N	1.700 RPM	2.300 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
31322X	110 mm	240 mm	57 mm	Open	430.000 N	535.000 N	1.600 RPM	2.200 RPM
31324X	120 mm	260 mm	62 mm	Open	515.000 N	655.000 N	1.500 RPM	2.000 RPM
31324XUS30-W1ND	120 mm	260 mm	62 mm	Open	515.000 N	655.000 N	1.500 RPM	2.000 RPM
31326X	130 mm	280 mm	66 mm	Open	600.000 N	780.000 N	1.400 RPM	1.800 RPM
31328X	140 mm	300 mm	70 mm	Open	685.000 N	905.000 N	1.300 RPM	1.700 RPM
31328XUS30-W1ND	140 mm	300 mm	70 mm	Open	685.000 N	905.000 N	1.300 RPM	1.700 RPM
31330X	150 mm	320 mm	75 mm	Open	775.000 N	1.030.000 N	1.200 RPM	1.600 RPM
31330XU	150 mm	320 mm	75 mm	Open	775.000 N	1.030.000 N	1.200 RPM	1.600 RPM
32004X	20 mm	42 mm	15 mm	Open	24.900 N	27.900 N	9.500 RPM	13.000 RPM
32004XP6	20 mm	42 mm	15 mm	Open	24.900 N	27.900 N	9.500 RPM	13.000 RPM
32005VC12	25 mm	47 mm	15 mm	Open	28.500 N	31.500 N	—	—
32005X	25 mm	47 mm	15 mm	Open	27.800 N	33.500 N	7.900 RPM	11.000 RPM
32005XP5	25 mm	47 mm	15 mm	Open	27.800 N	33.500 N	7.900 RPM	11.000 RPM
32005XUP4	25 mm	47 mm	15 mm	Open	27.800 N	33.500 N	7.900 RPM	11.000 RPM
32006X	30 mm	55 mm	17 mm	Open	37.500 N	46.000 N	6.900 RPM	9.200 RPM
32006XP5	30 mm	55 mm	17 mm	Open	37.500 N	46.000 N	6.900 RPM	9.200 RPM
32007	35 mm	62 mm	18 mm	Open	41.500 N	52.500 N	6.100 RPM	8.100 RPM
32007X	35 mm	62 mm	18 mm	Open	41.500 N	52.500 N	6.100 RPM	8.100 RPM
32007XP5	35 mm	62 mm	18 mm	Open	41.500 N	52.500 N	6.100 RPM	8.100 RPM
32007XP6	35 mm	62 mm	18 mm	Open	41.500 N	52.500 N	6.100 RPM	8.100 RPM
32008X	40 mm	68 mm	19 mm	Open	50.000 N	65.500 N	5.300 RPM	7.100 RPM
32008XDB-10-G045P5	40 mm	68 mm	—	Open	—	—	—	—
32008XP5	40 mm	68 mm	19 mm	Open	50.000 N	65.500 N	5.300 RPM	7.100 RPM
32008XST	40 mm	68 mm	19 mm	Open	50.000 N	65.500 N	5.300 RPM	7.100 RPM
32008XU	40 mm	68 mm	19 mm	Open	50.000 N	65.500 N	5.300 RPM	7.100 RPM
32008XUP4	40 mm	68 mm	19 mm	Open	50.000 N	65.500 N	5.300 RPM	7.100 RPM
32009X	45 mm	75 mm	20 mm	Open	57.500 N	76.500 N	4.800 RPM	6.400 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32009XP5	45 mm	75 mm	20 mm	Open	57.500 N	76.500 N	4.800 RPM	6.400 RPM
32009XUP4	45 mm	75 mm	20 mm	Open	57.500 N	76.500 N	4.800 RPM	6.400 RPM
32010A	50 mm	80 mm	20 mm	Open	69.000 N	95.000 N	—	—
32010X	50 mm	80 mm	20 mm	Open	62.500 N	88.000 N	4.400 RPM	5.800 RPM
32010XP5	50 mm	80 mm	20 mm	Open	62.500 N	88.000 N	4.400 RPM	5.800 RPM
32010XUP4	50 mm	80 mm	20 mm	Open	62.500 N	88.000 N	4.400 RPM	5.800 RPM
32011A	55 mm	90 mm	23 mm	Open	82.000 N	117.000 N	—	—
32011X	55 mm	90 mm	23 mm	Open	80.500 N	118.000 N	4.000 RPM	5.400 RPM
32011XP4	55 mm	90 mm	23 mm	Open	80.500 N	118.000 N	4.000 RPM	5.400 RPM
32011XP5	55 mm	90 mm	23 mm	Open	80.500 N	118.000 N	4.000 RPM	5.400 RPM
32011XSTPX4	55 mm	90 mm	23 mm	Open	80.500 N	118.000 N	4.000 RPM	5.400 RPM
32012X	60 mm	95 mm	23 mm	Open	82.000 N	123.000 N	3.700 RPM	4.900 RPM
32012XUP5	60 mm	95 mm	23 mm	Open	82.000 N	123.000 N	3.700 RPM	4.900 RPM
32013X	65 mm	100 mm	23 mm	Open	83.000 N	128.000 N	3.400 RPM	4.600 RPM
32013XE4	65 mm	100 mm	23 mm	Open	83.000 N	128.000 N	3.400 RPM	4.600 RPM
32013XP5	65 mm	100 mm	23 mm	Open	83.000 N	128.000 N	3.400 RPM	4.600 RPM
32013XPX1	65 mm	100 mm	23 mm	Open	83.000 N	128.000 N	3.400 RPM	4.600 RPM
32014X	70 mm	110 mm	25 mm	Open	105.000 N	160.000 N	3.200 RPM	4.200 RPM
32014XUP5	70 mm	110 mm	25 mm	Open	105.000 N	160.000 N	3.200 RPM	4.200 RPM
32015X	75 mm	115 mm	25 mm	Open	106.000 N	167.000 N	3.000 RPM	4.000 RPM
32015XUP5	75 mm	115 mm	25 mm	Open	106.000 N	167.000 N	3.000 RPM	4.000 RPM
32016X	80 mm	125 mm	29 mm	Open	139.000 N	216.000 N	2.800 RPM	3.700 RPM
32016XUDFCB69	80 mm	125 mm	58 mm	Open	239.000 N	430.000 N	—	—
32016XUP5	80 mm	125 mm	29 mm	Open	139.000 N	216.000 N	2.800 RPM	3.700 RPM
32017X	85 mm	130 mm	29 mm	Open	142.000 N	224.000 N	2.600 RPM	3.500 RPM
32017XP5	85 mm	130 mm	29 mm	Open	142.000 N	224.000 N	2.600 RPM	3.500 RPM
32018X	90 mm	140 mm	32 mm	Open	168.000 N	270.000 N	2.500 RPM	3.300 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32018XUP5	90 mm	140 mm	32 mm	Open	168.000 N	270.000 N	2.500 RPM	3.300 RPM
32019X	95 mm	145 mm	32 mm	Open	171.000 N	280.000 N	2.300 RPM	3.100 RPM
32019XP5	95 mm	145 mm	32 mm	Open	171.000 N	280.000 N	2.300 RPM	3.100 RPM
32020X	100 mm	150 mm	32 mm	Open	170.000 N	281.000 N	2.200 RPM	3.000 RPM
32020XP5	100 mm	150 mm	32 mm	Open	170.000 N	281.000 N	2.200 RPM	3.000 RPM
32021X	105 mm	160 mm	35 mm	Open	201.000 N	335.000 N	2.100 RPM	2.800 RPM
32022X	110 mm	170 mm	38 mm	Open	236.000 N	390.000 N	2.000 RPM	2.700 RPM
320-22XV1	22 mm	44 mm	15 mm	Open	27.000 N	31.500 N	8.900 RPM	12.000 RPM
320-22XX2	22 mm	44 mm	15 mm	Open	27.000 N	31.500 N	8.900 RPM	12.000 RPM
32024X	120 mm	180 mm	38 mm	Open	245.000 N	420.000 N	1.800 RPM	2.500 RPM
32026X	130 mm	200 mm	45 mm	Open	320.000 N	545.000 N	1.700 RPM	2.200 RPM
32026XDB-20C3	130 mm	200 mm	110 mm	Open	543.000 N	1.085.000 N	—	—
32026XP5	130 mm	200 mm	45 mm	Open	320.000 N	545.000 N	1.700 RPM	2.200 RPM
32026XUP6	130 mm	200 mm	45 mm	Open	320.000 N	545.000 N	1.700 RPM	2.200 RPM
32028X	140 mm	210 mm	45 mm	Open	330.000 N	580.000 N	1.600 RPM	2.100 RPM
32028XP5	140 mm	210 mm	45 mm	Open	330.000 N	580.000 N	1.600 RPM	2.100 RPM
320-28XX1	28 mm	52 mm	16 mm	Open	33.000 N	40.500 N	7.300 RPM	9.700 RPM
32030X	150 mm	225 mm	48 mm	Open	370.000 N	655.000 N	1.400 RPM	1.900 RPM
32030XDB-14CS225	150 mm	225 mm	—	Open	635.000 N	1.310.000 N	—	—
32030XDB-14CS300	150 mm	225 mm	—	Open	635.000 N	1.310.000 N	—	—
32032X	160 mm	240 mm	51 mm	Open	435.000 N	790.000 N	1.400 RPM	1.800 RPM
32032XUP5	160 mm	240 mm	51 mm	Open	435.000 N	790.000 N	1.400 RPM	1.800 RPM
320-32XX1	32 mm	58 mm	17 mm	Open	37.000 N	46.500 N	6.600 RPM	8.700 RPM
32034X	170 mm	260 mm	57 mm	Open	500.000 N	895.000 N	1.300 RPM	1.700 RPM
32036XE1	180 mm	280 mm	64 mm	Open	645.000 N	1.170.000 N	1.200 RPM	1.600 RPM
32036XE1PX4	180 mm	280 mm	64 mm	Open	645.000 N	1.170.000 N	1.200 RPM	1.600 RPM
32038X	190 mm	290 mm	64 mm	Open	655.000 N	1.210.000 N	1.100 RPM	1.500 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32038XE1	190 mm	290 mm	64 mm	Open	655.000 N	1.210.000 N	1.100 RPM	1.500 RPM
32040XE1	200 mm	310 mm	70 mm	Open	800.000 N	1.470.000 N	1.100 RPM	1.400 RPM
32044X	220 mm	340 mm	76 mm	Open	920.000 N	1.690.000 N	960 RPM	1.300 RPM
32044XPX4	220 mm	340 mm	76 mm	Open	920.000 N	1.690.000 N	960 RPM	1.300 RPM
32044XU	220 mm	340 mm	76 mm	Open	920.000 N	1.690.000 N	960 RPM	1.300 RPM
32048X	240 mm	360 mm	76 mm	Open	930.000 N	1.760.000 N	870 RPM	1.200 RPM
32052X	260 mm	400 mm	87 mm	Open	1.200.000 N	2.270.000 N	800 RPM	1.100 RPM
32056X	280 mm	420 mm	87 mm	Open	1.220.000 N	2.350.000 N	740 RPM	980 RPM
32060X	300 mm	460 mm	100 mm	Open	1.490.000 N	2.830.000 N	680 RPM	910 RPM
32064X	320 mm	480 mm	100 mm	Open	1.520.000 N	2.940.000 N	630 RPM	840 RPM
32203	17 mm	40 mm	16 mm	Open	27.300 N	28.300 N	9.900 RPM	1.300 RPM
32203A	17 mm	40 mm	16 mm	Open	31.000 N	31.000 N	—	—
32203R	17 mm	40 mm	16 mm	Open	26.200 N	28.200 N	9.900 RPM	13.000 RPM
32204	20 mm	47 mm	18 mm	Open	36.500 N	39.500 N	8.800 RPM	12.000 RPM
32204X1	20 mm	47 mm	18 mm	Open	36.500 N	39.500 N	8.800 RPM	12.000 RPM
32205	25 mm	52 mm	18 mm	Open	42.000 N	47.000 N	7.300 RPM	9.800 RPM
32205C	25 mm	52 mm	18 mm	Open	38.000 N	46.500 N	7.100 RPM	9.400 RPM
32205CR	25 mm	52 mm	18 mm	Open	34.500 N	42.000 N	7.100 RPM	9.400 RPM
32205R	25 mm	52 mm	18 mm	Open	38.000 N	43.000 N	7.300 RPM	9.800 RPM
32206	30 mm	62 mm	20 mm	Open	54.500 N	64.000 N	6.300 RPM	8.400 RPM
32206C	30 mm	62 mm	20 mm	Open	50.000 N	60.000 N	6.100 RPM	8.100 RPM
32207	35 mm	72 mm	23 mm	Open	72.500 N	87.000 N	5.500 RPM	7.400 RPM
32207C	35 mm	72 mm	23 mm	Open	68.000 N	85.500 N	5.300 RPM	7.100 RPM
32207CR	35 mm	72 mm	23 mm	Open	62.000 N	78.500 N	5.300 RPM	7.100 RPM
32208	40 mm	80 mm	23 mm	Open	79.500 N	93.500 N	4.900 RPM	6.600 RPM
32209	45 mm	85 mm	23 mm	Open	82.000 N	100.000 N	4.400 RPM	5.900 RPM
32210	50 mm	90 mm	23 mm	Open	87.500 N	109.000 N	4.000 RPM	5.300 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32211	55 mm	100 mm	25 mm	Open	108.000 N	134.000 N	3.600 RPM	4.900 RPM
32212	60 mm	110 mm	28 mm	Open	130.000 N	164.000 N	3.400 RPM	4.500 RPM
32212UDFCS00	60 mm	110 mm	28 mm	Open	—	—	—	—
32213	65 mm	120 mm	31 mm	Open	159.000 N	206.000 N	3.100 RPM	4.200 RPM
32213P5	65 mm	120 mm	31 mm	Open	159.000 N	206.000 N	3.100 RPM	4.200 RPM
32214	70 mm	125 mm	31 mm	Open	166.000 N	220.000 N	2.900 RPM	3.900 RPM
32214DB-7-5D1CS178	70 mm	125 mm	74 mm	Open	285.000 N	440.000 N	—	—
32214P5	70 mm	125 mm	31 mm	Open	166.000 N	220.000 N	2.900 RPM	3.900 RPM
32215	75 mm	130 mm	31 mm	Open	168.000 N	224.000 N	2.700 RPM	3.600 RPM
32215P5	75 mm	130 mm	31 mm	Open	168.000 N	224.000 N	2.700 RPM	3.600 RPM
32216	80 mm	140 mm	33 mm	Open	199.000 N	265.000 N	2.500 RPM	3.400 RPM
32216P5	80 mm	140 mm	33 mm	Open	199.000 N	265.000 N	2.500 RPM	3.400 RPM
32217	85 mm	150 mm	36 mm	Open	224.000 N	300.000 N	2.400 RPM	3.200 RPM
32217P5	85 mm	150 mm	36 mm	Open	224.000 N	300.000 N	2.400 RPM	3.200 RPM
32218	90 mm	160 mm	40 mm	Open	262.000 N	360.000 N	2.200 RPM	3.000 RPM
32218P5	90 mm	160 mm	40 mm	Open	262.000 N	360.000 N	2.200 RPM	3.000 RPM
32219	95 mm	170 mm	43 mm	Open	299.000 N	415.000 N	2.100 RPM	2.800 RPM
32220	100 mm	180 mm	46 mm	Open	330.000 N	465.000 N	2.000 RPM	2.700 RPM
32220DB-12	100 mm	180 mm	46 mm	Open	58.000 N	94.500 N	—	—
32220G1P4	100 mm	180 mm	46 mm	Open	330.000 N	465.000 N	2.000 RPM	2.700 RPM
32221	105 mm	190 mm	50 mm	Open	380.000 N	540.000 N	1.900 RPM	2.500 RPM
32222	110 mm	200 mm	53 mm	Open	420.000 N	605.000 N	1.800 RPM	2.400 RPM
32224	120 mm	215 mm	58 mm	Open	460.000 N	680.000 N	1.700 RPM	2.200 RPM
32224UP5	120 mm	215 mm	58 mm	Open	460.000 N	680.000 N	1.700 RPM	2.200 RPM
32226	130 mm	230 mm	64 mm	Open	530.000 N	815.000 N	1.500 RPM	2.000 RPM
32228	140 mm	250 mm	68 mm	Open	610.000 N	920.000 N	1.400 RPM	1.900 RPM
32230	150 mm	270 mm	73 mm	Open	700.000 N	1.070.000 N	1.300 RPM	1.700 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32230DFCS750	150 mm	270 mm	146 mm	Open	1.200.000 N	2.140.000 N	—	—
32230UP5	150 mm	270 mm	73 mm	Open	700.000 N	1.070.000 N	1.300 RPM	1.700 RPM
32232	160 mm	290 mm	60 mm	Open	890.000 N	1.420.000 N	1.200 RPM	1.600 RPM
32234	170 mm	310 mm	86 mm	Open	1.000.000 N	1.600.000 N	1.100 RPM	1.500 RPM
32236	180 mm	320 mm	86 mm	Open	1.030.000 N	1.690.000 N	1.100 RPM	1.400 RPM
32238	190 mm	340 mm	92 mm	Open	1.150.000 N	1.850.000 N	1.000 RPM	1.300 RPM
32240	200 mm	360 mm	98 mm	Open	1.320.000 N	2.130.000 N	950 RPM	1.300 RPM
32304	20 mm	52 mm	21 mm	Open	46.500 N	48.500 N	8.000 RPM	11.000 RPM
32305	25 mm	62 mm	24 mm	Open	61.500 N	64.500 N	6.700 RPM	8.900 RPM
32306	30 mm	72 mm	27 mm	Open	81.000 N	90.000 N	5.700 RPM	7.600 RPM
32306C	30 mm	72 mm	27 mm	Open	79.000 N	94.000 N	5.700 RPM	7.600 RPM
32306CR	30 mm	72 mm	27 mm	Open	70.000 N	88.500 N	5.500 RPM	7.300 RPM
32307	35 mm	80 mm	31 mm	Open	101.000 N	115.000 N	5.000 RPM	6.600 RPM
32307C	35 mm	80 mm	31 mm	Open	93.000 N	117.000 N	4.800 RPM	6.400 RPM
32308	40 mm	90 mm	33 mm	Open	122.000 N	150.000 N	4.400 RPM	5.900 RPM
32308C	40 mm	90 mm	33 mm	Open	110.000 N	140.000 N	4.200 RPM	5.600 RPM
32309	45 mm	100 mm	36 mm	Open	154.000 N	191.000 N	4.000 RPM	5.300 RPM
32310	50 mm	110 mm	40 mm	Open	184.000 N	232.000 N	3.600 RPM	4.800 RPM
32311	55 mm	120 mm	43 mm	Open	215.000 N	275.000 N	3.300 RPM	4.400 RPM
32312	60 mm	130 mm	46 mm	Open	244.000 N	315.000 N	3.000 RPM	4.000 RPM
32312C	60 mm	130 mm	46,050 mm	Open	—	—	—	—
32313	65 mm	140 mm	48 mm	Open	273.000 N	350.000 N	2.800 RPM	3.700 RPM
323138	190 mm	120 mm	104 mm	Open	—	—	—	—
32314	70 mm	150 mm	51 mm	Open	310.000 N	405.000 N	2.600 RPM	3.500 RPM
32315	75 mm	160 mm	55 mm	Open	355.000 N	470.000 N	2.400 RPM	3.200 RPM
32316	80 mm	170 mm	58 mm	Open	395.000 N	525.000 N	2.300 RPM	3.000 RPM
32316C	80 mm	170 mm	58 mm	Open	350.000 N	505.000 N	—	—

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32317	85 mm	180 mm	60 mm	Open	405.000 N	525.000 N	2.100 RPM	2.900 RPM
32318	90 mm	190 mm	64 mm	Open	450.000 N	595.000 N	2.000 RPM	2.700 RPM
32319	95 mm	200 mm	67 mm	Open	505.000 N	670.000 N	1.900 RPM	2.500 RPM
32320	100 mm	215 mm	73 mm	Open	570.000 N	770.000 N	1.800 RPM	2.400 RPM
32321	105 mm	225 mm	77 mm	Open	610.000 N	825.000 N	1.700 RPM	2.300 RPM
32324	120 mm	260 mm	86 mm	Open	815.000 N	1.130.000 N	1.500 RPM	2.000 RPM
32326DB-7-5	130 mm	280 mm	—	Open	1.530.000 N	2.470.000 N	—	—
32330DB-8C3	150 mm	320 mm	236 mm	Open	1.990.000 N	3.500.000 N	—	—
323-32C	32 mm	75 mm	28 mm	Open	84.000 N	102.000 N	5.200 RPM	6.900 RPM
32340DB-20C3	200 mm	420 mm	312 mm	Open	2.990 N	5.300 N	—	—
32907X	35 mm	55 mm	14 mm	Open	27.400 N	37.500 N	6.800 RPM	9.000 RPM
32908X	40 mm	62 mm	15 mm	Open	32.500 N	48.000 N	5.900 RPM	7.800 RPM
32909X	45 mm	68 mm	15 mm	Open	33.500 N	51.500 N	5.300 RPM	7.000 RPM
32910	50 mm	72 mm	14 mm	Open	31.500 N	50.500 N	4.700 RPM	6.300 RPM
32910X	50 mm	72 mm	15 mm	Open	35.500 N	57.000 N	4.700 RPM	6.300 RPM
32911	55 mm	80 mm	17 mm	Open	44.500 N	73.500 N	4.300 RPM	5.700 RPM
32911X	55 mm	80 mm	17 mm	Open	44.500 N	73.500 N	4.300 RPM	5.700 RPM
32912X	60 mm	85 mm	17 mm	Open	51.000 N	83.000 N	4.000 RPM	5.300 RPM
32912XA	60 mm	85 mm	17 mm	Open	51.000 N	83.000 N	4.000 RPM	5.300 RPM
32913X	65 mm	90 mm	17 mm	Open	48.500 N	85.000 N	3.700 RPM	4.900 RPM
32913XA	65 mm	90 mm	17 mm	Open	45.000 N	80.500 N	3.700 RPM	4.900 RPM
32914X	70 mm	100 mm	20 mm	Open	68.500 N	110.000 N	3.400 RPM	4.600 RPM
32915X	75 mm	105 mm	20 mm	Open	69.500 N	114.000 N	3.200 RPM	4.300 RPM
32916X	80 mm	110 mm	20 mm	Open	72.000 N	121.000 N	3.000 RPM	4.000 RPM
32916XU	80 mm	110 mm	20 mm	Open	72.000 N	121.000 N	3.000 RPM	4.000 RPM
32917X	85 mm	120 mm	23 mm	Open	94.000 N	157.000 N	2.800 RPM	3.800 RPM
32918X	90 mm	125 mm	23 mm	Open	97.500 N	168.000 N	2.700 RPM	3.600 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
32919X	95 mm	130 mm	23 mm	Open	101.000 N	178.000 N	2.500 RPM	3.400 RPM
32920	100 mm	140 mm	24 mm	Open	97.500 N	162.000 N	2.400 RPM	3.200 RPM
32920X	100 mm	140 mm	25 mm	Open	121.000 N	206.000 N	2.400 RPM	3.200 RPM
32921XA	105 mm	145 mm	25 mm	Open	126.000 N	219.000 N	2.300 RPM	3.000 RPM
32922XA	110 mm	150 mm	25 mm	Open	127.000 N	226.000 N	2.200 RPM	2.900 RPM
32924	120 mm	165 mm	27 mm	Open	118.000 N	205.000 N	2.000 RPM	2.600 RPM
32924P5	120 mm	165 mm	29 mm	Open	162.000 N	294.000 N	2.000 RPM	2.600 RPM
32924X	120 mm	165 mm	29 mm	Open	162.000 N	294.000 N	2.000 RPM	2.600 RPM
32926	130 mm	180 mm	30 mm	Open	142.000 N	252.000 N	1.800 RPM	2.400 RPM
32926X	130 mm	180 mm	32 mm	Open	194.000 N	350.000 N	1.800 RPM	2.400 RPM
32928X	140 mm	190 mm	32 mm	Open	200.000 N	375.000 N	1.700 RPM	2.200 RPM
32928XP5	140 mm	190 mm	32 mm	Open	200.000 N	375.000 N	1.700 RPM	2.200 RPM
32930X	150 mm	210 mm	38 mm	Open	268.000 N	490.000 N	1.600 RPM	2.100 RPM
32930XP5	150 mm	210 mm	38 mm	Open	268.000 N	490.000 N	1.600 RPM	2.100 RPM
32932X	160 mm	220 mm	38 mm	Open	276.000 N	520.000 N	1.500 RPM	1.900 RPM
32934X	170 mm	230 mm	38 mm	Open	286.000 N	560.000 N	1.400 RPM	1.800 RPM
32936X	180 mm	250 mm	45 mm	Open	350.000 N	700.000 N	1.300 RPM	1.700 RPM
32938	190 mm	260 mm	45 mm	Open	355.000 N	710.000 N	1.200 RPM	1.600 RPM
32938X	190 mm	260 mm	45 mm	Open	355.000 N	710.000 N	1.200 RPM	1.600 RPM
32940	200 mm	280 mm	51 mm	Open	485.000 N	895.000 N	—	—
32940XE1	200 mm	280 mm	51 mm	Open	485.000 N	895.000 N	1.100 RPM	1.500 RPM
32944	220 mm	300 mm	48 mm	Open	345.000 N	670.000 N	1.000 RPM	1.400 RPM
32944E1	220 mm	300 mm	48 mm	Open	345.000 N	670.000 N	1.000 RPM	1.400 RPM
32944XUE1	220 mm	300 mm	51 mm	Open	480.000 N	950.000 N	1.000 RPM	1.400 RPM
32948	260 mm	360 mm	51 mm	Open	490.000 N	1.000.000 N	940 RPM	1.200 RPM
32948XE1	240 mm	320 mm	51 mm	Open	490.000 N	1.000.000 N	940 RPM	1.200 RPM
32956XE1	280 mm	380 mm	63,500 mm	Open	725.000 N	1.520.000 N	790 RPM	1.100 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mỡ	Tốc độ dầu
32960XE1	300 mm	420 mm	76 mm	Open	1.010.000 N	2.090.000 N	720 RPM	970 RPM
32964E1	320 mm	440 mm	72 mm	Open	865.000 N	1.880.000 N	670 RPM	900 RPM
32964XE1	320 mm	440 mm	76 mm	Open	1.010.000 N	2.150.000 N	670 RPM	900 RPM
32968E1	340 mm	460 mm	72 mm	Open	910.000 N	1.980.000 N	630 RPM	900 RPM
32968XE1	340 mm	460 mm	76 mm	Open	1.040.000 N	2.270.000 N	630 RPM	840 RPM
32972XUE1	360 mm	480 mm	76 mm	Open	1.050.000 N	2.330.000 N	590 RPM	780 RPM
33005	25 mm	47 mm	17 mm	Open	32.500 N	40.500 N	8.000 RPM	11.000 RPM
33006	30 mm	55 mm	20 mm	Open	42.500 N	54.000 N	6.900 RPM	9.200 RPM
33007	35 mm	62 mm	21 mm	Open	50.500 N	66.500 N	6.100 RPM	8.100 RPM
33008	40 mm	68 mm	22 mm	Open	59.500 N	82.500 N	5.300 RPM	7.100 RPM
33009	45 mm	75 mm	24 mm	Open	66.000 N	93.500 N	4.800 RPM	6.400 RPM
33010	50 mm	80 mm	24 mm	Open	69.500 N	103.000 N	4.400 RPM	5.800 RPM
33011	55 mm	90 mm	27 mm	Open	91.500 N	138.000 N	4.000 RPM	5.400 RPM
33011A	55 mm	90 mm	27 mm	Open	97.000 N	145.000 N	—	—
33012	60 mm	95 mm	27 mm	Open	93.500 N	145.000 N	3.700 RPM	4.900 RPM
33012AL	60 mm	95 mm	27 mm	Open	84.000 N	88.000 N	3.700 RPM	—
33013	65 mm	100 mm	27 mm	Open	97.500 N	156.000 N	3.400 RPM	4.600 RPM
33013A	65 mm	100 mm	27 mm	Open	106.000 N	164.000 N	—	—
33013X1	65 mm	100 mm	27 mm	Open	97.500 N	156.000 N	3.400 RPM	4.600 RPM
33014	70 mm	110 mm	31 mm	Open	127.000 N	204.000 N	3.200 RPM	4.200 RPM
33015	75 mm	115 mm	31 mm	Open	111.000 N	186.000 N	3.000 RPM	4.000 RPM
33016	80 mm	125 mm	36 mm	Open	173.000 N	284.000 N	2.800 RPM	3.700 RPM
33017	85 mm	130 mm	36 mm	Open	176.000 N	296.000 N	2.600 RPM	3.500 RPM
33018	90 mm	140 mm	39 mm	Open	215.000 N	360.000 N	2.500 RPM	3.300 RPM
33019	95 mm	145 mm	39 mm	Open	219.000 N	375.000 N	2.300 RPM	3.100 RPM
33020	100 mm	150 mm	39 mm	Open	224.000 N	390.000 N	2.200 RPM	3.000 RPM
33021	105 mm	160 mm	43 mm	Open	245.000 N	420.000 N	2.100 RPM	2.800 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
33022	110 mm	170 mm	47 mm	Open	288.000 N	500.000 N	2.000 RPM	2.700 RPM
33108	40 mm	75 mm	26 mm	Open	79.500 N	103.000 N	5.200 RPM	6.900 RPM
33108X1	40 mm	75 mm	26 mm	Open	79.500 N	103.000 N	5.200 RPM	6.900 RPM
33109	45 mm	80 mm	26 mm	Open	84.500 N	115.000 N	4.700 RPM	6.200 RPM
33110	50 mm	85 mm	26 mm	Open	86.500 N	121.000 N	4.200 RPM	5.600 RPM
33111	55 mm	95 mm	30 mm	Open	111.000 N	155.000 N	3.900 RPM	5.200 RPM
33112	60 mm	100 mm	30 mm	Open	113.000 N	164.000 N	3.600 RPM	4.700 RPM
33113	65 mm	110 mm	34 mm	Open	144.000 N	211.000 N	3.300 RPM	4.400 RPM
33115	75 mm	125 mm	37 mm	Open	44.500 N	—	—	—
33116	80 mm	130 mm	37 mm	Open	—	—	—	—
33205	25 mm	52 mm	22 mm	Open	47.500 N	57.500 N	7.300 RPM	9.800 RPM
33206	30 mm	62 mm	25 mm	Open	65.000 N	77.000 N	6.300 RPM	8.400 RPM
33206STPX2V3	30 mm	62 mm	25 mm	Open	65.000 N	77.000 N	—	—
33207	35 mm	72 mm	28 mm	Open	87.500 N	109.000 N	5.500 RPM	7.400 RPM
33208	40 mm	80 mm	32 mm	Open	103.000 N	132.000 N	4.900 RPM	6.600 RPM
33209	45 mm	85 mm	32 mm	Open	107.000 N	141.000 N	4.400 RPM	5.900 RPM
33210	50 mm	90 mm	32 mm	Open	115.000 N	158.000 N	4.000 RPM	5.300 RPM
33211	55 mm	100 mm	35 mm	Open	138.000 N	188.000 N	3.600 RPM	4.900 RPM
33212	60 mm	110 mm	38 mm	Open	161.000 N	223.000 N	3.400 RPM	4.500 RPM
33213	65 mm	120 mm	41 mm	Open	195.000 N	265.000 N	3.100 RPM	4.200 RPM
33214	70 mm	125 mm	41 mm	Open	201.000 N	282.000 N	2.900 RPM	3.900 RPM
33215	75 mm	130 mm	41 mm	Open	208.000 N	298.000 N	2.700 RPM	3.600 RPM
33216	80 mm	140 mm	46 mm	Open	250.000 N	365.000 N	2.500 RPM	3.400 RPM
33217	85 mm	150 mm	36 mm	Open	284.000 N	420.000 N	2.400 RPM	3.200 RPM
33218	90 mm	160 mm	55 mm	Open	291.000 N	305.000 N	—	—
332-28	28 mm	58 mm	24 mm	Open	58.000 N	69.500 N	6.700 RPM	8.900 RPM
332-28PX1	28 mm	58 mm	24 mm	Open	58.000 N	69.500 N	6.700 RPM	8.900 RPM

Mã NTN	d	D	B	Kiểu	Tải động	Tải tĩnh	Tốc độ mở	Tốc độ đầu
332-32	32 mm	65 mm	26 mm	Open	70.500 N	85.000 N	6.000 RPM	8.000 RPM
33895-33822	53,975 mm	95,250 mm	28,575 mm	Open	107.000 N	139.000 N	—	—
3E-CR1-2066ZZPX1-0G	101,600 mm	260,350 mm	136,525 mm	Double Shielded	760.000 N	1.220.000 N	—	—
4T-JHM516849-JH-03	85 mm	140 mm	38 mm	Open	197.000 N	297.000 N	—	—
4T-JHM807045-JH-01	50 mm	105 mm	36 mm	Open	138.000 N	189.000 N	—	—
A13	35 mm	59,131 mm	16,764 mm	Open	35.500 N	47.500 N	—	—
CR-0566	25 mm	52 mm	18 mm	Open	42.000 N	46.500 N	—	—
CR-0614ST	28 mm	63 mm	22,250 mm	Open	77.500 N	71.500 N	—	—
CR-0627	30 mm	51 mm	15 mm	Open	26.400 N	34.500 N	—	—
CR-0643	30 mm	52 mm	16 mm	Open	26.400 N	34.500 N	—	—
CR-0643L	30 mm	54 mm	16 mm	Open	26.400 N	34.500 N	—	—
CR-0676	28 mm	50,292 mm	16,724 mm	Open	28.000 N	35.500 N	—	—
CR-10A33	50 mm	110 mm	27 mm	Open	107.000 N	121.000 N	—	—
CR-1194PX1	57,150 mm	100 mm	21,946 mm	Open	78.000 N	96.500 N	—	—
CR-1252L	60 mm	96,500 mm	23,700 mm	Open	79.500 N	115.000 N	—	—
CR-6016PX2V6	300 mm	380 mm	38 mm	Open	400.000 N	825.000 N	—	—
EC0-32204C	20 mm	47 mm	18 mm	Open	35.000 N	39.000 N	—	—
EC12245S04	43,600 mm	84,985 mm	18,250 mm	Open	58.000 N	62.000 N	—	—
EC12250	21,500 mm	47 mm	16,500 mm	Open	31.500 N	23.000 N	—	—
EC12589S01	28,500 mm	47 mm	15 mm	Open	28.500 N	31.500 N	—	—

LIÊN HỆ

Email: infos@catson.com.vn

Website: www.catson.vn

Điện thoại: +84 28 3820 8888

Fax: +84 28 3826 8888

