

Ultra Class Bearing Insert w/ Eccentric Locking Collar, Narrow Inner Ring - Spherical O.D.

Eccentric Locking Collar Type Bearings - Spherical O.D.

34 items



Select an NTN item number to open its detail page on www.catson.vn.

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
A-JEL201-008D1	12,700 mm	40 mm	19 mm	Double Sealed	9.600 N	4.580 N	11.000 RPM	—
A-JEL201-008D1M	12,700 mm	40 mm	18,999 mm	Double Sealed	9.600 N	4.600 N	—	—
A-JEL202-010D1	15,875 mm	40 mm	19 mm	Double Sealed	9.600 N	4.600 N	—	—
A-JEL202-010D1M	15,875 mm	40 mm	18,999 mm	Double Sealed	9.600 N	4.600 N	—	—
A-JEL204-012D1	19,050 mm	47 mm	21,500 mm	Double Sealed	12.800 N	6.650 N	—	—
A-JEL204-012D1M	19,050 mm	47 mm	21,501 mm	Double Sealed	12.800 N	6.650 N	—	—
A-JEL205-014D1	22,225 mm	52 mm	21,500 mm	Double Sealed	14.000 N	7.850 N	—	—
A-JEL205-014D1M	22,225 mm	51,999 mm	21,501 mm	Double Sealed	14.000 N	7.850 N	—	—
A-JEL205-015D1	23,813 mm	52 mm	21,500 mm	Double Sealed	14.000 N	7.850 N	—	—
A-JEL205-100D1	25,400 mm	52 mm	21,500 mm	Double Sealed	14.000 N	7.850 N	5.900 RPM	—
A-JEL206-102D1	28,575 mm	61,999 mm	23,800 mm	Double Sealed	19.500 N	11.300 N	—	—
A-JEL206-102D1M	28,575 mm	61,999 mm	23,800 mm	Double Sealed	19.500 N	11.300 N	—	—
A-JEL206-103D1	30,163 mm	61,999 mm	23,800 mm	Double Sealed	19.500 N	11.300 N	—	—
A-JEL206-103D1M	30,163 mm	61,999 mm	23,800 mm	Double Sealed	19.500 N	11.300 N	—	—
A-JEL206-104D1	31,750 mm	61,999 mm	23,800 mm	Double Sealed	19.500 N	11.300 N	—	—
A-JEL206-104D1M	31,750 mm	61,999 mm	23,800 mm	Double Sealed	19.500 N	11.300 N	—	—
A-JEL207-104D1	31,750 mm	71,999 mm	25,400 mm	Double Sealed	25.700 N	15.300 N	—	—

Item	d	D	B	Type	Dynamic	Static	Grease	Oil
A-JEL207-104D1M	31,750 mm	71,999 mm	25,400 mm	Double Sealed	25.700 N	15.300 N	—	—
A-JEL207-106D1	34,925 mm	71,999 mm	25,400 mm	Double Sealed	25.700 N	15.300 N	4.200 RPM	—
A-JEL207-106D1M	34,925 mm	71,999 mm	25,400 mm	Double Sealed	25.700 N	15.300 N	—	—
A-JEL207-107D1	36,513 mm	71,999 mm	25,400 mm	Double Sealed	25.700 N	15.300 N	—	—
A-JEL207-107D1M	36,513 mm	71,999 mm	25,400 mm	Double Sealed	25.700 N	15.300 N	—	—
A-JEL208-108D1M	38,100 mm	80 mm	30,201 mm	Double Sealed	29.100 N	17.800 N	—	—
A-JEL209-110D1	41,275 mm	85,001 mm	30,201 mm	Double Sealed	32.500 N	20.400 N	—	—
A-JEL209-111D1	42,863 mm	85,001 mm	30,201 mm	Double Sealed	32.500 N	20.400 N	—	—
A-JEL209-111D1M	42,863 mm	85,001 mm	30,201 mm	Double Sealed	32.500 N	20.400 N	—	—
A-JEL209-112D1	44,450 mm	85,001 mm	30,201 mm	Double Sealed	32.500 N	20.400 N	—	—
A-JEL209-112D1M	44,450 mm	85,001 mm	30,201 mm	Double Sealed	32.500 N	20.400 N	—	—
A-JEL210-114D1	47,625 mm	90 mm	30,201 mm	Double Sealed	35.000 N	23.200 N	—	—
A-JEL210-115D1	49,213 mm	90 mm	30,201 mm	Double Sealed	35.000 N	23.200 N	—	—
A-JEL210-115D1M	49,213 mm	90 mm	30,201 mm	Double Sealed	35.000 N	23.200 N	—	—
A-JEL210-200D1	50,800 mm	90 mm	30,200 mm	Double Sealed	35.300 N	23.200 N	3.100 RPM	—
A-JEL211-200D1	50,800 mm	100 mm	32,500 mm	Double Sealed	43.500 N	29.200 N	2.900 RPM	—
A-JEL211-203D1M	55,563 mm	100 mm	32,499 mm	Double Sealed	43.500 N	29.200 N	—	—

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

