



ITEM NUMBER

2LA-HSE924U

Single Row High-Speed Angular Contact Ball Bearings - HSE Ultage Type

Single Row High-Speed Angular Contact Ball Bearings - HSE Ultage Type

d
120 mm
Bore

D
162 mm
Outside diameter

B
22 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/2la-hse924u/?lang=en>

Technical Specifications

Type	Angular Contact Ball Bearing
Bore Type	Round
Material	High Carbon Chrome Steel
Cage Type	Machined
Cage Material	Phenolic Resin
Ball Material	Steel
Limiting Speed - Oil	15900 RPM
Limiting Speed - Grease	9900.0 RPM
Configuration	One
Static Load Rating	44000 N
Dynamic Load Rating	46500 N
Enclosure	Open
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	120.000 mm
D	162.000 mm

B	22.000 mm
d1	135.400 mm
d2	133.000 mm
D1	149.600 mm
D2	154.700 mm
r	1.100 mm
r1	0.600 mm
Contact Angle	20 °
a	37.100 mm
da min	127.000 mm
db min	124.500 mm
Da max	158.000 mm
Db max	160.500 mm
ras max	1.000 mm
r1as max	0.600 mm
Double Row Width	44.000 mm
Triple Row Width	66.000 mm
Quadruple Row Width	88.000 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

