



ITEM NUMBER

5S-2LA-HSL915U

Eco-Friendly Angular Contact Ball Bearing - HSL
Ultage Type

Eco-Friendly Angular Contact Ball Bearing - HSL
Ultage Type

d
75 mm
Bore

D
105 mm
Outside diameter

B
16 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/5s-2la-hsl915u/?lang=en>

Technical Specifications

Type	Angular Contact Ball Bearing
Bore Type	Round
Material	High Carbon Chrome Steel
Cage Type	Machined
Cage Material	Phenolic Resin
Ball Material	Steel
Limiting Speed - Oil	31300 RPM
Configuration	One
Static Load Rating	12200 N
Dynamic Load Rating	21200 N
Enclosure	Open
Weight	0.310 kg
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	75.000 mm
D	105.000 mm

B	16.000 mm
d1	85.100 mm
D2	98.200 mm
r	1.000 mm
r1	0.600 mm
Contact Angle	20 °
a	24.500 mm
da min	80.500 mm
Db max	100.500 mm
r1as max	0.600 mm
l min	9.000 mm
Double Row Width	32.000 mm
Triple Row Width	48.000 mm
Quadruple Row Width	64.000 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

