



#### ITEM NUMBER

# AC-6200LLU

AC Bearings - Double Sealed (Contact Rubber Seal)

AC Bearings

**d**  
**10 mm**  
Bore

**D**  
**30 mm**  
Outside diameter

**B**  
**9 mm**  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ac-6200llu/?lang=en>

## Technical Specifications

|                             |                          |
|-----------------------------|--------------------------|
| Type                        | Ball Bearing             |
| Bore Type                   | Round                    |
| Material                    | High Carbon Chrome Steel |
| Cage Type                   | Pressed                  |
| Cage Material               | Steel                    |
| Limiting Speed - Grease     | 18000 RPM                |
| Precision                   | Class 0                  |
| Configuration               | One                      |
| Factor                      | 13.2                     |
| Radial Internal Clearance   | CN                       |
| Static Load Rating          | 2390 N                   |
| Dynamic Load Rating         | 5650 N                   |
| Enclosure                   | Double Sealed            |
| Weight                      | 0.032 kg                 |
| Operating Temperature Range | -40 to 120 °C            |

## Dimensional Specifications

|         |           |
|---------|-----------|
| d       | 10.000 mm |
| D       | 30.000 mm |
| B       | 9.000 mm  |
| r       | 0.600 mm  |
| da min  | 14.000 mm |
| da max  | 16.000 mm |
| Da max  | 26.000 mm |
| ras max | 0.600 mm  |

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

