



#### ITEM NUMBER

# AC-6208T2XLLH C3

AC Bearings - Double Sealed (Contact Rubber Seal)

AC Bearings

**d**  
**40 mm**  
Bore

**D**  
**80 mm**  
Outside diameter

**B**  
**18 mm**  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ac-6208t2xllhc3/?lang=en>

## Technical Specifications

|                             |                          |
|-----------------------------|--------------------------|
| Type                        | Ball Bearing             |
| Bore Type                   | Round                    |
| Material                    | High Carbon Chrome Steel |
| Cage Type                   | Pressed                  |
| Cage Material               | Steel                    |
| Limiting Speed - Grease     | 6700 RPM                 |
| Precision                   | Class 0                  |
| Configuration               | One                      |
| Factor                      | 14.0                     |
| Radial Internal Clearance   | C3                       |
| Static Load Rating          | 17800 N                  |
| Dynamic Load Rating         | 32500 N                  |
| Enclosure                   | Double Sealed            |
| Weight                      | 0.338 kg                 |
| Operating Temperature Range | -40 to 120 °C            |

## Dimensional Specifications

|         |           |
|---------|-----------|
| d       | 40.000 mm |
| D       | 80.000 mm |
| B       | 18.000 mm |
| r       | 1.100 mm  |
| da min  | 46.500 mm |
| da max  | 51.000 mm |
| Da max  | 73.500 mm |
| ras max | 1.000 mm  |

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

