



ITEM NUMBER

AELP207D1

Pillow Block Unit, Cast Housing, Eccentric
 Locking Collar, AELP/AELPL Type

Pillow Block Unit, Cast Housing, Eccentric Locking
 Collar, AELP/AELPL Type

d 35 mm Bore	D — Outside diameter	B — Width
----------------------------------	-----------------------------------	------------------------

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/aelp207d1/?lang=en>

Technical Specifications	
Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Eccentric Locking Collar
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	AEL207D1
Housing Number	P207D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	25700 N
Static Load Rating	15300 N
Rotational Speed [Max]	4200 RPM
Weight	1.680 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	35.000 mm
J	127.0 mm
L	167.0 mm
A	48.0 mm
H	47.6 mm
H1	18.0 mm
H2	93.0 mm
L1	54.0 mm
N	17.0 mm
N1	20.0 mm
B1	38.900 mm
S	9.500 mm

Specifications

Ball Material	Through Hardened
Outside Diameter	72.000 mm
Bore Type	Cylindrical
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	25700 N
Rotational Speed [Max]-Grease	4200 RPM
Outside Ring Width	9.000 mm
Inside Ring Width	9.000 mm
Radial Static Load Rating	15300 N

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

