



ITEM NUMBER

ASPFL206

Two Bolt Rhombus Flanged Unit, Pressed Steel Housing, Set Screw, ASPFL Type

Two Bolt Rhombus Flanged Unit, Pressed Steel Housing, Set Screw, ASPFL Type

d
30 mm
Bore

D
—
Outside diameter

B
29 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/aspfl206/?lang=en>

Technical Specifications

Type	2-Bolt Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	AS206
Housing Number	PFL206
Housing Construction	2 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	19500 N
Static Load Rating	11300 N
Rotational Speed [Max]	4900 RPM
Weight	0.570 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Non-Relubricatable

Dimensional Specifications

d	30.000 mm
H	113.0 mm
L	84.0 mm
J	90.5 mm
A	18.0 mm
A1	5.2 mm
N	11.0 mm
B	29.000 mm
S	8.000 mm
H1	71.0 mm

Specifications

Ball Material	Through Hardened
Bore Type	Cylindrical
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	19500 N
Rotational Speed [Max]-Grease	4850 RPM
Radial Static Load Rating	11300 N

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

