



ITEM NUMBER

ASRPP204-012

Pillow Block Unit, Set Screw, Pressed Steel Housing, ASRPP Type

Pillow Block Unit, Set Screw, Pressed Steel Housing, ASPP/ASRPP Type

d
19,050 mm
Bore

D
—
Outside diameter

B
25 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/asrpp204-012/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	AS204-012
Housing Number	PP205
Housing Material	Pressed Steel
Housing Construction	1 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	12800 N
Static Load Rating	6650 N
Max. Load Recommended - Axial	200 N
Max. Load Recommended - Radial	1150 N
Rotational Speed [Max]	6700 RPM
Weight	0.320 kg

Operating Temperature Range	-40 to 120 °C
-----------------------------	---------------

Lubrication	Non-Relubricatable
-------------	--------------------

Dimensional Specifications

d	19.050 mm
J	86.0 mm
L	108.0 mm
A	32.0 mm
H	28.6 mm
H1	4.0 mm
H2	56.6 mm
N	11.5 mm
B	25.000 mm
S	7.000 mm

Specifications

Ball Material	Through Hardened
Outside Diameter	47.000 mm
Bore Type	Cylindrical
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	12800 N
Rotational Speed [Max]-Grease	6650.0 RPM
Radial Static Load Rating	6650 N

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

