



ITEM NUMBER

ASRPP205

Pillow Block Unit, Set Screw, Pressed Steel Housing, ASRPP Type

Pillow Block Unit, Set Screw, Pressed Steel Housing, ASPP/ASRPP Type

d
25 mm
Bore

D
—
Outside diameter

B
27 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/asrpp205/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	AS205
Housing Number	PP206
Housing Material	Pressed Steel
Housing Construction	1 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	14000 N
Static Load Rating	7850 N
Max. Load Recommended - Axial	200 N
Max. Load Recommended - Radial	1300 N
Rotational Speed [Max]	5900 RPM
Weight	0.300 kg

Operating Temperature Range	-40 to 120 °C
Lubrication	Non-Relubricatable

Dimensional Specifications

d	25.000 mm
J	95.0 mm
L	117.0 mm
A	38.0 mm
H	33.3 mm
H1	4.0 mm
H2	66.3 mm
N	11.5 mm
B	27.000 mm
S	7.500 mm

Specifications

Ball Material	Through Hardened
Outside Diameter	52.000 mm
Bore Type	Cylindrical
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	14000 N
Rotational Speed [Max]-Grease	5900 RPM
Outside Ring Width	37.000 mm
Inside Ring Width	47.000 mm
Radial Static Load Rating	7850 N
Lubrication	Non-Relubricatable

CONTACT Email: infos@catson.com.vn Website: www.catson.vn	
--	---

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888