



ITEM NUMBER

C- SPW2217-215N1

Sealed Spherical Pillow Blocks, Ductile End Cover, Open End, SPW Type

Sealed Spherical Pillow Blocks, Ductile End Cover, Open End, SPAW/SPW Type

d
74,613 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/c-spw2217-215n1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Spherical Roller Bearing
Seal Material	Nitrile Rubber
Locking Device	Adapter
Bearing Number	MX-W22217EALLKW33C3
Housing Number	SP217N1
Adapter Sleeve Number	HA2317XM1
Housing Material	Ductile Iron
Housing Construction	1 Piece
Mounting Type	2-Bolt
Performance	Heavy Duty
End Type	(2) Open
Dynamic Load Rating	324000 N
Static Load Rating	330000 N
Rotational Speed [Max]	1800.0 RPM
Operating Temperature Range	-40 to 200 °C
Lubrication	Relubricatable

Guidelines for Mounting

Axial Displacement - Min.	0.028 in
Axial Displacement - Max.	0.035 in
Recommended Locknut Rotation	150 °
Hydraulic Pressure - Min.	2050 lb/in ²
Hydraulic Pressure - Max.	2700 lb/in ²

Shaft Tolerance

Shaft Tolerance	nominal to -74 µm
-----------------	-------------------

Allowable Loads

Allowable Loads - P60	28500 lb
Allowable Loads - P90	17000 lb
Allowable Loads - P120	12500 lb
Allowable Loads - P150	11500 lb
Allowable Loads - P180	14500 lb

Dimensional Specifications

d	74.613 mm
h	95.0 mm
a	320.0 mm
b	80.0 mm
b1	90.0 mm
c	32.0 mm
l	156.000 mm
m	260.0 mm
w	192.0 mm
u	22.0 mm
v	27.0 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

