



#### ITEM NUMBER

## C-UKT305D1- WHEN-USED- WITH-HE2305

Take-Up Unit, Cast Housing, Adapter, Cast Dust Cover, Open End, UKT Type

Take-Up Unit, Cast Housing, Adapter, Cast Dust Cover, Open End, UKT Type

**d**  
**19,050 mm**  
Bore

**D**  
—  
Outside diameter

**B**  
—  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/c-ukt305d1-when-used-with-he2305/?lang=en>

### Technical Specifications

|                             |                |
|-----------------------------|----------------|
| Type                        | Take-Up Unit   |
| Bearing Type                | Ball Bearing   |
| Seal Type                   | Contact        |
| Seal Material               | Nitrile Rubber |
| Locking Device              | Adapter        |
| Bearing Number              | UK305D1        |
| Housing Material            | Cast Iron      |
| Housing Number              | C-T305D1       |
| Performance                 | Heavy Duty     |
| Dynamic Load Rating         | 21200 N        |
| Static Load Rating          | 10900 N        |
| Weight                      | 2.200 kg       |
| Operating Temperature Range | -40 to 120 °C  |
| Lubrication                 | Relubricatable |

### Dimensional Specifications

|    |           |
|----|-----------|
| d  | 19.050 mm |
| L  | 122.0 mm  |
| H  | 89.0 mm   |
| A5 | 80.000 mm |
| H1 | 80.0 mm   |
| H2 | 62.0 mm   |
| L1 | 76.0 mm   |
| L2 | 14.0 mm   |
| L3 | 65.0 mm   |
| N  | 26.0 mm   |
| N1 | 16.0 mm   |
| N2 | 36.0 mm   |
| A  | 36.0 mm   |
| A1 | 12.0 mm   |
| A2 | 26.0 mm   |
| r  | 46.0 mm   |
| B1 | 35.000 mm |
| F  | 5.000 mm  |

Notes

Sales drawing reflects  
"Bore Size w/o Adapter".  
They do not show the  
"d" dimension, which is the  
bore size with adapter

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

