



ITEM NUMBER

C-UKT306D1- WHEN-USED- WITH-HS2306

Take-Up Unit, Cast Housing, Adapter, Cast Dust
Cover, Open End, UKT Type

Take-Up Unit, Cast Housing, Adapter, Cast Dust
Cover, Open End, UKT Type

d
22,225 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/c-ukt306d1-when-used-with-hs2306/?lang=en>

Technical Specifications

Type	Take-Up Unit
Bearing Type	Ball Bearing
Seal Type	Contact
Seal Material	Nitrile Rubber
Locking Device	Adapter
Bearing Number	UK306D1
Housing Material	Cast Iron
Housing Number	C-T306D1
Performance	Heavy Duty
Dynamic Load Rating	26700 N
Static Load Rating	15000 N
Weight	2.900 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	22.225 mm
L	139.0 mm
H	100.0 mm
A5	85.000 mm
H1	90.0 mm
H2	70.0 mm
L1	85.0 mm
L2	16.0 mm
L3	74.0 mm
N	28.0 mm
N1	18.0 mm
N2	41.0 mm
A	41.0 mm
A1	16.0 mm
A2	28.0 mm
r	52.0 mm
B1	38.000 mm
F	5.900 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

