



ITEM NUMBER

**CM-
SPAW2222-400N
1**

Sealed Spherical Pillow Blocks, Ductile End Cover, Open/Closed End, SPAW Type

Sealed Spherical Pillow Blocks, Ductile End Cover, Open/Closed End, SPAW/SPW Type

d
101,600 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/cm-spaw2222-400n1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Spherical Roller Bearing
Seal Material	Nitrile Rubber
Locking Device	Adapter
Bearing Number	MX-W22222EALLKW33C3
Housing Number	SPA222N1
Adapter Sleeve Number	HE2322XM1
Housing Material	Ductile Iron
Housing Construction	1 Piece
Mounting Type	4-Bolt
Performance	Heavy Duty
End Type	(1) Open & (1) Closed
Dynamic Load Rating	602000 N
Static Load Rating	643000 N
Rotational Speed [Max]	1400 RPM
Operating Temperature Range	-40 to 200 °C

Guidelines for Mounting

Axial Displacement - Min.	0.030 in
Axial Displacement - Max.	0.043 in
Recommended Locknut Rotation	180 °
Hydraulic Pressure - Min.	2650 lb/in ²
Hydraulic Pressure - Max.	3700 lb/in ²

Shaft Tolerance

Shaft Tolerance	nominal to -87 µm
-----------------	-------------------

Allowable Loads

Allowable Loads - P60	47500 lb
Allowable Loads - P90	28500 lb
Allowable Loads - P120	21000 lb
Allowable Loads - P150	18500 lb
Allowable Loads - P180	23500 lb

Dimensional Specifications

d	101.600 mm
h	125.4 mm
a	419.0 mm
b	100.0 mm
b1	121.0 mm
c	45.0 mm
l	184.988 mm
m	344.5 mm
n	69.9 mm
w	262.0 mm
u	22.0 mm
v	42.9 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

