



#### ITEM NUMBER

## CM-UCT213D1

Take-Up Unit, Cast Housing, Set Screw, Cast Dust Cover, Closed End, UCT Type

Take-Up Unit, Cast Housing, Set Screw, Cast Dust Cover, Closed End, UCT Type

**d**  
**65 mm**  
Bore

**D**  
—  
Outside diameter

**B**  
**65,100 mm**  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/cm-uct213d1/?lang=en>

### Technical Specifications

|                             |                |
|-----------------------------|----------------|
| Type                        | Take-Up Unit   |
| Bearing Type                | Ball Bearing   |
| Locking Device              | Set Screw      |
| Seal Type                   | Contact        |
| Seal Material               | Nitrile Rubber |
| Bearing Number              | UC213D1        |
| Housing Number              | CM-T213D1      |
| Housing Material            | Cast Iron      |
| Performance                 | Light Duty     |
| Dynamic Load Rating         | 57500 N        |
| Static Load Rating          | 40000 N        |
| Rotational Speed [Max]      | 2400.0 RPM     |
| Weight                      | 8.400 kg       |
| Operating Temperature Range | -40 to 120 °C  |
| Lubrication                 | Relubricatable |

### Dimensional Specifications

|    |            |
|----|------------|
| d  | 65.000 mm  |
| L  | 224.0 mm   |
| H  | 167.0 mm   |
| A5 | 120.000 mm |
| H1 | 151.0 mm   |
| H2 | 111.0 mm   |
| L1 | 137.0 mm   |
| L2 | 23.0 mm    |
| L3 | 121.0 mm   |
| N  | 41.0 mm    |
| N1 | 32.0 mm    |
| N2 | 70.0 mm    |
| A  | 70.0 mm    |
| A1 | 26.0 mm    |
| A2 | 44.0 mm    |
| r  | 87.0 mm    |
| B  | 65.100 mm  |
| S  | 25.400 mm  |
| F  | 8.700 mm   |

## Specifications

|                               |                  |
|-------------------------------|------------------|
| Ball Material                 | Through Hardened |
| Outside Diameter              | 120.000 mm       |
| Bore Type                     | Cylindrical      |
| Clearance                     | CN               |
| Cage Material                 | Pressed Steel    |
| Precision Rating              | ISO Class 0      |
| Radial Dynamic Load Rating    | 57500 N          |
| Rotational Speed [Max]-Grease | 2250.0 RPM       |
| Radial Static Load Rating     | 40000 N          |

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

