



ITEM NUMBER

CM-UKFL216D1- WHEN-USED- WITH-HA2316

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Cast Dust Cover, Closed End, UKFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Cast Dust Cover, Closed End, UKFL Type

d
68,263 mm

Bore

D
 —
 Outside diameter

B
 —
 Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/cm-ukfl216d1-when-used-with-ha2316/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK216D1
Housing Number	CM-FL216D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Closed
Performance	Light Duty
Dynamic Load Rating	72500 N
Static Load Rating	53000 N
Weight	9.300 kg
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	68.263 mm
H	290.0 mm
L	180.0 mm
L1	183.0 mm
L2	90.0 mm
J	233.0 mm
A1	22.0 mm
A2	34.0 mm
A5	106.000 mm
N	25.0 mm
B1	78.000 mm
F	9.500 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

