



#### ITEM NUMBER

# CM-UKFL319D1- WHEN-USED- WITH-HE2319X

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Cast Dust Cover, Closed End, UKFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Cast Dust Cover, Closed End, UKFL Type

**d**  
**82,550 mm**

Bore

**D**  
—  
Outside diameter

**B**  
—  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/cm-ukfl319d1-when-used-with-he2319x/?lang=en>

## Technical Specifications

|                             |                             |
|-----------------------------|-----------------------------|
| Type                        | 2-Bolt Rhombus Flanged Unit |
| Bearing Type                | Ball Bearing                |
| Locking Device              | Adapter                     |
| Seal Type                   | Contact                     |
| Seal Material               | Nitrile Rubber              |
| Bearing Number              | UK319D1                     |
| Housing Number              | CM-FL319D1                  |
| Housing Material            | Cast Iron                   |
| Housing Construction        | 1 Piece                     |
| End Type                    | Closed                      |
| Performance                 | Heavy Duty                  |
| Dynamic Load Rating         | 153000 N                    |
| Static Load Rating          | 119000 N                    |
| Weight                      | 27.000 kg                   |
| Operating Temperature Range | -40 to 120 °C               |

## Dimensional Specifications

|    |            |
|----|------------|
| d  | 82.550 mm  |
| H  | 405.0 mm   |
| L  | 250.0 mm   |
| L1 | 260.0 mm   |
| L2 | 125.0 mm   |
| J  | 330.0 mm   |
| A1 | 40.0 mm    |
| A2 | 59.0 mm    |
| A5 | 149.000 mm |
| N  | 41.0 mm    |
| B1 | 90.000 mm  |
| F  | 12.800 mm  |

Notes

Sales drawing reflects  
"Bore Size w/o Adapter".  
They do not show the  
"d" dimension, which is the  
bore size with adapter

### CONTACT

Email: [infos@catson.com.vn](mailto:infos@catson.com.vn)

Website: [www.catson.vn](http://www.catson.vn)

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

