



ITEM NUMBER

CM-UKFLX10D1- WHEN-USED- WITH-HE2310X

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Cast Dust Cover, Closed End, UKFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Cast Dust Cover, Closed End, UKFL Type

d
44,450 mm

Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/cm-ukflx10d1-when-used-with-he2310x/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UKX10D1
Housing Number	CM-FLX10D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Closed
Performance	Medium Duty
Dynamic Load Rating	43500 N
Static Load Rating	29200 N
Weight	3.600 kg
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	44.450 mm
H	216.0 mm
L	133.0 mm
L1	133.5 mm
L2	66.5 mm
J	184.0 mm
A1	18.0 mm
A2	26.0 mm
A5	76.000 mm
N	19.0 mm
B1	55.000 mm
F	6.000 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

