




ITEM NUMBER

HPC100TR

Adapter Bearing - HP Type, Hex Bore,
Cylindrical O.D.

Farm Implement Bearings - Hex Bore

d
26 mm
Bore

D
62 mm
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/hpc100tr/?lang=en>

Technical Specifications

Type	Heavy Duty Disc Bearings
Bore Type	Hex
Outside Ring Type	Cylindrical
Material	Through Hardened Steel
Cage Type	Pressed
Cage Material	Steel
Ball Material	Steel
Seal Type	Contact
Seal Material	Nitrile Rubber
Precision Rating	ISO Class 0
Configuration	One
Lubrication	Outer Ring
Clearance	C3
Static Load Rating	11300 N
Dynamic Load Rating	19500 N
Enclosure	Double Sealed
Weight	0.360 kg

Operating Temperature Range

-40 to 120 °C

Dimensional Specifications

H (0.0050/0)	29.234 mm
D	62.000 mm
C (0/-0.0047)	18.000 mm
B (0/-0.0047)	24.000 mm
d	26.000 mm
R	1.000 mm
Shaft Size	25.400 mm

Specifications

Ball Material	Through Hardened
Lubrication	Outer Ring
Radial Dynamic Load Rating	19500 N
Radial Static Load Rating	11300 N

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

