



#### ITEM NUMBER

# MUB1309TM

Cylindrical Roller Bearing - Non-Separable, Inner Ring w/ Two Ribs, Outer Ring w/ Two Retaining Rings

Single Row Cylindrical Roller Bearings - Non-Separable Type

|          |                  |          |
|----------|------------------|----------|
| <b>d</b> | <b>D</b>         | <b>B</b> |
| —        | 100 mm           | 45 mm    |
| Bore     | Outside diameter | Width    |

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/mub1309tm/?lang=en>

## Technical Specifications

|                             |                            |
|-----------------------------|----------------------------|
| Type                        | Cylindrical Roller Bearing |
| Bore Type                   | Round                      |
| Material                    | Hardened Alloy Steel       |
| Cage Material               | Pressed Steel              |
| Configuration               | One                        |
| Tolerance                   | ISO Class 0 (RBEC 1)       |
| Oil Hole                    | w/o Oil Hole               |
| Radial Internal Clearance   | CN                         |
| Static Load Rating          | 137000 N                   |
| Dynamic Load Rating         | 118000 N                   |
| Enclosure                   | Open                       |
| Weight                      | 0.990 kg                   |
| Operating Temperature Range | -40 to 120 °C              |

## Dimensional Specifications

|   |            |
|---|------------|
| B | 45.000 mm  |
| D | 100.000 mm |

|                 |           |
|-----------------|-----------|
| W               | 25.000 mm |
| C               | 86.110 mm |
| F               | 64.130 mm |
| R               | 3.960 mm  |
| U (Plain Rings) | 55.900 mm |
| V (Rib Rings)   | 59.200 mm |
| X (Plain Rings) | 90.400 mm |
| Z (Rib Rings)   | 86.100 mm |
| r               | 3.960 mm  |

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

