



ITEM NUMBER

N1012HSLK

Cylindrical Roller Bearing w/ Tapered Bore -
Inner Ring w/ Two Ribs, Plain Outer Ring

ISO Series Single Row Cylindrical Roller Bearings

d
60 mm
Bore

D
95 mm
Outside diameter

B
18 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/n1012hslk/?lang=en>

Technical Specifications

Type	Cylindrical Roller Bearing
Bore Type	Tapered
Material	Hardened Alloy Steel
Cage Material	PEEK
Limiting Speed - Grease	28900 RPM
Taper	1:12
Bearing Design	Tapered Bore
Precision	ISO Class 0
Configuration	One
Oil Hole	w/o Oil Hole
Radial Internal Clearance	CN
Static Load Rating	28900 N
Dynamic Load Rating	23800 N
Enclosure	Open
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	60.000 mm
D	95.000 mm
B	18.000 mm
Ew	86.100 mm
r	1.100 mm
da min	66.500 mm
db min	87.000 mm
Db max	88.500 mm
Db min	87.000 mm
r1as max	1.000 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

