



#### ITEM NUMBER

# N2328

Cylindrical Roller Bearing - Inner Ring w/ Two Ribs, Separable, Plain Outer Ring - N Type

ISO Series Single Row Cylindrical Roller Bearings

**d**  
**140 mm**  
Bore

**D**  
**300 mm**  
Outside diameter

**B**  
**102 mm**  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/n2328/?lang=en>

## Technical Specifications

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| Type                      | Cylindrical Roller Bearing                                  |
| Bore Type                 | Round                                                       |
| Material                  | Hardened Alloy Steel                                        |
| Cage Material             | High Strength Machined Brass Rivetless Cage w/ Square Holes |
| Limiting Speed - Oil      | 2300.0 RPM                                                  |
| Limiting Speed - Grease   | 2000 RPM                                                    |
| Precision                 | ISO Class 0                                                 |
| Configuration             | One                                                         |
| Oil Hole                  | w/o Oil Hole                                                |
| Radial Internal Clearance | CN                                                          |
| Static Load Rating        | 1250000 N                                                   |
| Dynamic Load Rating       | 920000 N                                                    |
| Enclosure                 | Open                                                        |

## Dimensional Specifications

|   |            |
|---|------------|
| d | 140.000 mm |
| D | 300.000 mm |

|          |            |
|----------|------------|
| B        | 102.000 mm |
| Ew       | 260.000 mm |
| J        | 196.000 mm |
| r        | 4.000 mm   |
| da min   | 156.000 mm |
| db min   | 156.000 mm |
| Da max   | 284.000 mm |
| Db max   | 284.000 mm |
| Db min   | 284.000 mm |
| r1as max | 4.000 mm   |

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

