



ITEM NUMBER

S-UCFL212D1

Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, Pressed Steel Dust Cover, Open End, UCFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, Pressed Steel Dust Cover, Open End, UCFL Type

d
60 mm
Bore

D
—
Outside diameter

B
65,100 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/s-ucfl212d1/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UC212D1
Housing Number	S-FL212D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	52500 N
Static Load Rating	36000 N
Rotational Speed [Max]	2500.0 RPM
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	60.000 mm
H	250.0 mm
L	140.0 mm
J	202.0 mm
A	48.0 mm
A1	18.0 mm
A2	29.0 mm
A4	80.000 mm
N	23.0 mm
B	65.100 mm
S	25.400 mm
F	6.200 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

