



ITEM NUMBER

S-UKFL209D1- WHEN-USED- WITH-HA2309

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Open End, UKFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Open End, UKFL Type

d
36,513 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/s-ukfl209d1-when-used-with-ha2309/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK209D1
Housing Number	S-FL209D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	32500 N
Static Load Rating	20400 N
Weight	2.100 kg

Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	36.513 mm
H	188.0 mm
L	108.0 mm
J	148.0 mm
A	38.0 mm
A1	16.0 mm
A2	22.0 mm
A4	63.000 mm
N	19.0 mm
B1	50.000 mm
F	4.900 mm

Notes	Sales drawing reflects "Bore Size w/o Adapter". They do not show the "d" dimension, which is the bore size with adapter
-------	--

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

