



ITEM NUMBER

SFCW2215-207N
1

Sealed Spherical Flange Blocks, SFCW Type

Sealed Spherical Flange Blocks, SFCW Type

d
61,913 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sfcw2215-207n1/?lang=en>

Technical Specifications

Type	4-Bolt Round Flanged Unit
Bearing Type	Spherical Roller Bearing
Locking Device	Adapter
Seal Material	Nitrile Rubber
Bearing Number	MX-W22215EALLKW33C3
Housing Number	SFC215N1
Adapter Sleeve Number	HA2315M1
Housing Material	Ductile Iron
Housing Construction	1 Piece
Performance	Heavy Duty
End Type	Open
Dynamic Load Rating	244000 N
Static Load Rating	249000 N
Rotational Speed [Max]	2000.0 RPM
Operating Temperature Range	-40 to 200 °C
Lubrication	Relubricatable

Guidelines for Mounting

Axial Displacement - Min.	0.024 in
Axial Displacement - Max.	0.030 in
Recommended Locknut Rotation	120 °
Hydraulic Pressure - Min.	1800 lb/in ²
Hydraulic Pressure - Max.	2250 lb/in ²

Shaft Tolerance

Shaft Tolerance	nominal to -74 µm
-----------------	-------------------

Dimensional Specifications

d	61.913 mm
a	255.0 mm
b	72.0 mm
c	24.0 mm
m	215.0 mm
f	170.0 mm
j	32.0 mm
s	17.0 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

