



ITEM NUMBER

SM-UCFLX05D1

Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, Pressed Steel Dust Cover, Closed End, UCFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, Pressed Steel Dust Cover, Closed End, UCFL Type

d
25 mm
Bore

D
—
Outside diameter

B
38,100 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sm-ucflx05d1/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UCX05D1
Housing Number	SM-FLX05D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Closed
Performance	Medium Duty
Dynamic Load Rating	19500 N
Static Load Rating	11300 N
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	25.000 mm
H	141.0 mm
L	83.0 mm
J	117.0 mm
A	30.0 mm
A1	13.0 mm
A2	18.0 mm
A4	49.000 mm
N	12.0 mm
B	38.100 mm
S	15.900 mm
F	4.600 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

