



ITEM NUMBER

SM-UCFLX10D1

Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, Pressed Steel Dust Cover, Closed End, UCFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, Pressed Steel Dust Cover, Closed End, UCFL Type

d
50 mm
Bore

D
—
Outside diameter

B
55,600 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sm-ucflx10d1/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UCX10D1
Housing Number	SM-FLX10D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Closed
Performance	Medium Duty
Dynamic Load Rating	43500 N
Static Load Rating	29200 N
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	50.000 mm
H	216.0 mm
L	133.0 mm
J	184.0 mm
A	44.0 mm
A1	18.0 mm
A2	26.0 mm
A4	71.000 mm
N	19.0 mm
B	55.600 mm
S	22.200 mm
F	6.000 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

