



ITEM NUMBER

SM-UKFL213D1- WHEN-USED- WITH-HS2313X

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Closed End, UKFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Closed End, UKFL Type

d 60,325 mm Bore	D — Outside diameter	B — Width
--------------------------------------	-----------------------------------	------------------------

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sm-ukfl213d1-when-used-with-hs2313x/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK213D1
Housing Number	SM-FL213D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Closed
Performance	Light Duty
Dynamic Load Rating	57500 N
Static Load Rating	40000 N
Weight	5.400 kg

Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	60.325 mm
H	258.0 mm
L	155.0 mm
J	210.0 mm
A	50.0 mm
A1	22.0 mm
A2	30.0 mm
A4	83.500 mm
N	23.0 mm
B1	65.000 mm
F	8.700 mm

Notes	Sales drawing reflects "Bore Size w/o Adapter". They do not show the "d" dimension, which is the bore size with adapter
-------	--

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

