



ITEM NUMBER

SM-UKT209D1- WHEN-USED- WITH-HA2309

Take-Up Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Closed End, UKT Type

Take-Up Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Closed End, UKT Type

d
36,513 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sm-ukt209d1-when-used-with-ha2309/?lang=en>

Technical Specifications

Type	Take-Up Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK209D1
Housing Number	SM-T209D1
Housing Material	Cast Iron
Performance	Light Duty
Dynamic Load Rating	32500 N
Static Load Rating	20400 N
Weight	2.500 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	36.513 mm
L	145.0 mm
H	117.0 mm
A4	82.000 mm
H1	102.0 mm
H2	83.0 mm
L1	88.0 mm
L2	18.0 mm
L3	83.0 mm
N	16.0 mm
N1	29.0 mm
N2	19.0 mm
A	49.0 mm
A1	49.0 mm
A2	35.0 mm
r	57.0 mm
B1	50.000 mm
F	4.900 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

