



#### ITEM NUMBER

# SM-UKT211D1- WHEN-USED- WITH-H2311X

Take-Up Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Closed End, UKT Type

Take-Up Unit, Cast Housing, Adapter, Pressed Steel Dust Cover, Closed End, UKT Type

**d**  
**50 mm**  
Bore

**D**  
—  
Outside diameter

**B**  
—  
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sm-ukt211d1-when-used-with-h2311x/?lang=en>

## Technical Specifications

|                             |                |
|-----------------------------|----------------|
| Type                        | Take-Up Unit   |
| Bearing Type                | Ball Bearing   |
| Locking Device              | Adapter        |
| Seal Type                   | Contact        |
| Seal Material               | Nitrile Rubber |
| Bearing Number              | UK211D1        |
| Housing Number              | SM-T211D1      |
| Housing Material            | Cast Iron      |
| Performance                 | Light Duty     |
| Dynamic Load Rating         | 43500 N        |
| Static Load Rating          | 29200 N        |
| Weight                      | 4.100 kg       |
| Operating Temperature Range | -40 to 120 °C  |
| Lubrication                 | Relubricatable |

## Dimensional Specifications

|    |           |
|----|-----------|
| d  | 50.000 mm |
| L  | 171.0 mm  |
| H  | 146.0 mm  |
| A4 | 92.000 mm |
| H1 | 130.0 mm  |
| H2 | 102.0 mm  |
| L1 | 106.0 mm  |
| L2 | 21.0 mm   |
| L3 | 95.0 mm   |
| N  | 22.0 mm   |
| N1 | 35.0 mm   |
| N2 | 25.0 mm   |
| A  | 64.0 mm   |
| A1 | 64.0 mm   |
| A2 | 38.0 mm   |
| r  | 65.0 mm   |
| B1 | 59.000 mm |
| F  | 6.000 mm  |

Notes

Sales drawing reflects  
"Bore Size w/o Adapter".  
They do not show the  
"d" dimension, which is the  
bore size with adapter

## CONTACT

**Email:** [infos@catson.com.vn](mailto:infos@catson.com.vn)

**Website:** [www.catson.vn](http://www.catson.vn)

**Phone:** +84 28 3820 8888

**Fax:** +84 28 3826 8888

