




ITEM NUMBER

SPAW2226-408N
1

Sealed Spherical Pillow Blocks, SPAW Type

Sealed Spherical Pillow Blocks, SPAW/SPW Type

d
114,300 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/spaw2226-408n1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Spherical Roller Bearing
Seal Material	Nitrile Rubber
Locking Device	Adapter
Bearing Number	MX-W22226EALLKW33C3
Housing Number	SPA226N1
Adapter Sleeve Number	HE2326M1
Housing Material	Ductile Iron
Housing Construction	1 Piece
Mounting Type	4-Bolt
Performance	Heavy Duty
End Type	Open
Dynamic Load Rating	808000 N
Static Load Rating	898000 N
Rotational Speed [Max]	1200 RPM
Weight	45.813 kg
Operating Temperature Range	-40 to 200 °C

Guidelines for Mounting

Axial Displacement - Min.	0.043 in
Axial Displacement - Max.	0.055 in
Recommended Locknut Rotation	210 °
Hydraulic Pressure - Min.	3250 lb/in ²
Hydraulic Pressure - Max.	4500 lb/in ²

Shaft Tolerance

Shaft Tolerance	nominal to -87 µm
-----------------	-------------------

Allowable Loads

Allowable Loads - P60	77000 lb
Allowable Loads - P90	48500 lb
Allowable Loads - P120	26500 lb
Allowable Loads - P150	24000 lb
Allowable Loads - P180	26500 lb

Dimensional Specifications

d	114.300 mm
h	152.4 mm
a	467.0 mm
b	115.0 mm
b1	130.0 mm
c	52.0 mm
m	388.9 mm
m1	82.6 mm
w	295.0 mm
u	24.0 mm
v	39.7 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

