




ITEM NUMBER

SPW2226-408N1

Sealed Spherical Pillow Blocks, SPW Type

Sealed Spherical Pillow Blocks, SPAW/SPW Type

d
114,300 mm
 Bore

D
 —
 Outside diameter

B
 —
 Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/spw2226-408n1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Spherical Roller Bearing
Seal Material	Nitrile Rubber
Locking Device	Adapter
Bearing Number	MX-W22226EALLKW33C3
Housing Number	SP226N1
Adapter Sleeve Number	HE2326M1
Housing Material	Ductile Iron
Housing Construction	1 Piece
Mounting Type	2-Bolt
Performance	Heavy Duty
End Type	Open
Dynamic Load Rating	808000 N
Static Load Rating	898000 N
Rotational Speed [Max]	1200 RPM
Weight	45.810 kg
Operating Temperature Range	-40 to 200 °C

Guidelines for Mounting

Axial Displacement - Min.	0.043 in
Axial Displacement - Max.	0.047 in
Recommended Locknut Rotation	180 °

Allowable Loads

Allowable Loads - P60	77000 lb
Allowable Loads - P90	48500 lb
Allowable Loads - P120	26500 lb
Allowable Loads - P150	24000 lb
Allowable Loads - P180	26500 lb

Dimensional Specifications

d	114.300 mm
h	150.0 mm
a	445.0 mm
b	115.0 mm
b1	130.0 mm
c	50.0 mm
m	380.0 mm
w	293.0 mm
u	28.0 mm
v	36.0 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888



--	--