



ITEM NUMBER

SUCPA210

Tapped-Base Pillow Block Unit, Stainless Steel
Housing, Set Screw, SUCPA Type

Tapped-Base Pillow Block Unit, Stainless Steel
Housing, Set Screw, SUCPA Type

d
50 mm
Bore

D
—
Outside diameter

B
51,600 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/sucpa210/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Silicone
Bearing Number	SUC210
Housing Number	SPA210N
Insert Material	Stainless Steel
Housing Material	Stainless Steel
Performance	Normal Duty
End Type	Open
Dynamic Load Rating	27500 N
Static Load Rating	23700 N
Rotational Speed [Max]	2900 RPM
Weight	2.890 kg
Operating Temperature Range	-20 to 120 °C
Lubrication	Outer Ring

Dimensional Specifications

d	50.000 mm
J	101.6 mm
L	140.0 mm
A	51.0 mm
H	57.2 mm
H1	13.0 mm
H2	117.0 mm
N	M16
E	19.0 mm
B	51.600 mm
S	19.000 mm

Specifications

Lubrication	Outer Ring
Ball Material	Stainless Steel
Outside Diameter	90.000 mm
Bore Type	Cylindrical
Outside Ring Width	24.000 mm
Inside Ring Width	51.600 mm
Clearance	CN
Cage Material	Stainless Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	27500 N
Radial Static Load Rating	23700 N
Rotational Speed [Max]-Grease	4800 RPM

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

