



ITEM NUMBER

SUCTBL208-24F G1

Tapped-Base Pillow Block Unit, Thermoplastic
Housing, Set Screw, SUCTBL Type

Tapped-Base Pillow Block Unit, Thermoplastic
Housing, Set Screw, SUCTBL Type

d
38,100 mm
Bore

D
—
Outside diameter

B
49,200 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/suctbl208-24fg1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Silicone
Bearing Number	SUC208-24FG1
Housing Number	WTBLI208
Insert Material	Stainless Steel
Housing Material	Thermoplastic
Performance	Normal Duty
End Type	Open
Dynamic Load Rating	22800 N
Static Load Rating	18200 N
Rotational Speed [Max]	3300 RPM
Weight	0.980 kg
Operating Temperature Range	-20 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	38.100 mm
J	88.9 mm
L	120.0 mm
A	48.0 mm
H	49.2 mm
H1	22.5 mm
H2	100.5 mm
N	1/2
E	16.0 mm
B	49.200 mm
S	19.000 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

