



ITEM NUMBER

UCPG211D1

Pillow Block Unit, Set Screw, Steel Housing, UCPG Type

Pillow Block Unit, Set Screw, Steel Housing, UCPG Type

d
55 mm
Bore

D
—
Outside diameter

B
55,600 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ucpg211d1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UC211D1
Housing Number	PG211D1
Housing Material	Steel
Performance	Light Duty
End Type	Open
Dynamic Load Rating	43500 N
Static Load Rating	29200 N
Rotational Speed [Max]	2900 RPM
Weight	3.900 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Outer Ring

Dimensional Specifications

d	55.000 mm
J	171.0 mm
L	219.0 mm
A	45.0 mm
H	63.5 mm
H1	23.0 mm
H2	126.0 mm
N	19.0 mm
B	55.600 mm
S	22.200 mm
F	6.000 mm

Specifications

Lubrication	Outer Ring
Ball Material	Through Hardened
Outside Diameter	100.000 mm
Bore Type	Cylindrical
Outside Ring Width	25.000 mm
Inside Ring Width	55.600 mm
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	43500 N
Radial Static Load Rating	29200 N
Rotational Speed [Max]-Grease	2850 RPM

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

