



ITEM NUMBER

UCPX05D1

Pillow Block Unit, Cast Housing, Set Screw,
UCP/UCPX Type

Pillow Block Unit, Cast Housing, Set Screw, UCP/
UCPX Type

d
25 mm
Bore

D
—
Outside diameter

B
38,100 mm
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ucpx05d1/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UCX05D1
Housing Number	PX05D1
Housing Material	Cast Iron
Housing Construction	1 Piece
Performance	Medium Duty
End Type	Open
Dynamic Load Rating	19500 N
Static Load Rating	11300 N
Weight	1.020 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Outer Ring

Dimensional Specifications

d	25.000 mm
J	119.0 mm
L	159.0 mm
A	51.0 mm
H	44.4 mm
H1	18.0 mm
H2	85.0 mm
L1	50.0 mm
N	17.0 mm
N1	20.0 mm
B	38.100 mm
S	15.900 mm
F	4.600 mm

Specifications

Lubrication	Outer Ring
Ball Material	Through Hardened
Outside Diameter	62.000 mm
Bore Type	Cylindrical
Outside Ring Width	19.000 mm
Inside Ring Width	38.100 mm
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	19500 N
Radial Static Load Rating	11300 N
Rotational Speed [Max]-Grease	4000 RPM

CONTACT

Email: infos@catson.com.vn



Website: www.catson.vn Phone: +84 28 3820 8888 Fax: +84 28 3826 8888	
--	--