



ITEM NUMBER

UELFLU-1-3-8

Ultra-Class Two Bolt Flanged Unit with Eccentric Lock, UELFLU Type

Ultra-Class Two Bolt Flanged Unit with Eccentric Lock

d
34,925 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/uelflu-1-3-8/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Eccentric Locking Collar
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	A-UEL207-106D1
Housing Number	FLU207D1V50
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Finish/Coating	Black Oxide
Performance	Light Duty
Dynamic Load Rating	25700 N
Static Load Rating	15300 N
Max Tightening Torque	104 lb·in
Rotational Speed [Max]	4200 RPM
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	34.925 mm
H	156.4 mm
E	130.2 mm
L	96.0 mm
A	35.7 mm
A0	53.200 mm
A1	16.7 mm
A2	21.0 mm
N	13.1 mm
B1	51.100 mm
S	18.800 mm
F	4.600 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

