



ITEM NUMBER

UELPL-2-3-4

Ultra-Class Pillow Block Unit with Eccentric Locking Collar, Low Base, UELPL Type

Ultra-Class Pillow Block Unit with Eccentric Locking Collar

d
69,850 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/uelpl-2-3-4/?lang=en>

Technical Specifications

Type	Pillow Block Unit
Bearing Type	Ball Bearing
Locking Device	Eccentric Locking Collar
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	A-UEL214-212D1
Housing Number	PL214D1V50
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Finish/Coating	Black Oxide
Performance	Heavy Duty
Dynamic Load Rating	62000 N
Static Load Rating	44000 N
Max Tightening Torque	260 lb·in
Rotational Speed [Max]	2250.0 RPM
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	69.850 mm
J	203.2 mm
L	265.9 mm
A	72.2 mm
H	76.2 mm
H1	27.0 mm
H2	154.0 mm
N	20.6 mm
N1	34.9 mm
L1	77.0 mm
B1	85.700 mm
S	34.150 mm
F	8.800 mm

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

