



ITEM NUMBER

UKFL306D1- WHEN-USED- WITH-H2306X

Two Bolt Rhombus Flanged Unit, Cast Housing,
Adapter, UKFL Type

Two Bolt Rhombus Flanged Unit, Cast Housing,
Adapter, UKFL Type

d
25 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ukfl306d1-when-used-with-h2306x/?lang=en>

Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK306D1
Housing Number	FL306D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Heavy Duty
Dynamic Load Rating	26700 N
Static Load Rating	15000 N
Weight	1.500 kg
Operating Temperature Range	-40 to 120 °C

Dimensional Specifications

d	25.000 mm
H	180.0 mm
L	90.0 mm
J	134.0 mm
A	32.0 mm
A0	40.500 mm
A1	15.0 mm
A2	18.0 mm
N	23.0 mm
B1	38.000 mm
F	5.900 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

