



ITEM NUMBER

UKFS306D1- WHEN-USED- WITH-H2306X

Four Bolt Square Flanged Unit, Cast Housing,
Adapter, UKFS Type

Four Bolt Square Flanged Unit, Cast Housing,
Adapter, UKFS Type

d
25 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ukfs306d1-when-used-with-h2306x/?lang=en>

Technical Specifications

Type	4-Bolt Square Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK306D1
Adapter Number	H2306X
Housing Number	FS306D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Heavy Duty
Dynamic Load Rating	26700 N
Static Load Rating	15000 N
Weight	1.800 kg

Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	25.000 mm
L	125.0 mm
J	95.0 mm
A	32.0 mm
A0	40.500 mm
A1	15.0 mm
A2	10.000 mm
A3	8.0 mm
H3	90.0 mm
N	16.0 mm
B1	38.000 mm
F	5.900 mm

Notes	Sales drawing reflects "Bore Size w/o Adapter". They do not show the "d" dimension, which is the bore size with adapter
-------	--

CONTACT Email: infos@catson.com.vn Website: www.catson.vn Phone: +84 28 3820 8888 Fax: +84 28 3826 8888	
---	---