



ITEM NUMBER

UKFS308D1- WHEN-USED- WITH-H2308X

Four Bolt Square Flanged Unit, Cast Housing,
Adapter, UKFS Type

Four Bolt Square Flanged Unit, Cast Housing,
Adapter, UKFS Type

d
35 mm
Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ukfs308d1-when-used-with-h2308x/?lang=en>

Technical Specifications

Type	4-Bolt Square Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK308D1
Adapter Number	H2308X
Housing Number	FS308D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Heavy Duty
Dynamic Load Rating	40500 N
Static Load Rating	24000 N
Weight	3.200 kg

Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	35.000 mm
L	150.0 mm
J	112.0 mm
A	40.0 mm
A0	50.000 mm
A1	17.0 mm
A2	13.000 mm
A3	10.0 mm
H3	115.0 mm
N	19.0 mm
B1	46.000 mm
F	7.400 mm

Notes	Sales drawing reflects "Bore Size w/o Adapter". They do not show the "d" dimension, which is the bore size with adapter
-------	--

CONTACT Email: infos@catson.com.vn Website: www.catson.vn Phone: +84 28 3820 8888 Fax: +84 28 3826 8888	
---	---