



ITEM NUMBER

UKT216D1- WHEN-USED- WITH-HA2316

Take-Up Unit, Cast Housing, Adapter, UKT Type

Take-Up Unit, Cast Housing, Adapter, UKT Type

d
68,263 mm

Bore

D
—
Outside diameter

B
—
Width

View details: <https://catson.vn/tra-cuu-vong-bi/ntn/ukt216d1-when-used-with-ha2316/?lang=en>

Technical Specifications

Type	Take-Up Unit
Bearing Type	Ball Bearing
Locking Device	Adapter
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UK216D1
Housing Number	T216D1
Housing Material	Cast Iron
Dynamic Load Rating	72500 N
Static Load Rating	53000 N
Weight	8.700 kg
Operating Temperature Range	-40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications

d	68.263 mm
L	235.0 mm

H	184.0 mm
H1	165.0 mm
H2	111.0 mm
L1	140.0 mm
L2	23.0 mm
L3	121.0 mm
N	41.0 mm
N1	32.0 mm
N2	70.0 mm
A	70.0 mm
A1	26.0 mm
A2	51.0 mm
r	95.0 mm
B1	78.000 mm
F	9.500 mm

Notes

Sales drawing reflects
"Bore Size w/o Adapter".
They do not show the
"d" dimension, which is the
bore size with adapter

CONTACT

Email: infos@catson.com.vn

Website: www.catson.vn

Phone: +84 28 3820 8888

Fax: +84 28 3826 8888

