

MOUNTING PASTE – ANTI-FRETTING AGENT

The NTN-SNR mounting paste is specially designed to prevent contact rust, wear and fretting corrosion between 2 metal surfaces.

36

It is an innovative heavy metal free paste, which is safe for the environment.



APPLICATIONS

- Contact corrosion, also known as fretting corrosion, appears in assemblies subjected to vibration or very slight slippage or oscillation. It can lead to the serious deterioration of bearings and other machine components and thus make dismantling very difficult.

ADVANTAGES

- Allows slippage for assemblies with play (wheel bearings, vibrating screens, etc.).
- Preserves the quality of the surfaces and the adjustment of mechanical assemblies by preventing contact (fretting) corrosion.
- Facilitates the mounting and dismantling of bearings and components such as nuts, bolts, pins, flanges, couplings, fluted shafts, etc.
- Water and washing resistant.
- Cost saving considering its light density (0.910) and subsequently lower consumption.
- Grease without heavy metals (Zn, Cu, Pb) and powdered graphite.
- Temperature range for use -30°C to +145°C.

COMMERCIAL REFERENCES

LUB MOUNTING PASTE / T 60G
LUB MOUNTING PASTE / B 500G

ADJUSTABLE SPANNERS

10 spanners for tightening and loosening up to 30 differently sized nuts!

36



APPLICATIONS

- NTN-SNR adjustable spanners enable the safe and effortless tightening and loosening of all KM, KML and KMK type nuts and also B, TB, BR and TBR precision nuts. They avoid any damage to the nuts or the shaft.


ADVANTAGES

- Made of special tempered steel, these spanners are extremely strong.
- The joint with its spring washer guarantees gentle reliable operation.
- The laser-etched imprint makes them easily and permanently identifiable.
- The hole in the handle makes them easy to store.
- They are adaptable to cover nut diameters from 15 to 180 mm.

Available in two versions:

With pins for nuts with holes

With hook for slotted nuts



COMMERCIAL REFERENCES

TOOL PS (size) / Pin Spanner (with pin)
TOOL HS (size) / Hook Spanner (with hook)